

Separate Sheet

Product Specifications of the R-Car W1R and R-Car W2H

R-Car W1R

Part Number	R-Car W1R (uPD35901)
Standard	ARIB STD-T109 (Rev.1.2) PHY/MAC protocol
Frequency Band	760 MHz
Power Supply Voltage	3.3 V (IO), 1.2 V (Core)
CPU Core	32 bit (operating frequency 160MHz)
Built-in Memory	RAM: 128 KB, ROM: 32 KB
Host Interface	SDIO
Memory Interface	I ² C
Package	176-pin Plastic FBGA 10mm x 10mm /0.65 ball pitch
Operating Temperature	T _a =-40°C - +85°C (JEDEC JESD 51-9), T _j = -40°C - +125°C

R-Car W2H

Part Number	R-Car W2H (R8A77460)	
Power Supply Voltage	1.8 V: (SD and JTAG), 1.2 V: (Core), 1.5 V: (DDR3-I/O SSTL), 2.5 V: (PCI-express), 3.3 V: (Others)	
CPU Core	ARM® Cortex®-A7 Dual	SH-4AL
Cache memory	L1 Instruction cache: 32 KB L1 Data cache: 32 KB L2 Cache: 512 KB	Cache memory
External memory	<ul style="list-style-type: none"> ·Flash ROM and SRAM ·Data bus width: 32 bit 	
Storage interface	<ul style="list-style-type: none"> ·SD card host interface ·USB 2.0 host/ function interface 	
External communication interface	<ul style="list-style-type: none"> ·PCI Express interface ·Control area network(CAN) interface 	
V2X Security function	<ul style="list-style-type: none"> High speed ECDSA engine NIST P-256 - 512, Brainpool support NIST / Brainpool Dynamic switching AES 128 – 256 support RSA, HASH, TRNG 	

Package	501-pin FC-BGA 21 mm x 21 mm /0.80 ball pitch
Operating temperature	T _a = -40°C - +85°C (JEDEC JESD 51-9), T _c = -40°C - +115°C

###

(Remarks) All registered trademarks or trademarks are the property of their respective owners.