

# CE Radio Test Report

**Project No.** : 1910C137C  
**Equipment** : WiFi Module  
**Brand Name** : Dialog  
**Test Model** : DA16200MOD-AAE4WA32  
**Series Model** : N/A  
**Applicant** : Renesas Design Korea Inc.  
**Address** : B-7F, 35, Pangyo-ro 255beon-gil, Bundang-gu, Seongnam-si,  
Gyeonggi-do (Zip 13486), Republic of Korea  
**Manufacturer** : Iton Technology Corp.  
**Address** : 7 FLOOR EAST, BUILDING C, NO1006 SHENNAN ROAD SHENZHEN  
INTERNATIONAL INNOVATION CENTER (FUTIAN TECHNOLOGY  
SQUARE), HUAFU STREET, FUTIAN DISTRICT, SHENZHEN  
GUANGDONG CHINA  
**Factory** : Iton Technology Corp.  
**Address** : 7 FLOOR EAST, BUILDING C, NO1006 SHENNAN ROAD SHENZHEN  
INTERNATIONAL INNOVATION CENTER (FUTIAN TECHNOLOGY  
SQUARE), HUAFU STREET, FUTIAN DISTRICT, SHENZHEN  
GUANGDONG CHINA  
**Date of Receipt** : Nov. 07, 2019  
Nov. 29, 2021  
**Date of Test** : Nov. 08, 2019 ~ Nov. 28, 2019  
Dec. 01, 2021 ~ Dec. 07, 2021  
**Issued Date** : Jul. 30, 2024  
**Report Version** : R00  
**Test Sample** : Engineering Sample No.: DG2019110652, DG2021113048 for Receiver  
blocking.  
**Standard(s)** : ETSI EN 300 328 V2.2.2 (2019-07)

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

**Prepared by** :

*Evan Yang*

Evan Yang

**Approved by** :

*Chay . Cai*

Chay Cai

Room 108, Building 2, No.1, Yile Road, Songshan Lake Zone, Dongguan City, Guangdong,  
People's Republic of China

Tel: +86-769-8318-3000 Web: [www.newbtl.com](http://www.newbtl.com) Service mail: [btl\\_qa@newbtl.com](mailto:btl_qa@newbtl.com)

**Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** assumes no responsibility for the data provided by the customer, any statements, inferences or generalizations drawn by the customer or others from the reports issued by **BTL**.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

**BTL** is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

**Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

<b>Table of Contents</b>	<b>Page</b>
<b>REPORT ISSUED HISTORY</b>	<b>7</b>
<b>1 . RF EMISSIONS MEASUREMENT</b>	<b>8</b>
1.1 TEST FACILITY	8
1.2 MEASUREMENT UNCERTAINTY	8
1.3 TEST ENVIRONMENT CONDITIONS	8
1.4 TEST CHANNEL	8
1.5 TEST METHODOLOGY AND RESULT	9
<b>2 . GENERAL INFORMATION</b>	<b>10</b>
2.1 GENERAL DESCRIPTION OF EUT	10
2.2 DESCRIPTION OF TEST MODES	11
2.3 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	11
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	12
2.5 DESCRIPTION OF SUPPORT UNITS	12
<b>3 . RF OUTPUT POWER</b>	<b>13</b>
3.1 APPLIED PROCEDURES / LIMIT	13
3.2 TEST PROCEDURES	13
3.3 TEST SETUP LAYOUT	13
3.4 TEST DEVIATION	13
3.5 EUT OPERATION DURING TEST	13
3.6 TEST RESULTS	13
<b>4 . POWER SPECTRAL DENSITY</b>	<b>14</b>
4.1 APPLIED PROCEDURES / LIMIT	14
4.2 TEST PROCEDURES	14
4.3 TEST SETUP LAYOUT	14
4.4 TEST DEVIATION	14
4.5 EUT OPERATION DURING TEST	14
4.6 TEST RESULTS	14
<b>5 . DUTY CYCLE, TX-SEQUENCE, TX-GAP</b>	<b>15</b>
5.1 APPLIED PROCEDURES / LIMIT	15
5.2 TEST PROCEDURES	15
5.3 TEST SETUP LAYOUT	15
5.4 TEST DEVIATION	15

<b>Table of Contents</b>	<b>Page</b>
5.5 EUT OPERATION DURING TEST	15
5.6 TEST RESULTS	15
<b>6 . MEDIUM UTILISATION (MU) FACTOR</b>	<b>16</b>
6.1 APPLIED PROCEDURES / LIMIT	16
6.2 TEST PROCEDURES	16
6.3 TEST SETUP LAYOUT	16
6.4 TEST DEVIATION	16
6.5 EUT OPERATION DURING TEST	16
6.6 TEST RESULTS	16
<b>7 . ADAPTIVITY (ADAPTIVE EQUIPMENT USING MODULATIONS OTHER THAN FHSS)</b>	<b>17</b>
7.1 APPLIED PROCEDURES / LIMIT	17
7.2 TEST PROCEDURES	21
7.3 TEST SETUP LAYOUT	21
7.4 TEST DEVIATION	21
7.5 EUT OPERATION DURING TEST	21
7.6 TEST RESULTS	21
<b>8 . OCCUPIED CHANNEL BANDWIDTH</b>	<b>22</b>
8.1 APPLIED PROCEDURES / LIMIT	22
8.2 TEST PROCEDURES	22
8.3 TEST SETUP LAYOUT	22
8.4 TEST DEVIATION	22
8.5 EUT OPERATION DURING TEST	22
8.6 TEST RESULTS	22
<b>9 . TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN</b>	<b>23</b>
9.1 APPLIED PROCEDURES / LIMIT	23
9.2 TEST PROCEDURES	23
9.3 TEST SETUP LAYOUT	23
9.4 TEST DEVIATION	23
9.5 EUT OPERATION DURING TEST	23
9.6 TEST RESULTS	23
<b>10 . TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN</b>	<b>24</b>
10.1 APPLIED PROCEDURES / LIMIT	24

<b>Table of Contents</b>	<b>Page</b>
10.2 TEST PROCEDURES	24
10.3 TEST SETUP LAYOUT	25
10.4 TEST DEVIATION	25
10.5 EUT OPERATION DURING TEST	25
10.6 TEST RESULTS	25
<b>11 . RECEIVER SPURIOUS EMISSIONS</b>	<b>26</b>
11.1 APPLIED PROCEDURES / LIMIT	26
11.2 TEST PROCEDURES	26
11.3 TEST SETUP LAYOUT	26
11.4 TEST DEVIATION	26
11.5 EUT OPERATION DURING TEST	26
11.6 TEST RESULTS	26
<b>12 . RECEIVER BLOCKING</b>	<b>27</b>
12.1 APPLIED PROCEDURES / LIMIT	27
12.2 TEST PROCEDURES	28
12.3 TEST SETUP LAYOUT	28
12.4 TEST DEVIATION	28
12.5 EUT OPERATION DURING TEST	28
12.6 TEST RESULTS	28
<b>13 . MEASUREMENT INSTRUMENTS LIST</b>	<b>29</b>
<b>14 . EUT TEST PHOTO</b>	<b>31</b>
<b>APPENDIX A - RF OUTPUT POWER</b>	<b>32</b>
<b>APPENDIX B - POWER SPECTRAL DENSITY</b>	<b>34</b>
<b>APPENDIX C - DUTY CYCLE, TX-SEQUENCE, TX-GAP</b>	<b>41</b>
<b>APPENDIX D - MEDIUM UTILISATION (MU) FACTOR</b>	<b>42</b>
<b>APPENDIX E - ADAPTIVITY</b>	<b>43</b>
<b>APPENDIX F - OCCUPIED CHANNEL BANDWIDTH</b>	<b>60</b>
<b>APPENDIX G - TRANSMITTER UNWANTED EMISSIONS IN THE OOB DOMAIN</b>	<b>64</b>
<b>APPENDIX H - TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN</b>	<b>68</b>

**Table of Contents****Page**

<b>APPENDIX I - RECEIVER SPURIOUS EMISSIONS</b>	<b>85</b>
<b>APPENDIX J - RECEIVER BLOCKING</b>	<b>94</b>
<b>APPENDIX K - INFORMATION AS REQUIRED BY</b>	<b>96</b>
<b>EN 300 328 V2.2.2, CLAUSE 5.4.1</b>	<b>96</b>

### REPORT ISSUED HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-ETSP-1-1910C137C	R00	This is a copy report which referencing test data are provided from test report (BTL-ETSP-1-1910C137B). The device is identical to the original one recorded in the referencing report. And in this report only update applicant information, manufacturer and factory address. Other are kept the same.	Jul. 30, 2024	Valid

Remark: For the original report (BTL-ETSP-1-1910C137B), the test data, data evaluation, and equipment configuration contained was accredited by the Authority of A2LA according to the ISO/IEC 17025 quality assessment standard and technical standard(s).

## 1. RF EMISSIONS MEASUREMENT

### 1.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-CB12/TR16/TR17** at the location of No.3, Jinshagang 1st Road, Dalang, Dongguan City, Guangdong People's Republic of China.

### 1.2 MEASUREMENT UNCERTAINTY

The measurement uncertainty figures shall be calculated according the methods described in the ETSI TR 100 028 and shall correspond to an expansion factor (coverage factor)  $k=1.96$  or  $k=2$ (which provide confidence levels of respectively 95% and 95.45% in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Measurement Uncertainty for a Level of Confidence of 95.45%,  $U=2 \times u_c(y)$ .

The BTL measurement uncertainty as below table:

Parameter	Uncertainty
Output Power	$\pm 0.95$ dB
Occupied Channel Bandwidth	$\pm 3.8$ %
Power Spectral Density	$\pm 0.86$ dB
Conducted Spurious Emission	$\pm 2.71$ dB
Spurious Emissions, Radiated $f \leq 1$ GHz	$\pm 3.38$ dB
Spurious Emissions, Radiated $1\text{GHz} < f \leq 12.75\text{GHz}$	$\pm 3.06$ dB
Temperature	$\pm 0.08$ °C
Time	$\pm 0.58$ %
Supply voltages	$\pm 0.3$ %

### 1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
RF Output Power	Normal & Extreme	52%	DC 3.3V	Grani Zhou
Power Spectral Density	24°C	52%	DC 3.3V	Grani Zhou
Adaptivity	24°C	52%	DC 3.3V	Grani Zhou
Occupied Channel Bandwidth	24°C	52%	DC 3.3V	Grani Zhou
Transmitter unwanted emissions in the OOB domain	24°C	52%	DC 3.3V	Grani Zhou
Transmitter unwanted emissions in the spurious domain	26°C	50%	DC 3.3V	Damon Deng
Receiver spurious emissions	26°C	50%	DC 3.3V	Damon Deng
Receiver Blocking	21.9°C	35.1%	DC 3.3V	King Huang

### 1.4 TEST CHANNEL

IEEE 802.11b/g/n(HT20)		
Test Channel	EUT Channel	Test Frequency
low	CH01	2412 MHz
middle	CH07	2442 MHz
high	CH13	2472 MHz

Note:

- (1) The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be stated by the supplier.



## 1.5 TEST METHODOLOGY AND RESULT

Harmonised Standard ETSI EN 300 328					
Essential Requirement			Requirement Conditionality		Result
No	Description	Reference: Clause No	U/C	Condition	
1	RF Output Power	4.3.1.2 or 4.3.2.2	U	-	Pass
2	Power Spectral Density	4.3.2.3	C	Only for non-FHSS equipment	Pass
3	Duty cycle, Tx-Sequence, Tx-gap	4.3.1.3 or 4.3.2.4	C	Only for non-Adaptive equipment	N/A
4	Accumulated Transmit time, Frequency Occupation & Hopping Sequence	4.3.1.4	C	Only for FHSS equipment	N/A
5	Hopping Frequency Separation	4.3.1.5	C	Only for FHSS equipment	N/A
6	Medium Utilization	4.3.1.6 or 4.3.2.5	C	Only for non-Adaptive equipment	N/A
7	Adaptivity	4.3.1.7 or 4.3.2.6	C	Only for Adaptive equipment	Pass
8	Occupied Channel Bandwidth	4.3.1.8 or 4.3.2.7	U	-	Pass
9	Transmitter unwanted emissions in the OOB domain	4.3.1.9 or 4.3.2.8	U	-	Pass
10	Transmitter unwanted emissions in the spurious domain	4.3.1.10 or 4.3.2.9	U	-	Pass
11	Receiver spurious emissions	4.3.1.11 or 4.3.2.10	U	-	Pass
12	Receiver Blocking	4.3.1.12 or 4.3.2.11	U	-	Pass
13	Geo-location capability	4.3.1.13 or 4.3.2.12	C	Only for equipment with geo-location capability	N/A

Note:

- (1) "U/C": Indicates whether the requirement is unconditionally applicable (U) or is conditional upon the manufacturer's claimed functionality of the equipment (C).
- (2) The geographical location would not be accessible to the user in a way that would allow the user to alter it.

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	WiFi Module
Brand Name	Dialog
Test Model	DA16200MOD-AAE4WA32
Series Model	N/A
Model Difference(s)	N/A
Power Source	DC voltage supplied from external power supply.
Power Rating	DC 3.3V
Operation Frequency	2412 MHz ~ 2472 MHz
Modulation Technology	IEEE 802.11b: DSSS IEEE 802.11g: OFDM IEEE 802.11n: OFDM
Bit Rate of Transmitter	IEEE 802.11b: 11/5.5/2/1 Mbps IEEE 802.11g: 54/48/36/24/18/12/9/6 Mbps IEEE 802.11n: up to 72.2 Mbps
Max. e.i.r.p.	IEEE 802.11b: 18.28 dBm IEEE 802.11g: 19.13 dBm IEEE 802.11n (HT20): 18.08 dBm
Categorization	<input checked="" type="checkbox"/> Receiver category 1 <input type="checkbox"/> Receiver category 2 <input type="checkbox"/> Receiver category 3

Note:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

#### 2. Channel List:

CH01 - CH13 for IEEE 802.11b, IEEE 802.11g, IEEE 802.11n(HT20)					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	06	2437	11	2462
02	2417	07	2442	12	2467
03	2422	08	2447	13	2472
04	2427	09	2452		
05	2432	10	2457		

#### 3. Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Dipole	N/A	2

Note: The antenna gain is provided by the manufacturer.

## 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test Items	Mode	Data Rate	Channel
RF Output Power	IEEE 802.11b/CCK	1 Mbps	01/07/13
	IEEE 802.11g/BPSK	6 Mbps	01/07/13
Power Spectral Density	IEEE 802.11n(HT20)/BPSK	MCS 0	01/07/13
Adaptivity, Occupied Channel Bandwidth	IEEE 802.11b/CCK	1 Mbps	01/13
	IEEE 802.11g/BPSK	6 Mbps	01/13
Transmitter unwanted emissions in the OOB domain	IEEE 802.11n(HT20)/BPSK	MCS 0	01/13
Transmitter unwanted emissions in the spurious domain (30 MHz ~ 1 GHz)	IEEE 802.11g/BPSK	6 Mbps	01/13
Transmitter unwanted emissions in the spurious domain (1 GHz ~ 12.75 GHz)	IEEE 802.11b/CCK	1 Mbps	01/13
	IEEE 802.11g/BPSK	6 Mbps	01/13
	IEEE 802.11n(HT20)/BPSK	MCS 0	01/13
Receiver spurious emissions (30 MHz ~ 1 GHz)	IEEE 802.11g/BPSK	6 Mbps	01/13
Receiver spurious emissions (1 GHz ~ 12.75 GHz)	IEEE 802.11g/BPSK	6 Mbps	01/13
Receiver Blocking	IEEE 802.11b/CCK	1 Mbps	01/13

Note:


For radiated spurious emissions below 1 GHz and receiver spurious emissions above 1 GHz test, the IEEE 802.11g channel 01/13 are found to be the worst case and recorded.

## 2.3 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Test Software Version	DA16200_AT_GUI_1.0.0.0		
Frequency (MHz)	2412	2442	2472
IEEE 802.11b	5	5	1
IEEE 802.11g	1	1	1
IEEE 802.11n(HT20)	2	2	2

## 2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



## 2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model No.	Series No.
A	Notebook	Dell	Inspiron 15-7559	N/A

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	USB Cable	NO	NO	0.8m

### 3. RF OUTPUT POWER

#### 3.1 APPLIED PROCEDURES / LIMIT

Clause	4.3.2.2
Test Item	RF output power
Limit	<p>The RF output power for non-FHSS equipment shall be equal to or less than 20 dBm.</p> <p>NOTE: For Non-adaptive FHSS equipment, the manufacturer may have declared a reduced RF Output Power (see clause 5.4.1 m) and associated Duty Cycle (see clause 5.4.1 e) that will ensure that the equipment meets the requirement for the Medium Utilization (MU) factor further described in clause 4.3.2.5. This is verified by the conformance test referred to in clause 4.3.2.5.4.</p> <p>For non-adaptive non-FHSS equipment, where the manufacturer has declared an RF output power of less than 20 dBm e.i.r.p., the RF output power shall be equal to or less than that declared value.</p> <p>This limit shall apply for any combination of power level and intended antenna assembly.</p>

#### 3.2 TEST PROCEDURES


Refer to ETSI EN 300 328, chapter 5.4.2.2.1.

#### 3.3 TEST SETUP LAYOUT

##### Normal Condition



##### Extreme Condition



#### 3.4 TEST DEVIATION

There is no deviation with the original standard.

#### 3.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

#### 3.6 TEST RESULTS

Please refer to the Appendix A.

## 4. POWER SPECTRAL DENSITY

### 4.1 APPLIED PROCEDURES / LIMIT

Clause	4.3.2.3
Test Item	Power Spectral Density
Limit	The maximum Power Spectral Density for non-FHSS equipment is 10 dBm per MHz.

### 4.2 TEST PROCEDURES

Refer to ETSI EN 300 328, chapter 5.4.3.2.1.

### 4.3 TEST SETUP LAYOUT



### 4.4 TEST DEVIATION

There is no deviation with the original standard.

### 4.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

### 4.6 TEST RESULTS

Please refer to the Appendix B.

## 5. DUTY CYCLE, TX-SEQUENCE, TX-GAP

### 5.1 APPLIED PROCEDURES / LIMIT

Clause	4.3.2.4
Test Item	Duty Cycle, Tx-sequence, Tx-gap
Limit	<p>Non-FHSS equipment shall comply with the following: The Duty Cycle shall be equal to or less than the maximum value declared by the manufacturer. The Tx-sequence time shall be equal to or less than 10 ms. The minimum Tx-gap time following a Tx-sequence shall be equal to the duration of that proceeding Txsequence with a minimum of 3,5 ms.</p> <p>NOTE: For Non-adaptive FHSS equipment, the manufacturer may have declared a reduced RF Output Power (see clause 5.4.1 m) and associated Duty Cycle (see clause 5.4.1 e) that will ensure that the equipment meets the requirement for the Medium Utilization (MU) factor further described in clause 4.3.2.5. This is verified by the conformance test referred to in clause 4.3.2.5.4.</p>

### 5.2 TEST PROCEDURES

Refer to ETSI EN 300 328, chapter 5.4.2.2.1.

### 5.3 TEST SETUP LAYOUT



### 5.4 TEST DEVIATION

There is no deviation with the original standard.

### 5.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

### 5.6 TEST RESULTS

Please refer to the Appendix C.

## 6. MEDIUM UTILISATION (MU) FACTOR

### 6.1 APPLIED PROCEDURES / LIMIT

Clause	4.3.2.5
Test Item	Medium Utilisation (MU) factor
Limit	The maximum Medium Utilization factor for non-adaptive non-FHSS equipment shall be 10 %.

### 6.2 TEST PROCEDURES

Refer to ETSI EN 300 328, chapter 5.4.2.2.1.

### 6.3 TEST SETUP LAYOUT



### 6.4 TEST DEVIATION

There is no deviation with the original standard.

### 6.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

### 6.6 TEST RESULTS

Please refer to the Appendix D.



## 7. ADAPTIVITY (ADAPTIVE EQUIPMENT USING MODULATIONS OTHER THAN FHSS)

### 7.1 APPLIED PROCEDURES / LIMIT

Clause	4.3.2.6											
Test Item	Adaptivity (adaptive equipment using modulations other than FHSS)											
Limit	<p><b><u>Adaptive non-FHSS using DAA</u></b></p> <p>Adaptive non-FHSS equipment using DAA shall comply with the following minimum set of requirements:</p> <ol style="list-style-type: none"><li>1) During normal operation, the equipment shall evaluate the presence of a signal on its current operating channel(s). If it is determined that a signal is present with a level above the detection threshold defined in step 5 that channel shall be marked as 'unavailable'.</li><li>2) The channel(s) shall remain unavailable for a minimum time equal to 1 s after which the channel may be considered again as an 'available' channel.</li><li>3) The total time during which an equipment has transmissions on a given channel without re-evaluating the availability of that channel, is defined as the Channel Occupancy Time. The Channel Occupancy Time shall be less than 40 ms. Each such transmission sequence shall be followed by an Idle Period (no transmissions) of minimum 5 % of the Channel Occupancy Time with a minimum of 100 μs. After this, the procedure as in step 1 needs to be repeated.</li><li>4) The detection threshold shall be proportional to the transmit power of the transmitter: for a 20 dBm e.i.r.p. transmitter the detection threshold level (TL) shall be equal to or less than -70 dBm/MHz at the input to the receiver assuming a 0 dBi (receive) antenna assembly. This threshold level (TL) may be corrected for the (receive) antenna assembly gain (G); however, beamforming gain (Y) shall not be taken into account. For power levels less than 20 dBm e.i.r.p., the detection threshold level may be relaxed to: <math display="block">TL = -70 \text{ dBm/MHz} + 10 \times \log_{10} (100 \text{ mW} / P_{out})</math>(P<sub>out</sub> in mW e.i.r.p.)</li><li>5) The equipment shall comply with the requirements defined in step 1 to step 4 of the present clause in the presence of an unwanted CW signal as defined in table 9.</li></ol>											
	<p style="text-align: center;"><b>Table 9: Unwanted Signal parameters</b></p> <table><tr><th>Wanted signal mean power from companion device (dBm)</th><th>Unwanted signal frequency (MHz)</th><th>Unwanted CW signal power (dBm)</th></tr><tr><td>-30 (see note 2)</td><td>2 395 or 2 488,5 (see note 1)</td><td>-35 (see note 2)</td></tr><tr><td colspan="3">NOTE 1: The highest frequency shall be used for testing operating channels within the range 2 400 MHz to 2 442 MHz, while the lowest frequency shall be used for testing operating channels within the range 2 442 MHz to 2 483,5 MHz. See clause 5.4.6.1.</td></tr><tr><td colspan="3">NOTE 2: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density in front of the UUT antenna.</td></tr></table>	Wanted signal mean power from companion device (dBm)	Unwanted signal frequency (MHz)	Unwanted CW signal power (dBm)	-30 (see note 2)	2 395 or 2 488,5 (see note 1)	-35 (see note 2)	NOTE 1: The highest frequency shall be used for testing operating channels within the range 2 400 MHz to 2 442 MHz, while the lowest frequency shall be used for testing operating channels within the range 2 442 MHz to 2 483,5 MHz. See clause 5.4.6.1.			NOTE 2: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density in front of the UUT antenna.	
Wanted signal mean power from companion device (dBm)	Unwanted signal frequency (MHz)	Unwanted CW signal power (dBm)										
-30 (see note 2)	2 395 or 2 488,5 (see note 1)	-35 (see note 2)										
NOTE 1: The highest frequency shall be used for testing operating channels within the range 2 400 MHz to 2 442 MHz, while the lowest frequency shall be used for testing operating channels within the range 2 442 MHz to 2 483,5 MHz. See clause 5.4.6.1.												
NOTE 2: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density in front of the UUT antenna.												

Limit	<p><b><u>Adaptive non-FHSS using LBT</u></b></p> <p>The present document defines two types of adaptive non-FHSS equipment that uses an LBT mechanism: Frame Based Equipment and Load Based Equipment. Adaptive non-FHSS equipment which is capable of operating as either Load Based Equipment or as Frame Based Equipment is allowed to switch dynamically between these types of operation.</p> <p><b><u>a. Frame Based Equipment</u></b></p> <p>Frame Based Equipment shall comply with the following requirements:</p> <ol style="list-style-type: none"> <li>1) Before transmission, the equipment shall perform a Clear Channel Assessment (CCA) check using energy detect. The equipment shall observe the operating channel for the duration of the CCA observation time which shall be not less than 18 <math>\mu</math>s. The channel shall be considered occupied if the energy level in the channel exceeds the threshold given in step 5 below. If the equipment finds the channel to be clear, it may transmit immediately. See figure 2.</li> <li>2) If the equipment finds the channel occupied, it shall not transmit on this channel during the next Frame Period. The equipment is allowed to switch to a non-adaptive mode and to continue transmissions on this channel providing it complies with the requirements applicable to non-adaptive equipment. See clause 4.3.2.6.1. Alternatively, the equipment is also allowed to continue Short Control Signalling Transmissions on this channel providing it complies with the requirements given in clause 4.3.2.6.4.</li> <li>3) The total time during which an equipment has transmissions on a given channel without re-evaluating the availability of that channel, is defined as the Channel Occupancy Time. The Channel Occupancy Time shall be in the range 1 ms to 10 ms followed by an Idle Period of at least 5 % of the Channel Occupancy Time used in the equipment for the current Frame Period. See figure 2.</li> <li>4) An equipment, upon correct reception of a transmission which was intended for this equipment can skip CCA and immediately (see also next paragraph) proceed with the transmission of management and control frames. A consecutive sequence of such transmissions by the equipment without a new CCA shall not exceed the maximum Channel Occupancy Time. For the purpose of multi-cast, the ACK transmissions (associated with the same data packet) of the individual devices are allowed to take place in a sequence.</li> <li>5) The energy detection threshold for the CCA shall be proportional to the transmit power of the transmitter: for a 20 dBm e.i.r.p. transmitter the CCA threshold level (TL) shall be equal to or less than -70 dBm/MHz at the input to the receiver assuming a 0 dBi (receive) antenna assembly. This threshold level (TL) may be corrected for the (receive) antenna assembly gain (G); however, beamforming gain (Y) shall not be taken into account. For power levels less than 20 dBm e.i.r.p. the CCA threshold level may be relaxed to:  <math display="block">TL = -70 \text{ dBm/MHz} + 10 \times \log_{10} (100 \text{ mW}/P_{\text{out}}) \text{ (} P_{\text{out}} \text{ in mW e.i.r.p.)}</math> </li> </ol>
-------	---

Limit	6) The equipment shall comply with the requirements defined in step 1 to step 4 in the present clause in the presence of an unwanted CW signal as defined in table 10.						
	<p style="text-align: center;"><b>Table 10: Unwanted Signal parameters</b></p> <table><tr><th>Wanted signal mean power from companion device</th><th>Unwanted signal frequency (MHz)</th><th>Unwanted signal power (dBm)</th></tr><tr><td>sufficient to maintain the link (see note 2)</td><td>2 395 or 2 488,5 (see note 1)</td><td>-35 (see note 3)</td></tr></table> <p>NOTE 1: The highest frequency shall be used for testing operating channels within the range 2 400 MHz to 2 442 MHz, while the lowest frequency shall be used for testing operating channels within the range 2 442 MHz to 2 483,5 MHz. See clause 5.4.6.1.</p> <p>NOTE 2: A typical conducted value which can be used in most cases is -50 dBm/MHz.</p> <p>NOTE 3: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density in front of the UUT antenna.</p>	Wanted signal mean power from companion device	Unwanted signal frequency (MHz)	Unwanted signal power (dBm)	sufficient to maintain the link (see note 2)	2 395 or 2 488,5 (see note 1)	-35 (see note 3)
	Wanted signal mean power from companion device	Unwanted signal frequency (MHz)	Unwanted signal power (dBm)				
	sufficient to maintain the link (see note 2)	2 395 or 2 488,5 (see note 1)	-35 (see note 3)				
	<p><b><u>b. Load Based Equipment</u></b></p> <p>Load Based Equipment may implement an LBT based spectrum sharing mechanism based on the Clear Channel Assessment (CCA) mode using energy detect as described in IEEE 802.11™ [i.3], clause 10 clause 11, clause 15, clause 16, clause 18 and clause 19, or in IEEE 802.15.4™ [i.4], clause 5, clause 6 and clause 10 providing the equipment complies with the conformance requirements referred to in clause 4.3.2.6.3.4. Load Based Equipment not using any of the mechanisms referenced above shall comply with the following minimum set of requirements:</p> <p>1) Before a transmission or a burst of transmissions, the equipment shall perform a Clear Channel Assessment (CCA) check using energy detect. The equipment shall observe the operating channel for the duration of the CCA observation time which shall be not less than 18 µs. The channel shall be considered occupied if the energy level in the channel exceeds the threshold given in step 5 below. If the equipment finds the channel to be clear, it may transmit immediately.</p> <p>2) If the equipment finds the channel occupied, it shall not transmit on this channel (see also the next paragraph). The equipment shall perform an Extended CCA check in which the channel is observed for a random duration in the range between 18 µs and at least 160 µs. If the extended CCA check has determined the channel to be no longer occupied, the equipment may resume transmissions on this channel. If the Extended CCA time has determined the channel still to be occupied, it shall perform new Extended CCA checks until the channel is no longer occupied.</p> <p>NOTE: The Idle Period in between transmissions is considered to be the CCA or the Extended CCA check as there are no transmissions during this period.</p> <p>The equipment is allowed to switch to a non-adaptive mode and to continue transmissions on this channel providing it complies with the requirements applicable to non-adaptive equipment. Alternatively, the equipment is also allowed to continue Short Control Signalling Transmissions on this channel providing it complies with the requirements given in clause 4.3.2.6.4.</p>						

Limit

- 3) The total time that an equipment makes use of a RF channel is defined as the Channel Occupancy Time. This Channel Occupancy Time shall be less than 13 ms, after which the device shall perform a new CCA as described in step 1 above.
- 4) The equipment, upon correct reception of a transmission which was intended for this equipment can skip CCA and immediately (see also next paragraph) proceed with the transmission of management and control frames. A consecutive sequence of transmissions by the equipment without a new CCA shall not exceed the maximum channel occupancy time as defined in step 3 above.  
For the purpose of multi-cast, the ACK transmissions (associated with the same data packet) of the individual devices are allowed to take place in a sequence.
- 5) The energy detection threshold for the CCA shall be proportional to the transmit power of the transmitter: for a 20 dBm e.i.r.p. transmitter the CCA threshold level (TL) shall be equal to or less than -70 dBm/MHz at the input to the receiver assuming a 0 dBi (receive) antenna assembly. This threshold level (TL) may be corrected for the (receive) antenna assembly gain (G); however, beamforming gain (Y) shall not be taken into account. For power levels less than 20 dBm e.i.r.p., the CCA threshold level may be relaxed to:  
$$TL = -70 \text{ dBm/MHz} + 10 \times \log_{10} (100 \text{ mW}/P_{\text{out}}) \text{ (} P_{\text{out}} \text{ in mW e.i.r.p.)}$$
- 6) The equipment shall comply with the requirements defined in step 1 to step 4 of the present clause in the presence of an unwanted CW signal as defined in table 11.

**Table 11: Unwanted Signal parameters**

Wanted signal mean power from companion device	Unwanted signal frequency (MHz)	Unwanted signal power (dBm)
sufficient to maintain the link (see note 2)	2 395 or 2 488,5 (see note 1)	-35 (see note 3)
NOTE 1: The highest frequency shall be used for testing operating channels within the range 2 400 MHz to 2 442 MHz, while the lowest frequency shall be used for testing operating channels within the range 2 442 MHz to 2 483,5 MHz. See clause 5.4.6.1.		
NOTE 2: A typical conducted value which can be used in most cases is -50 dBm/MHz.		
NOTE 3: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna.		

#### **Short Control Signalling Transmissions**


If implemented, Short Control Signalling Transmissions of adaptive non-FHSS equipment shall have a maximum TxOn / (TxOn + TxOff) ratio of 10 % within any observation period of 50 ms.

NOTE: Duty Cycle is defined in clause 4.3.2.4.2.

## 7.2 TEST PROCEDURES

Refer to ETSI EN 300 328, chapter 5.4.6.2.1.

## 7.3 TEST SETUP LAYOUT



## 7.4 TEST DEVIATION

There is no deviation with the original standard.

## 7.5 EUT OPERATION DURING TEST

The measurements shall be performed during normal operation.

## 7.6 TEST RESULTS

Please refer to the Appendix E.

## 8. OCCUPIED CHANNEL BANDWIDTH

### 8.1 APPLIED PROCEDURES / LIMIT

Clause	4.3.2.7						
Test Item	Occupied Channel Bandwidth						
Limit	<p>The Occupied Channel Bandwidth shall be within the band given in table 1.</p> <p><b>Table 1: Service frequency bands</b></p> <table> <tr> <th></th><th>Service frequency bands</th></tr> <tr> <td>Transmit</td><td>2 400 MHz to 2 483,5 MHz</td></tr> <tr> <td>Receive</td><td>2 400 MHz to 2 483,5 MHz</td></tr> </table> <p>In addition, for non-adaptive non-FHSS equipment with e.i.r.p. greater than 10 dBm, the Occupied Channel Bandwidth shall be equal to or less than 20 MHz.</p>		Service frequency bands	Transmit	2 400 MHz to 2 483,5 MHz	Receive	2 400 MHz to 2 483,5 MHz
	Service frequency bands						
Transmit	2 400 MHz to 2 483,5 MHz						
Receive	2 400 MHz to 2 483,5 MHz						

### 8.2 TEST PROCEDURES

Refer to ETSI EN 300 328, chapter 5.4.7.2.1.

### 8.3 TEST SETUP LAYOUT



### 8.4 TEST DEVIATION

There is no deviation with the original standard.

### 8.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

### 8.6 TEST RESULTS

Please refer to the Appendix F.

## 9. TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN

### 9.1 APPLIED PROCEDURES / LIMIT

Clause	4.3.2.8
Test Item	Transmitter unwanted emissions in the out-of-band domain
Limit	<p>The transmitter unwanted emissions in the out-of-band domain shall not exceed the values provided by the mask in figure 3.</p> <p>A: -10 dBm/MHz e.i.r.p. B: -20 dBm/MHz e.i.r.p. C: Spurious Domain limits</p> <p>BW = Occupied Channel Bandwidth in MHz or 1 MHz whichever is greater</p>

Figure 3: Transmit mask

### 9.2 TEST PROCEDURES

Refer to ETSI EN 300 328, chapter 5.4.8.2.1.

### 9.3 TEST SETUP LAYOUT



### 9.4 TEST DEVIATION

There is no deviation with the original standard.

### 9.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

### 9.6 TEST RESULTS

Please refer to the Appendix G.

## 10. TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN

### 10.1 APPLIED PROCEDURES / LIMIT

Clause	4.3.2.9																																	
Test Item	Transmitter unwanted emissions in the spurious domain																																	
Limit	<p>The transmitter unwanted emissions in the spurious domain shall not exceed the values given in table 12.</p> <p>In case of equipment with antenna connectors, these limits apply to emissions at the antenna port (conducted). For emissions radiated by the cabinet or emissions radiated by integral antenna equipment (without antenna connectors), these limits are e.r.p. for emissions up to 1 GHz and as e.i.r.p. for emissions above 1 GHz.</p> <p><b>Table 12: Transmitter limits for spurious emissions</b></p> <table><tr><th>Frequency range</th><th>Maximum power</th><th>Bandwidth</th></tr><tr><td>30 MHz to 47 MHz</td><td>-36 dBm</td><td>100 kHz</td></tr><tr><td>47 MHz to 74 MHz</td><td>-54 dBm</td><td>100 kHz</td></tr><tr><td>74 MHz to 87,5 MHz</td><td>-36 dBm</td><td>100 kHz</td></tr><tr><td>87,5 MHz to 118 MHz</td><td>-54 dBm</td><td>100 kHz</td></tr><tr><td>118 MHz to 174 MHz</td><td>-36 dBm</td><td>100 kHz</td></tr><tr><td>174 MHz to 230 MHz</td><td>-54 dBm</td><td>100 kHz</td></tr><tr><td>230 MHz to 470 MHz</td><td>-36 dBm</td><td>100 kHz</td></tr><tr><td>470 MHz to 694 MHz</td><td>-54 dBm</td><td>100 kHz</td></tr><tr><td>694 MHz to 1 GHz</td><td>-36 dBm</td><td>100 kHz</td></tr><tr><td>1 GHz to 12,75 GHz</td><td>-30 dBm</td><td>1 MHz</td></tr></table>	Frequency range	Maximum power	Bandwidth	30 MHz to 47 MHz	-36 dBm	100 kHz	47 MHz to 74 MHz	-54 dBm	100 kHz	74 MHz to 87,5 MHz	-36 dBm	100 kHz	87,5 MHz to 118 MHz	-54 dBm	100 kHz	118 MHz to 174 MHz	-36 dBm	100 kHz	174 MHz to 230 MHz	-54 dBm	100 kHz	230 MHz to 470 MHz	-36 dBm	100 kHz	470 MHz to 694 MHz	-54 dBm	100 kHz	694 MHz to 1 GHz	-36 dBm	100 kHz	1 GHz to 12,75 GHz	-30 dBm	1 MHz
	Frequency range	Maximum power	Bandwidth																															
	30 MHz to 47 MHz	-36 dBm	100 kHz																															
	47 MHz to 74 MHz	-54 dBm	100 kHz																															
	74 MHz to 87,5 MHz	-36 dBm	100 kHz																															
	87,5 MHz to 118 MHz	-54 dBm	100 kHz																															
	118 MHz to 174 MHz	-36 dBm	100 kHz																															
	174 MHz to 230 MHz	-54 dBm	100 kHz																															
	230 MHz to 470 MHz	-36 dBm	100 kHz																															
	470 MHz to 694 MHz	-54 dBm	100 kHz																															
694 MHz to 1 GHz	-36 dBm	100 kHz																																
1 GHz to 12,75 GHz	-30 dBm	1 MHz																																


### 10.2 TEST PROCEDURES

Refer to ETSI EN 300 328, chapter 5.4.9.2.2.




### 10.3 TEST SETUP LAYOUT

Emission\_ Radiated Measurement Test Set-Up Frequency Below 1 GHz



Emission\_ Radiated Measurement Test Set-Up Frequency Above 1 GHz



### 10.4 TEST DEVIATION

There is no deviation with the original standard.

### 10.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously transmitting.

### 10.6 TEST RESULTS

Please refer to the Appendix H

## 11. RECEIVER SPURIOUS EMISSIONS

### 11.1 APPLIED PROCEDURES / LIMIT

Clause	4.3.2.10										
Test Item	Receiver spurious emissions										
Limit	The spurious emissions of the receiver shall not exceed the values given in table 13.										
	In case of non-FHSS equipment with antenna connectors, these limits apply to emissions at the antenna port (conducted). For emissions radiated by the cabinet or for emissions radiated by integral antenna equipment (without antenna connectors), these limits are e.r.p. for emissions up to 1 GHz and e.i.r.p. for emissions above 1 GHz.										
	Table 13: Spurious emission limits for receivers										
	<table><tr><th>Frequency range</th><th>Maximum power</th><th>Bandwidth</th></tr><tr><td>30 MHz to 1 GHz</td><td>-57 dBm</td><td>100 kHz</td></tr><tr><td>1 GHz to 12,75 GHz</td><td>-47 dBm</td><td>1 MHz</td></tr></table>			Frequency range	Maximum power	Bandwidth	30 MHz to 1 GHz	-57 dBm	100 kHz	1 GHz to 12,75 GHz	-47 dBm
Frequency range	Maximum power	Bandwidth									
30 MHz to 1 GHz	-57 dBm	100 kHz									
1 GHz to 12,75 GHz	-47 dBm	1 MHz									

### 11.2 TEST PROCEDURES

Refer to ETSI EN 300 328, chapter 5.4.10.2.2.

### 11.3 TEST SETUP LAYOUT

Refer to clause 10.3.

### 11.4 TEST DEVIATION

There is no deviation with the original standard.

### 11.5 EUT OPERATION DURING TEST

The measurements shall be performed during continuously receiving.

### 11.6 TEST RESULTS

Please refer to the Appendix I.

## 12. RECEIVER BLOCKING

### 12.1 APPLIED PROCEDURES / LIMIT


Clause	4.3.2.11										
Test Item	Receiver Blocking										
Limit	While maintaining the minimum performance criteria as defined in clause 4.3.2.11.3, the blocking levels at specified frequency offsets shall be equal to or greater than the limits defined for the applicable receiver category provided in table 14, table 15 or table 16.										
	Receiver Category 1										
	Table 14 contains the Receiver Blocking parameters for Receiver Category 1 equipment.										
	Table 14: Receiver Blocking parameters for Receiver Category 1 equipment										
	<table><tr><th>Wanted signal mean power from companion device (dBm) (see notes 1 and 4)</th><th>Blocking signal frequency (MHz)</th><th>Blocking signal power (dBm) (see note 4)</th><th>Type of blocking signal</th></tr><tr><td>(-133 dBm + 10 × log<sub>10</sub>(OCBW)) or -68 dBm whichever is less (see note 2)</td><td>2 380 2 504</td><td rowspan="5">-34</td><td rowspan="5">CW</td></tr><tr><td>(-139 dBm + 10 × log<sub>10</sub>(OCBW)) or -74 dBm whichever is less (see note 3)</td><td>2 300 2 330 2 360 2 524 2 584 2 674</td></tr></table>	Wanted signal mean power from companion device (dBm) (see notes 1 and 4)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 4)	Type of blocking signal	(-133 dBm + 10 × log <sub>10</sub> (OCBW)) or -68 dBm whichever is less (see note 2)	2 380 2 504	-34	CW	(-139 dBm + 10 × log <sub>10</sub> (OCBW)) or -74 dBm whichever is less (see note 3)	2 300 2 330 2 360 2 524 2 584 2 674
	Wanted signal mean power from companion device (dBm) (see notes 1 and 4)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 4)	Type of blocking signal							
	(-133 dBm + 10 × log <sub>10</sub> (OCBW)) or -68 dBm whichever is less (see note 2)	2 380 2 504	-34	CW							
	(-139 dBm + 10 × log <sub>10</sub> (OCBW)) or -74 dBm whichever is less (see note 3)	2 300 2 330 2 360 2 524 2 584 2 674									
	NOTE 1: OCBW is in Hz.										
	NOTE 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to P <sub>min</sub> + 26 dB where P <sub>min</sub> is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.										
NOTE 3: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to P <sub>min</sub> + 20 dB where P <sub>min</sub> is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.											
NOTE 4: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned as recorded in clause 5.4.3.2.2.											
Receiver Category 2											
Table 15 contains the Receiver Blocking parameters for Receiver Category 2 equipment.											
Table 15: Receiver Blocking parameters receiver Category 2 equipment											
<table><tr><th>Wanted signal mean power from companion device (dBm) (see notes 1 and 3)</th><th>Blocking signal frequency (MHz)</th><th>Blocking signal power (dBm) (see note 3)</th><th>Type of blocking signal</th></tr><tr><td>(-139 dBm + 10 × log<sub>10</sub>(OCBW) + 10 dB) or (-74 dBm + 10 dB) whichever is less (see note 2)</td><td>2 380 2 504 2 300 2 584</td><td>-34</td><td>CW</td></tr></table>	Wanted signal mean power from companion device (dBm) (see notes 1 and 3)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 3)	Type of blocking signal	(-139 dBm + 10 × log <sub>10</sub> (OCBW) + 10 dB) or (-74 dBm + 10 dB) whichever is less (see note 2)	2 380 2 504 2 300 2 584	-34	CW			
Wanted signal mean power from companion device (dBm) (see notes 1 and 3)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 3)	Type of blocking signal								
(-139 dBm + 10 × log <sub>10</sub> (OCBW) + 10 dB) or (-74 dBm + 10 dB) whichever is less (see note 2)	2 380 2 504 2 300 2 584	-34	CW								
NOTE 1: OCBW is in Hz.											
NOTE 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to P <sub>min</sub> + 26 dB where P <sub>min</sub> is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.											
NOTE 3: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned as recorded in clause 5.4.3.2.2.											

Limit	Receiver Category 3			
	Table 16 contains the Receiver Blocking parameters for Receiver Category 3 equipment.			
	Table 16: Receiver Blocking parameters receiver Category 3 equipment			
	Wanted signal mean power from companion device (dBm) (see notes 1 and 3)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 3)	Type of blocking signal
	(-139 dBm + 10 × log <sub>10</sub> (OCBW) + 20 dB) or (-74 dBm + 20 dB) whichever is less (see note 2)	2 380 2 504 2 300 2 584	-34	CW
	NOTE 1: OCBW is in Hz.			
	NOTE 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to P <sub>min</sub> + 30 dB where P <sub>min</sub> is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.			
	NOTE 3: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned as recorded in clause 5.4.3.2.2.			

## 12.2 TEST PROCEDURES

Refer to ETSI EN 300 328, chapter 5.4.11.2.1.

## 12.3 TEST SETUP LAYOUT



## 12.4 TEST DEVIATION

There is no deviation with the original standard.

## 12.5 EUT OPERATION DURING TEST

The measurements shall be performed during normal receiving.

## 12.6 TEST RESULTS

Please refer to the Appendix J.

### 13. MEASUREMENT INSTRUMENTS LIST

RF Output Power					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	X-series USB Peak and Average Power Sensor	Agilent	U2021XA	MY55190003	Mar. 10, 2020
2	X-series USB Peak and Average Power Sensor	Agilent	U2021XA	MY55190006	Mar. 10, 2020
3	X-series USB Peak and Average Power Sensor	Agilent	U2021XA	MY55150012	Mar. 10, 2020
4	X-series USB Peak and Average Power Sensor	Agilent	U2021XA	MY55150014	Mar. 10, 2020
5	Const Temp. & Humidity Chamber	Bell	BTH-50C	20170306001	Mar. 10, 2020
6	Cable	emci	EMC104-SM-SM-9000(0.01GHz–26.5GHz)	N/A	N/A
7	Measurement Software	Keysight	EN300328v2.1.1 (v1.02.07)	N/A	N/A

Power Spectral Density & Occupied Channel Bandwidth & Transmitter Unwanted Out Of Band Domain					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EXA Spectrum Analyzer	Agilent	N9010A	MY55150209	Mar. 10, 2020
2	Cable	emci	EMC104-SM-SM-9000(0.01GHz–26.5GHz)	N/A	N/A
3	Measurement Software	Keysight	EN300328v2.1.1 (v1.02.07)	N/A	N/A

Adaptivity					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EXG-B RF Vector Signal Generator	Agilent	N5172B	MY53051637	Mar. 10, 2020
2	EXA Spectrum Analyzer	Agilent	N9010A	MY55150209	Mar. 10, 2020
3	EXG-B RF Vector Signal Generator	Keysight	N5171B	MY53051228	Mar. 10, 2020
4	Data Collector	Keysight	AD191A	N/A	N/A
5	Home Gateway	HUAWEI	DG8245V	N/A	N/A
6	Measurement Software	Keysight	EN300328v2.1.1 (v1.02.07)	N/A	N/A

Receiver Blocking					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	POWER SPLITTER	Mini-Circuits	ZN4PD1-63-S+	SF9335D1045-2	Feb. 07, 2022
2	EXG-B RF Vector Signal Generator	Agilent	N5172B	MY53051637	Feb. 27, 2022
3	wideband radio communication tester	R&S	CMW500	153083	Feb. 28, 2022



Transmitter and Receiver Spurious Emission (Radiated Measurement)					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarzbeck	VULB9160	9160-3231	Mar. 09, 2020
2	Amplifier	HP	8447D	2944A08908	Mar. 10, 2020
3	EXA Spectrum Analyzer	Agilent	N9010A	MY50520044	Mar. 10, 2020
4	Amplifier	Agilent	8449B	3008A02274	Mar. 10, 2020
5	Cable	emci	EMC104-SM-SM-9000(0.01GHz—26.5GHz)	N/A	N/A
6	Cable	emci	EMC80-NM-NM-12000(9KHz-1GHz)	N/A	N/A
7	Controller	ETS-Lindgren	2090	N/A	N/A
8	Double-Ridged Waveguide Horn Antennas	ETS-LINDGREN	3117-PA	00224991	Mar. 09, 2020
9	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

## 14. EUT TEST PHOTO

Radiated Emissions Test Photos





## APPENDIX A - RF OUTPUT POWER



Test Mode:	TX Mode_ IEEE 802.11b Mode
------------	----------------------------

Test Conditions		e.i.r.p. ( dBm )			Number Of Bursts		
		CH01	CH07	CH13	CH01	CH07	CH13
T nom (°C)	24.00	18.03	18.12	18.05	12.00	12.00	12.00
T min (°C)	-40.00	18.23	18.28	18.19	12.00	12.00	12.00
T max (°C)	80.00	17.82	17.89	17.78	12.00	12.00	12.00
Max. e.i.r.p.		18.28			Min Number		12.00
Limits		20dBm			≥ 10		
Result		Complies			Complies		

Test Mode:	TX Mode_ IEEE 802.11g Mode
------------	----------------------------

Test Conditions		e.i.r.p. ( dBm )			Number Of Bursts		
		CH01	CH07	CH13	CH01	CH07	CH13
T nom (°C)	24.00	19.00	18.82	18.93	13.00	13.00	13.00
T min (°C)	-40.00	19.13	18.99	19.04	13.00	13.00	13.00
T max (°C)	80.00	18.74	18.63	18.70	13.00	13.00	13.00
Max. e.i.r.p.		19.13			Min Number		13.00
Limits		20dBm			≥ 10		
Result		Complies			Complies		

Test Mode:	TX Mode_ IEEE 802.11n (HT20) Mode
------------	-----------------------------------


Test Conditions		e.i.r.p. ( dBm )			Number Of Bursts		
		CH01	CH07	CH13	CH01	CH07	CH13
T nom (°C)	24.00	17.95	17.80	17.72	15.00	15.00	15.00
T min (°C)	-40.00	18.08	17.96	17.94	15.00	15.00	15.00
T max (°C)	80.00	17.67	17.57	17.49	15.00	15.00	15.00
Max. e.i.r.p.		18.08			Min Number		15.00
Limits		20dBm			≥ 10		
Result		Complies			Complies		

Note: e.i.r.p. = Conducted output power + G (Ant Gain)


## **APPENDIX B - POWER SPECTRAL DENSITY**

Test Mode:	TX Mode_ IEEE 802.11b Mode
------------	----------------------------


Frequency (MHz)	Power Spectral Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
2412	9.84	10.00	Pass
2442	9.83	10.00	Pass
2472	9.80	10.00	Pass



### IEEE 802.11b Mode 2442 MHz




### IEEE 802.11b Mode 2472 MHz




Test Mode:	TX Mode_ IEEE 802.11g Mode
------------	----------------------------

Frequency (MHz)	Power Spectral Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
2412	7.96	10.00	Pass
2442	7.87	10.00	Pass
2472	7.93	10.00	Pass


IEEE 802.11g Mode 2412 MHz



## IEEE 802.11g Mode 2442 MHz




## IEEE 802.11g Mode 2472 MHz




Test Mode:	TX Mode_ IEEE 802.11n (HT20) Mode
------------	-----------------------------------

Frequency (MHz)	Power Spectral Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
2412	6.78	10.00	Pass
2442	6.71	10.00	Pass
2472	6.81	10.00	Pass


IEEE 802.11n (HT20) Mode 2412 MHz



### IEEE 802.11n (HT20) Mode 2442 MHz



### IEEE 802.11n (HT20) Mode 2472 MHz





## **APPENDIX C - DUTY CYCLE, TX-SEQUENCE, TX-GAP**

**Test Mode: N/A**

## **APPENDIX D - MEDIUM UTILISATION (MU) FACTOR**

**Test Mode: N/A**

## **APPENDIX E - ADAPTIVITY**

## 1. List of measurements

UUT Operational Mode	Frame Based Equipment	
	Load Based Equipment (CCA using 'energy detect')	✓
	Load Based Equipment (CCA not using any of the mechanisms referenced)	


Clause	Test Parameter	Remarks	Pass / Fail
4.3.2.6.3.2.2	Adaptive (Frame Based Equipment)	Not Applicable	N/A
4.3.2.6.3.2.3	Adaptive (Load Based Equipment)	Applicable	Pass
4.3.2.6.4	Short Control Signalling Transmissions	Applicable	Pass


Test Mode:	TX Mode_ IEEE 802.11b Mode
------------	----------------------------

Channel Occupancy Time and Clear Channel Assessment Measured Results		
Freq.(MHz)	Channel Occupancy Time (ms)	Clear Channel Assessment (us)
2412	1.29	63.00
2472	1.29	63.00
Limit	13	18~160
Note: Channel Occupancy Time and Clear Channel Assessment follow as IEEE Std. 802.11-2012 and IEEE 802.11n-2012 Specification without restriction.		

Adaptivity		
Adaptivity Detection Threshold Level	2412 MHz	-66.23 dBm/MHz
	2472 MHz	-66.19 dBm/MHz
Freq.(MHz)	Adaptivity	Short Control Signalling Transmissions (ms)
2412	Pass	1
2472	Pass	0.5
Limit	N/A	5
Result	Pass	
Note: Threshold Level =-70 dBm/MHz + 10 x log10 (100 mW/Pout) + EUT Antenna Gain (Pout in mW e.i.r.p.) Short Control Signalling Transmissions = 50 (ms) * Duty cycle (%)		

## IEEE 802.11b Mode 2412 MHz






COT Time Info

Max Channel Occupancy Time (ms) : 1.29

\*Please make sure the COT less than 13ms. or it will be failed.




Duty Cycle Info

Test Result : Pass



Short Control Signalling Transmission Time (us) : 1000

Duty Cycle (Hz) : 2.00

\* If Implemented, Short Control Signalling Transmissions shall have a maximum TxOn / (TxOn + TxOff) ratio of 10 % within any observation period of 50 ms or within an observation period equal to the dwell time, whichever is less.










Test Mode:	TX Mode_ IEEE 802.11g Mode
------------	----------------------------

Channel Occupancy Time and Clear Channel Assessment Measured Results		
Freq.(MHz)	Channel Occupancy Time (ms)	Clear Channel Assessment (us)
2412	1.04	138.01
2472	1.04	138.01
Limit	13	18~160
Note: Channel Occupancy Time and Clear Channel Assessment follow as IEEE Std. 802.11-2012 and IEEE 802.11n-2012 Specification without restriction.		

Adaptivity		
Adaptivity Detection Threshold Level	2412 MHz	-67.13 dBm/MHz
	2472 MHz	-67.04 dBm/MHz
Freq.(MHz)	Adaptivity	Short Control Signalling Transmissions (ms)
2412	Pass	1
2472	Pass	0.25
Limit	N/A	5
Result	Pass	
Note: Threshold Level =-70 dBm/MHz + 10 x log10 (100 mW/Pout) + EUT Antenna Gain (Pout in mW e.i.r.p.) Short Control Signalling Transmissions = 50 (ms) * Duty cycle (%)		

## IEEE 802.11g Mode 2412 MHz




#### CCA Time Info

Maximum CCA time should be between 18us ~ 160us

DIFS / PIFS (us) : 160.00

SIFS (us) : 10.99

Measured CCA (us) : 138.01



COT Time Info

Max Channel Occupancy Time (ms) : 1.04

\*Please make sure the COT less than 13ms. or it will be failed.



Duty Cycle Info




Test Result : Pass

Short Control Signalling Transmission Time (us) : 1000

Duty Cycle (%) : 2.00

\* If Implemented, Short Control Signalling Transmissions shall have a maximum TxOn / (TxOn + TxOff) ratio of 10 % within any observation period of 50 ms or within an observation period equal to the dwell time, whichever is less.

## IEEE 802.11g Mode 2472 MHz




#### CCA Time Info

Maximum CCA time should between 18us ~ 160us

DIFS / PIFS (us) : 160.00

SIFS (us) : 10.99


Measured CCA (us) : 138.01



COT Time Info

Max Channel Occupancy Time (ms) : 1.04

\*Please make sure the COT less than 13ms, or it will be failed.



Duty Cycle Info

Test Result : Pass

Short Control Signalling Transmission Time (us) : 250

Duty Cycle (%) : 0.50




\* If implemented, Short Control Signalling Transmissions shall have a maximum TxOn / (TxOn + TxOff) ratio of 10 % within any observation period of 50 ms or within an observation period equal to the dwell time, whichever is less.

Test Mode:	TX Mode_ IEEE 802.11n (HT20) Mode
------------	-----------------------------------

Channel Occupancy Time and Clear Channel Assessment Measured Results		
Freq.(MHz)	Channel Occupancy Time (ms)	Clear Channel Assessment (us)
2412	1.67	140.00
2472	1.67	138.01
Limit	13	18~160
Note: Channel Occupancy Time and Clear Channel Assessment follow as IEEE Std. 802.11-2012 and IEEE 802.11n-2012 Specification without restriction.		

Adaptivity		
Adaptivity Detection Threshold Level	2412 MHz	-66.08 dBm/MHz
	2472 MHz	-65.94 dBm/MHz
Freq.(MHz)	Adaptivity	Short Control Signalling Transmissions (ms)
2412	Pass	0
2472	Pass	0.5
Limit	N/A	5
Result	Pass	
Note: Threshold Level =-70 dBm/MHz + 10 x log10 (100 mW/Pout) + EUT Antenna Gain (Pout in mW e.i.r.p.) Short Control Signalling Transmissions = 50 (ms) * Duty cycle (%)		

## IEEE 802.11n (HT20) Mode 2412 MHz



### CCA Time Info


Maximum CCA time should be between 18us ~ 160us

DIFS / PIFS (us) : 160.00

SIFS (us) : 10.00

Measured CCA (us) : 140.00






COT Time Info

Max Channel Occupancy Time (ms) : 1.67

\*Please make sure the COT less than 13ms, or it will be failed.



Duty Cycle Info




Test Result : Pass

Short Control Signalling Transmission Time (ms) : 0


Duty Cycle (%) : 0.00

\* If implemented, Short Control Signalling Transmissions shall have a maximum TxOn / (TxOn + TxOff) ratio of 10 % within any observation period of 50 ms or within an observation period equal to the dwell time, whichever is less.

## IEEE 802.11n (HT20) Mode 2472 MHz



CCA Time Info		
Maximum CCA time should between 18us ~ 160us	DIFS / PIFS (us) : 160.00	SIFS (us) : 10.99
	Measured CCA (us) : 138.01	



COT Time Info

Max Channel Occupancy Time (ms) : 1.67

\*Please make sure the COT less than 13ms. or it will be failed.



Duty Cycle Info

Test Result : Pass

Duty Cycle (%) : 1.00

Short Control Signalling Transmission Time (us) : 500


\* If implemented, Short Control Signalling Transmissions shall have a maximum TxOn / (TxOn + TxOff) ratio of 10 % within any observation period of 50 ms or within an observation period equal to the dwell time, whichever is less.

## APPENDIX F - OCCUPIED CHANNEL BANDWIDTH


Test Mode:	TX Mode_ IEEE 802.11b Mode
------------	----------------------------

Frequency (MHz)	Occupied Channel Bandwidth (MHz)	F <sub>L</sub> at 99% BW (MHz)	F <sub>H</sub> at 99% BW (MHz)	Result
2412	13.535	2405.24	-	Pass
2472	13.569	-	2478.79	
N/A		F <sub>L</sub> > 2400	F <sub>H</sub> < 2483.5	

## IEEE 802.11b Mode\_2412 MHz




## IEEE 802.11b Mode\_2472 MHz




Test Mode:	TX Mode_ IEEE 802.11g Mode
------------	----------------------------

Frequency (MHz)	Occupied Channel Bandwidth (MHz)	F <sub>L</sub> at 99% BW (MHz)	F <sub>H</sub> at 99% BW (MHz)	Result
2412	16.456	2403.78	-	Pass
2472	16.451	-	2480.23	
N/A		F <sub>L</sub> > 2400	F <sub>H</sub> < 2483.5	

## IEEE 802.11g Mode\_2412 MHz




## IEEE 802.11g Mode\_2472 MHz




Test Mode:	TX Mode_ IEEE 802.11n (HT20) Mode
------------	-----------------------------------

Frequency (MHz)	Occupied Channel Bandwidth (MHz)	F <sub>L</sub> at 99% BW (MHz)	F <sub>H</sub> at 99% BW (MHz)	Result
2412	17.516	2403.25	-	Pass
2472	17.517	-	2480.76	
N/A		F <sub>L</sub> > 2400	F <sub>H</sub> < 2483.5	

## IEEE 802.11n (HT20) Mode\_2412 MHz



## IEEE 802.11n (HT20) Mode\_2472 MHz




## **APPENDIX G - TRANSMITTER UNWANTED EMISSIONS IN THE OOB DOMAIN**




Test Mode: TX Mode\_ IEEE 802.11b Mode

## IEEE 802.11b Mode\_2412 MHz




## IEEE 802.11b Mode\_2472 MHz




Test Mode: TX Mode\_ IEEE 802.11g Mode

## IEEE 802.11g Mode\_2412 MHz




## IEEE 802.11g Mode\_2472 MHz




Test Mode: TX Mode\_ IEEE 802.11n (HT20) Mode

## IEEE 802.11n (HT20) Mode\_2412 MHz




## IEEE 802.11n (HT20) Mode\_2472 MHz



## **APPENDIX H - TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN**

Test Mode:	TX Mode IEEE 802.11g_2412 MHz
------------	-------------------------------


## Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin		
		MHz	Level	Factor	ment			Detector	Comment
			dBm	dB	dBm	dBm	dB		
1		41.834	-74.82	-3.24	-78.06	-36.00	-42.06	RMS	
2		102.459	-72.89	-3.88	-76.77	-54.00	-22.77	RMS	
3		359.994	-70.77	0.43	-70.34	-36.00	-34.34	RMS	
4	*	479.983	-67.03	3.69	-63.34	-54.00	-9.34	RMS	
5		719.961	-77.27	7.52	-69.75	-54.00	-15.75	RMS	
6		959.939	-71.17	9.57	-61.60	-36.00	-25.60	RMS	

Test Mode: TX Mode IEEE 802.11g\_2412 MHz


## Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1		32.425	-77.76	-2.02	-79.78	-36.00	-43.78	RMS	
2		144.072	-71.14	-0.73	-71.87	-36.00	-35.87	RMS	
3		359.994	-67.65	0.58	-67.07	-36.00	-31.07	RMS	
4	*	479.983	-68.73	3.37	-65.36	-54.00	-11.36	RMS	
5		719.961	-77.61	7.76	-69.85	-54.00	-15.85	RMS	
6		959.939	-72.79	9.73	-63.06	-36.00	-27.06	RMS	

Test Mode: TX Mode IEEE 802.11g\_2472 MHz


## Vertical



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		30.000	-72.93	-4.91	-77.84	-36.00	-41.84	RMS	
2		102.459	-71.37	-3.88	-75.25	-54.00	-21.25	RMS	
3		359.994	-70.46	0.43	-70.03	-36.00	-34.03	RMS	
4 *		479.983	-67.18	3.69	-63.49	-54.00	-9.49	RMS	
5		719.961	-77.11	7.52	-69.59	-54.00	-15.59	RMS	
6		959.939	-71.75	9.57	-62.18	-36.00	-26.18	RMS	

Test Mode:	TX Mode IEEE 802.11g_2472 MHz
------------	-------------------------------

## Horizontal




No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		32.425	-77.76	-2.02	-79.78	-36.00	-43.78	RMS	
2		160.853	-69.77	-1.62	-71.39	-36.00	-35.39	RMS	
3		240.005	-72.28	-2.43	-74.71	-36.00	-38.71	RMS	
4		359.994	-67.46	0.58	-66.88	-36.00	-30.88	RMS	
5	*	479.983	-69.02	3.37	-65.65	-54.00	-11.65	RMS	
6		960.036	-72.42	9.74	-62.68	-36.00	-26.68	RMS	



Test Mode:	TX Mode IEEE 802.11b_2412 MHz
------------	-------------------------------


## Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	3216.0500	-51.92	0.87	-51.05	-30.00	-21.05	RMS	
2 *	4824.0379	-48.61	4.22	-44.39	-30.00	-14.39	RMS	
3	7236.9000	-60.80	4.41	-56.39	-30.00	-26.39	RMS	
4	9648.0000	-59.79	8.10	-51.69	-30.00	-21.69	RMS	

Test Mode:	TX Mode IEEE 802.11b_2412 MHz
------------	-------------------------------


## Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	3216.0500	-55.25	-0.22	-55.47	-30.00	-25.47	RMS	
2 *	4824.0379	-50.82	3.40	-47.42	-30.00	-17.42	RMS	
3	7237.4880	-60.47	7.32	-53.15	-30.00	-23.15	RMS	
4	9648.0000	-57.67	8.02	-49.65	-30.00	-19.65	RMS	

Test Mode:	TX Mode IEEE 802.11b_2472 MHz
------------	-------------------------------


## Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1 *	4943.8870	-46.10	4.19	-41.91	-30.00	-11.91	RMS	
2	9887.7000	-63.75	7.32	-56.43	-30.00	-26.43	RMS	

Test Mode:	TX Mode IEEE 802.11b_2472 MHz
------------	-------------------------------


## Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1 *	4943.8870	-51.13	3.36	-47.77	-30.00	-17.77	RMS	
2	9887.7000	-61.09	8.10	-52.99	-30.00	-22.99	RMS	

Test Mode:	TX Mode IEEE 802.11g_2412 MHz
------------	-------------------------------


## Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1 *	3216.0500	-52.32	0.87	-51.45	-30.00	-21.45	RMS	
2	4822.2750	-57.01	4.22	-52.79	-30.00	-22.79	RMS	
3	7235.7250	-61.85	4.41	-57.44	-30.00	-27.44	RMS	
4	9648.0000	-64.33	8.10	-56.23	-30.00	-26.23	RMS	

Test Mode:	TX Mode IEEE 802.11g_2412 MHz
------------	-------------------------------


## Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1 *	3216.0500	-55.35	-0.22	-55.57	-30.00	-25.57	RMS	
2	4824.6250	-60.17	3.40	-56.77	-30.00	-26.77	RMS	
3	9648.0000	-63.80	8.02	-55.78	-30.00	-25.78	RMS	

Test Mode:	TX Mode IEEE 802.11g_2472 MHz
------------	-------------------------------


## Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	3295.9500	-57.63	0.84	-56.79	-30.00	-26.79	RMS	
2 *	9888.2880	-63.21	7.32	-55.89	-30.00	-25.89	RMS	

Test Mode:	TX Mode IEEE 802.11g_2472 MHz
------------	-------------------------------

## Horizontal




No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	3295.9500	-59.67	0.05	-59.62	-30.00	-29.62	RMS	
2	4943.8870	-58.86	3.36	-55.50	-30.00	-25.50	RMS	
3 *	9887.7000	-59.56	8.10	-51.46	-30.00	-21.46	RMS	



Test Mode:	TX Mode IEEE 802.11n(HT20)_2412 MHz
------------	-------------------------------------


## Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1 *	3216.0500	-51.84	0.87	-50.97	-30.00	-20.97	RMS	
2	4825.8000	-59.30	4.22	-55.08	-30.00	-25.08	RMS	
3	7236.3130	-62.47	4.41	-58.06	-30.00	-28.06	RMS	
4	9648.0000	-64.78	8.10	-56.68	-30.00	-26.68	RMS	

Test Mode:	TX Mode IEEE 802.11n(HT20)_2412 MHz
------------	-------------------------------------


## Horizontal



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1 *	3216.0500	-54.85	-0.22	-55.07	-30.00	-25.07	RMS	
2	4823.4500	-60.62	3.40	-57.22	-30.00	-27.22	RMS	
3	9648.0000	-63.49	8.02	-55.47	-30.00	-25.47	RMS	

Test Mode:	TX Mode IEEE 802.11n(HT20)_2472 MHz
------------	-------------------------------------


## Vertical



No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	3295.9500	-57.36	0.84	-56.52	-30.00	-26.52	RMS	
2	4121.9750	-62.08	4.39	-57.69	-30.00	-27.69	RMS	
3 *	9887.7000	-63.33	7.32	-56.01	-30.00	-26.01	RMS	

Test Mode:	TX Mode IEEE 802.11n(HT20)_2472 MHz
------------	-------------------------------------

## Horizontal




No.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure ment dBm	Limit dBm	Margin dB	Detector	Comment
1	3295.9500	-59.13	0.05	-59.08	-30.00	-29.08	RMS	
2	4948.0000	-60.13	3.36	-56.77	-30.00	-26.77	RMS	
3 *	9887.7000	-60.10	8.10	-52.00	-30.00	-22.00	RMS	

## **APPENDIX I - RECEIVER SPURIOUS EMISSIONS**

Test Mode:	RX Mode IEEE 802.11g_2412 MHz
------------	-------------------------------


## Vertical



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		33.201	-72.54	-6.25	-78.79	-57.00	-21.79	RMS	
2		103.526	-71.60	-3.77	-75.37	-57.00	-18.37	RMS	
3		359.994	-70.56	0.43	-70.13	-57.00	-13.13	RMS	
4		479.983	-67.57	3.69	-63.88	-57.00	-6.88	RMS	
5		719.961	-77.13	7.52	-69.61	-57.00	-12.61	RMS	
6	*	960.036	-71.60	9.58	-62.02	-57.00	-5.02	RMS	

Test Mode:	RX Mode IEEE 802.11g_2412 MHz
------------	-------------------------------


## Horizontal



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		41.543	-78.55	-1.72	-80.27	-57.00	-23.27	RMS	
2		145.333	-70.56	-0.69	-71.25	-57.00	-14.25	RMS	
3		240.005	-72.01	-2.43	-74.44	-57.00	-17.44	RMS	
4		359.994	-67.80	0.58	-67.22	-57.00	-10.22	RMS	
5		479.983	-68.70	3.37	-65.33	-57.00	-8.33	RMS	
6	*	959.939	-72.41	9.73	-62.68	-57.00	-5.68	RMS	

Test Mode:	RX Mode IEEE 802.11g_2472 MHz
------------	-------------------------------

## Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1		32.425	-73.13	-5.92	-79.05	-57.00	-22.05	RMS	
2		104.108	-71.08	-3.71	-74.79	-57.00	-17.79	RMS	
3		359.994	-70.35	0.43	-69.92	-57.00	-12.92	RMS	
4		479.983	-67.38	3.69	-63.69	-57.00	-6.69	RMS	
5		719.961	-76.97	7.52	-69.45	-57.00	-12.45	RMS	
6	*	960.019	-69.24	9.57	-59.67	-57.00	-2.67	RMS	



Test Mode:	RX Mode IEEE 802.11g_2472 MHz
------------	-------------------------------


## Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1		43.386	-77.18	-2.44	-79.62	-57.00	-22.62	RMS	
2		145.430	-69.94	-0.69	-70.63	-57.00	-13.63	RMS	
3		240.005	-71.96	-2.43	-74.39	-57.00	-17.39	RMS	
4		359.994	-67.41	0.58	-66.83	-57.00	-9.83	RMS	
5		479.983	-69.09	3.37	-65.72	-57.00	-8.72	RMS	
6	*	959.939	-72.70	9.73	-62.97	-57.00	-5.97	RMS	

Test Mode:	RX Mode IEEE 802.11g_2412 MHz
------------	-------------------------------


## Vertical



No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1 *	9334.8620	-64.78	8.23	-56.55	-47.00	-9.55	RMS	

Test Mode:	RX Mode IEEE 802.11g_2412 MHz
------------	-------------------------------


### Horizontal



No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1 *	7728.0500	-63.47	7.23	-56.24	-47.00	-9.24	RMS	

Test Mode:	RX Mode IEEE 802.11g_2472 MHz
------------	-------------------------------


### Vertical



No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1 *	9356.0130	-64.92	8.28	-56.64	-47.00	-9.64	RMS	

Test Mode:	RX Mode IEEE 802.11g_2472 MHz
------------	-------------------------------

## Horizontal



No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1 *	7260.4000	-63.50	7.33	-56.17	-47.00	-9.17	RMS	

## **APPENDIX J - RECEIVER BLOCKING**

Receiver Blocking Result						
Modulation Mode	Operation Freq. (MHz)	Wanted Signal Mean Power from Companion Device (dBm) (See Note 1)	Blocking Signal Freq. (MHz) (See Note 2)	Blocking Signal Power (dBm) (See Note 1)	Blocking Signal Power + Max. Ant. Gain (dBm)	PER (%)
802.11b Mode	2412	-66.00	2380	-34	-32	0.20
		-72.00	2300	-34	-32	1.20
			2330	-34	-32	0.20
			2360	-34	-32	0.00
	2472	-66.00	2504	-34	-32	1.00
		-72.00	2524	-34	-32	0.20
			2584	-34	-32	0.00
			2674	-34	-32	0.20
Limit	PER(Packet Error Rate) ≤ 10%					
Result	Pass					

Note:

- 1) The levels had been corrected by the actual antenna assembly gain.
- 2) The test report did not use the shift of blocking frequencies with the standard Clause 5.4.11.2.1 Step 5.

**APPENDIX K - INFORMATION AS REQUIRED BY  
EN 300 328 V2.2.2, CLAUSE 5.4.1**



**a) The type of wideband data transmission equipment:**

- ☐ FHSS  
☒ non-FHSS

**b) In case of FHSS:**

(1) In case of non-Adaptive FHSS equipment:

The number of Hopping Frequencies: N/A

(2) In case of Adaptive FHSS equipment:

The maximum number of Hopping Frequencies: N/A

The minimum number of Hopping Frequencies: N/A

(3) The (average) dwell time: N/A

**c) Adaptive / non-adaptive equipment:**

- ☐ non-adaptive Equipment  
☒ adaptive Equipment without the possibility to switch to a non-adaptive mode  
☐ adaptive Equipment which can also operate in a non-adaptive mode

**d) In case of adaptive equipment:**

The maximum Channel Occupancy Time implemented by the equipment: 1.67 ms

☒ The equipment has implemented an LBT mechanism

\* In case of non-FHSS equipment:

- ☐ The equipment is Frame Based equipment  
☒ The equipment is Load Based equipment  
☐ The equipment can switch dynamically between Frame Based and Load Based

equipment

The CCA time implemented by the equipment: 140  $\mu$ s

- ☐ The equipment has implemented a DAA mechanism  
☐ The equipment can operate in more than one adaptive mode

**f) The worst case operational mode for each of the following tests:**

- (1) RF Output Power: 19.13 dBm
- (2) Power Spectral Density: 9.84 dBm/MHz
- (3) Duty cycle, Tx-Sequence, Tx-gap: N/A
- (4) Accumulated Transmit time, Frequency Occupation & Hopping Sequence (only for FHSS equipment): N/A
- (5) Hopping Frequency Separation (only for FHSS equipment) : N/A
- (6) Medium Utilisation: N/A
- (7) Adaptivity : 1 ms , Receiver Blocking: 1.20 %
- (8) Nominal Channel Bandwidth: 20 MHz
- (9) Transmitter unwanted emissions in the OOB domain: -14.57 dBm
- (10) Transmitter unwanted emissions in the spurious domain: -63.34 dBm
- (11) Receiver spurious emissions: -59.67 dBm

**g) The different transmit operating modes (tick all that apply):**

- ☒ Operating mode 1: Single Antenna Equipment
  - ☒ Equipment with only one antenna
  - ☐ Equipment with two diversity antennas but only one antenna active at any moment in time
  - ☐ Smart Antenna Systems with two or more antennas, but operating in a (legacy) mode

where only one antenna is used. (e.g. IEEE 802.11™ legacy mode in smart antenna systems)

- ☐ Operating mode 2: Smart Antenna Systems - Multiple Antennas without beam forming
  - ☐ Single spatial stream / Standard throughput (e.g. IEEE 802.11™ legacy mode)
  - ☐ High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 1
  - ☐ High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 2

NOTE 1: Add more lines if more channel bandwidths are supported.

- ☐ Operating mode 3: Smart Antenna Systems - Multiple Antennas with beam forming
  - ☐ Single spatial stream / Standard throughput (e.g. IEEE 802.11™ legacy mode)
  - ☐ High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 1
  - ☐ High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 2

NOTE 2: Add more lines if more channel bandwidths are supported.

#### h) In case of Smart Antenna Systems: N/A

(1) The number of Receive chains: \_\_\_\_

(2) The number of Transmit chains: \_\_\_\_

☐ symmetrical power distribution

☐ asymmetrical power distribution

In case of beam forming, the maximum (additional) beam forming gain: \_\_\_\_dB

NOTE: The additional beam forming gain does not include the basic gain of a single antenna.

#### i) Operating Frequency Range(s) of the equipment:

(1) Operating Frequency Range 1: 2412 MHz to 2472 MHz

NOTE: Add more lines if more Frequency Ranges are supported.

#### j) Nominal Channel Bandwidth(s):

(1) Nominal Channel Bandwidth 1: 20 MHz

NOTE: Add more lines if more channel bandwidths are supported.

#### k) Type of Equipment (stand-alone, combined, plug-in radio device, etc.):

☒ Stand-alone

☐ Combined Equipment

☐ Plug-in radio device

☐ Other \_\_\_\_\_

#### l) The extreme operating conditions that apply to the equipment:

Operating temperature range: -40 ° C to 80 ° C

Details provided are for the: ☒ stand-alone equipment

☐ combined equipment

☐ test jig

**n) The nominal voltages of the stand-alone radio equipment or the nominal voltages of the combined equipment or test jig in case of plug-in devices:**

Details provided are for the: ☐ stand-alone equipment  
☐ combined (or host) equipment  
☒ test jig

Supply voltage ☐ AC Mains    State AC voltage \_\_\_\_\_ V  
☒ DC                      State DC voltage 3.3 V

In case of DC, indicate the type of power source

- ☐ Internal Power Supply  
☒ External Power Supply or AC/DC adapter  
☐ Battery  
☐ Other: \_\_\_\_\_

**o) Describe the test modes available which can facilitate testing:**

The measurements shall be performed during continuously transmitting and normal operation.

**p) The equipment type (e.g. Bluetooth®, IEEE 802.11™, IEEE 802.15.4™, proprietary, etc.):**

IEEE 802.11™

**s) Geo-location capability supported by the equipment:**

- ☐ Yes  
☐ The geographical location determined by the equipment as defined in clause 4.3.1.13.2 or clause 4.3.2.12.2 is not accessible to the user  
☒ No

**End of Test Report**