

# FCC RF EXPOSURE REPORT

## FCC ID: 2AU49-DA16200MC

**Project No.** : 1910C137  
**Equipment** : WiFi Module  
**Brand Name** : Dialog  
**Test Model** : DA16200MOD-AAE4WA32  
**Series Model** : N/A  
**Applicant** : Dialog Semiconductor Korea Inc.  
**Address** : 7th SiliconPark, 35, Pangyo-ro 255 beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do (Zip 13486), Korea  
**Manufacturer** : Iton Technology Corp.  
**Address** : 7 Floor East, Building C, Shenzhen International Innovation Center, No. 1006 Shennan Road, Futian District, Shenzhen, China  
**Factory** : Iton Technology Corp.  
**Address** : Building E, Weixinda Industrial Park, Ainan Road 95, Longgang District, Shenzhen, Guangdong Province, China  
**Date of Receipt** : Nov. 07, 2019  
**Date of Test** : Nov. 08, 2019 ~ Nov. 28, 2019  
**Issued Date** : Dec. 13, 2019  
**Report Version** : R00  
**Test Sample** : Engineering Sample No.: DG2019110653  
**Standard(s)** : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091  
FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

*Vincent Tan*

Prepared by : Vincent Tan

*Ethan Ma*

Approved by : Ethan Ma



Certificate #5123.02

Add: No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

Tel: +86-769-8318-3000

Web: www.newbtl.com

**REPORT ISSUED HISTORY**

Report Version	Description	Issued Date
R00	Original Issue.	Dec. 13, 2019

## 1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	Dipole	N/A	2

## 2. TEST RESULTS

Tune up tolerance(dBm)
2

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Max. Peak Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
2	1.5849	19.55	90.1571	0.02844	1	Complies

Note: The calculated distance is 20 cm.

Output power including tune up tolerance(tune up tolerance: X.XX dBm).

**End of Test Report**