RSS-247, ISSUE 4, July 2025

RSS-GEN, ISSUE 5, February 2021 Amendment 2

TEST REPORT

For

Renesas Design Korea Inc.

7th SiliconPark, 35 Pangyo-ro 255 beon-gil Bundang-gu, Seongnam-si, Gyeonggi-do, 13486

IC: 34654-RRQ61051009

Report Type:	**Product Type:**
Original Report	RRQ61051 Module

Report Producer : Cedric Xu

Report Number : RLK250801005RF08

Report Date : 2026-01-20

Reviewed By: Jack Hsu Jack Hsu

Prepared By: Bay Area Compliance Laboratories Corp.
(Linkou Laboratory)
No. 6, Wende 2Rd., Guishan Dist.,
Taoyuan City 33382, Taiwan (R.O.C.).
Tel: +886 (3) 3961072
Fax: +886 (3) 3961027
www.baclcorp.com.tw

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Revision History

Revision	No.	Report Number	Issue Date	Description	Author/ Revised by
0.0	RLK250801005	RLK250801005RF08	2026-01-20	Original Report	Cedric Xu

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

TABLE OF CONTENTS

1 General Information 5

1.1 Product Description for Equipment under Test (EUT) 5
1.2 Objective 6
1.3 Test Methodology 6
1.4 Statement of Compliance 6
1.5 Measurement Uncertainty 7
1.6 Environmental Conditions 7
1.7 Test Facility 7

2 System Test Configuration 8

2.1 Description of Test Configuration 8
2.2 EUT Exercise Software 8
2.3 Test Mode 9
2.4 Support Equipment List and Details 9
2.5 External Cable List and Details 9
2.6 Block Diagram of Test Setup 10
2.7 Duty Cycle 12

3 Summary of Test Results 19

4 Test Equipment List and Details 20

5 RSS-GEN §6.8 – Antenna Requirements 22

5.1 Applicable Standard 22
5.2 Antenna List and Details 22

6 RSS-GEN §8.8 – AC Line Conducted Emissions 23

6.1 Applicable Standard 23
6.2 EUT Setup 24
6.3 EMI Test Receiver Setup 24
6.4 Test Procedure 24
6.5 Factor & Over Limit Calculation 24
6.6 Test Results 25

7 RSS-GEN §8.9, §8.10 – Spurious Emissions 26

7.1 Applicable Standard 26
7.2 EUT Setup 28
7.3 EMI Test Receiver & Spectrum Analyzer Setup 29
7.4 Test Procedure 29
7.5 Factor & Over Limit Calculation 29
7.6 Test Results 30

8 RSS-247 §6.3.1 (b), RSS-GEN §6.7) – 6 dB Emission Bandwidth & Occupied Bandwidth 69

8.1 Applicable Standard 69
8.2 Test Procedure 69
8.3 Test Results 70

9 RSS-247 §6.3.2 – Maximum Output Power 87

9.1 Applicable Standard 87
9.2 Test Procedure 87
9.3 Test Results 88

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

10 RSS-247 §6.6 – 100 kHz Bandwidth of Frequency Band Edge 90

10.1 Applicable Standard 90
10.2 Test Procedure 90
10.3 Test Results 91

11 RSS-247 §6.3.1(b) – Power Spectral Density 97

11.1 Applicable Standard 97
11.2 Test Procedure 97
11.3 Test Results 98

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

1 General Information

1.1 Product Description for Equipment under Test (EUT)

Applicant	Renesas Design Korea Inc. 7th SiliconPark, 35 Pangyo-ro 255 beon-gil Bundang-gu, Seongnam-si, Gyeonggi-do, 13486
Manufacturer	Renesas Design Korea Inc. 7th SiliconPark, 35 Pangyo-ro 255 beon-gil Bundang-gu, Seongnam-si, Gyeonggi-do, 13486
Brand(Trade) Name	Renesas
Product (Equipment)	RRQ61051 Module
Main Model Name	RRQ61051-009
Series Model Name	RRQ61051-010
Model Differences	Different antenna interfaces
Frequency Range	IEEE 802.11b/g/n HT20/ax HE20 Mode: 2412 ~ 2462 MHz BLE(1M): 2402 ~ 2480 MHz
Maximum Conducted Peak Output Power	IEEE 802.11b Mode: 19.59dBm (0.091W) IEEE 802.11g Mode: 19.62dBm (0.092W) IEEE 802.11n HT20 Mode: 19.61dBm (0.091W) IEEE 802.11ax HE20 Mode: 19.68dBm (0.093W) BLE(1M) Mode : 1.42 dBm (0.00139W)
Modulation Technique	IEEE 802.11b Mode: DSSS IEEE 802.11g Mode: OFDM IEEE 802.11n HT20 Mode: OFDM IEEE 802.11ax HE20 Mode: OFDMA BLE(1M) Mode: GFSK
Power Operation (Voltage Range)	☐ AC 120V/60Hz ☐ Adapter ☐ By AC Power Cord ☐ PoE
	☐ DC Type ☐ Battery ☐ DC Power Supply ☐ External from USB Cable ☐ External DC Adapter
	☒ 3.3Vdc
Received Date	Aug 01, 2025
Date of Test	Oct. 20, 2025～ Jan. 20, 2026

*All measurement and test data in this report was gathered from production sample serial number:

RLK250801005-01 (Assigned by BACL, Linkou Laboratory).

**802.11ax mode only support full RU

***This device cannot run both WIFI 2.4G and WIFI 5G simultaneously.

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

1.2 Objective

This report is prepared on behalf of Renesas Design Korea Inc. in accordance with RSS-247, Issue 4, July 2025, RSS-Gen, Issue 5, February 2021 Amendment 2 of the Innovation, Science and Economic Development Canada.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

KDB 558074 D01 DTS Meas Guidance v05r02 and RSS-247, Issue 4, July 2025, RSS-Gen, Issue 5, February 2021 Amendment 2 of the Innovation, Science and Economic Development Canada.

1.4 Statement of Compliance

Decision Rule: No, (The test results do not include MU judgment)

1. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory).
2. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.
3. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
4. The determination of the test results does not require consideration of the uncertainty of the measurement, unless the assessment is required by customer agreement, regulation or standard document specification.
5. Bay Area Compliance Laboratories Corp. (Linkou Laboratory) is not responsible for the authenticity of the information provided by the applicant that affects the test results.

1.5 Measurement Uncertainty

Parameter		Uncertainty
AC Mains		±2.98 (dB)
RF output power, conducted		±3.73 (dB)
Power Spectral Density, conducted		±0.65 (dBm)
Occupied Bandwidth		±0.09 (%)
Unwanted Emissions, conducted		±1.03 (dB)
Emissions, radiated	9kHz~30MHz	±3.20 (dB)
	30 MHz~1GHz	±3.30 (dB)
	1 GHz~18 GHz	±4.99 (dB)
	18 GHz~40 GHz	±4.52 (dB)
Temperature		±0.78 (℃)
Humidity		±0.04 (%)

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

1.6 Environmental Conditions

Test Site	Test Data	Temperature (℃)	Relative Humidity (%)	Test Engineer
AC Line Conducted Emissions	2025/10/21	23.4	52	Cedric Xu
Radiation Spurious Emissions	2025/10/20~2025/12/24	18.2 ~ 24.5	45~59	Derek
Conducted Spurious Emissions	2025/10/20~2025/10/28	21.7~23.2	42~57	Alan
6 dB Emission Bandwidth & Occupied Bandwidth	2025/10/20~2025/10/28	21.7~23.2	42~57	Alan
Maximum Output Power	2025/10/20~2026/01/20	21.7~23.2	42~57	Alan
100 kHz Bandwidth of Frequency Band Edge	2025/10/20~2025/10/28	21.7~23.2	42~57	Alan
Power Spectral Density	2025/10/20~2025/10/28	21.7~23.2	42~57	Alan
Duty Cycle	2025/10/20~2026/01/20	21.7~23.2	42~57	Alan

1.7 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Linkou Laboratory) to collect test data is located on

☒ No.6, Wende 2Rd., Guishan Dist., Taoyuan City 33382, Taiwan (R.O.C.).

Bay Area Compliance Laboratories Corp. (Linkou Laboratory) is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 3546) and the lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: TW3546.

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

2 System Test Configuration

2.1 Description of Test Configuration

For WIFI mode, there are totally 11 channels.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

For 802.11 b/g/n20/ax20 Modes were tested with channel 1, 6 and 11.

For BLE mode, there are totally 40 channels.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	--	--
2	2406	--	--
3	2408	37	2476
--	--	38	2478
19	2440	39	2480

For 802.11 b/g/n20 Modes were tested with channel 1, 19 and 39.

The system was configured for testing in engineering mode, which was provided by manufacturer.

2.2 EUT Exercise Software

WIFI 2.4G Used “TeraTerm5” software.

BLE Used “TeraTerm5” software. & SmartSnippets_Toolbox.exe

Test Frequency		Low	Mid	High
Power Level Setting	b Mode	9	9	6
	g Mode	11	11	10
	n20 Mode	9	11	9
	ax20 Mode	10	11	10
	BLE 1M	Default	Default	Default

The worst case data rates are as follows:

802.11b: 1Mbps

802.11g: 6Mbps

802.11n HT20: MCS0

802.11ax HE20: MCS0

BLE 1M : 1 Mbps

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

2.3 Test Mode

Mode 1: Full System (model: RRQ61051-009) for all test item.

2.4 Support Equipment List and Details

No.	Description	Manufacturer	Model
1	Notebook (Lab provided)	DELL	E6410
2	Notebook (Lab provided)	Acer	N16Q1
3	Test Development Board (Customer provided)	RENESAS	EK-RQ61 565-11-C-0001 Ver 3.1
4	Daughter Board (Customer provided)	RENESAS	RRQ61x1 565-16-B
5	Antenna (Customer provided)	ARISTOTLE	RFA-27-H60-U-GB70

2.5 External Cable List and Details

No.	Description	Manufacturer	Model
1	USB-A to C cable (Customer provided)	VENTION	COZ
2	I-PEX to SMA Cable (Customer provided)	TAOGLAS	0.2m


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

2.6 Block Diagram of Test Setup


See test photographs attached in setup photos for the actual connections between EUT and support equipment.

Radiation:

Below 1GHz:




Above 1GHz:




Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Conduction:



Conducted:



2.7 Duty Cycle

Test EUT Mode : RRQ61051-009

Radio Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T VBW Seting (kHz)	1/T (kHz)
802.11b	0.624	0.714	87	0.60	3	1.60
802.11g	0.696	0.790	88	0.56	3	1.44
802.11 n20	0.290	0.320	91	0.41	5	3.45
802.11 ax20	2.830	2.950	99	0.00	3	0.35
BLE(1M)	9.940	10.029	99	0.00	/	0.10

Note: Duty Cycle Correction Factor = 10*log(1/duty cycle)

Please refer to the following plots.

Test EUT Mode : RRQ61051-010

Radio Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T VBW Seting (kHz)	1/T (kHz)
802.11b	0.627	0.648	97	0.13	3	1.60
802.11g	0.696	0.723	96	0.18	3	1.44
802.11 n20	0.292	0.320	91	0.41	5	3.45
802.11 ax20	2.832	2.870	96	0.18	3	0.35
BLE(1M)	9.930	10.020	99	0.00	/	0.10


Note: Duty Cycle Correction Factor = 10*log(1/duty cycle)

Please refer to the following plots.

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


Test EUT Mode : RRQ61051-009

b Mode



Date: 20.OCT.2025 16:07:31


g Mode



Date: 20.OCT.2025 16:06:49


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

n20 Mode



Date: 20.OCT.2025 16:06:01


ax20 Mode



Date: 20.OCT.2025 16:01:29

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


BLE (1M) Mode



Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


Test EUT Mode : RRQ61051-010

b Mode



Date: 20.JAN.2026 09:58:11


g Mode



Date: 20.JAN.2026 09:59:39


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

n20 Mode



Date: 20.JAN.2026 10:00:54


ax20 Mode



Date: 20.JAN.2026 10:02:19

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

BLE (1M) Mode



Date: 20.JAN.2026 10:07:58

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

3 Summary of Test Results

Rules	Description of Test	Results
RSS-Gen §6.8	Antenna Requirement	Compliance
RSS-Gen §8.8	AC Line Conducted Emissions	Compliance
RSS-247 §6.6 RSS-Gen §8.9 RSS-Gen §8.10	Spurious Emissions	Compliance
RSS-247 §6.3.1(a) RSS-Gen §6.7	6 dB Emission Bandwidth & Occupied Bandwidth	Compliance
RSS-247 §6.3.2	Maximum Peak Output Power	Compliance
RSS-247 §6.6	100 kHz Bandwidth of Frequency Band Edge	Compliance
RSS-247 §6.3.1	Power Spectral Density	Compliance

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

4 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due Date
AC Line Conduction Room (CON-A)					
Pulse Limiter	SCHWARZBECK	VTSD 9561-F	00432	2025/08/14	2026/08/14
ESR EMI Test Receiver	Rohde & Schwarz	ESCI7	100769	2025/04/02	2026/04/02
RF Cable	EMCI	EMCCFD300-BM-BM-3000	221013	2025/10/16	2026/10/16
Two-Line V-Network	Rohde & Schwarz	ENV216	100037	2025/09/15	2026/09/15
Software	Audix	e3 v9	E3LK-03	N.C.R	N.C.R
Radiated Room (966-B)					
Bilog Antenna & 6 dB Attenuator	SUNOL SCIENCES & EMCI	JB3 & N-6-06	A071318 & AT-N0670	2025/08/14	2026/08/14
Active Loop Antenna	ETS-Lindgren	6502	0001-3322	2025/03/27	2026/03/27
Horn Antenna	ETS-Lindgren	3115	85775	2025/10/03	2026/10/03
Horn Antenna	ETS-Lindgren	3160-09	123853	2025/08/28	2026/08/28
18-40GHz Preamplifier	GLOBAL	1313-A1840	5031371	2025/04/28	2026/04/28
30M-18GHz Preamplifier	A.H. Systems	PAM-0118P	479	2025/09/05	2026/09/05
ESR EMI Test Receiver	Rohde & Schwarz	ESR3	102430	2025/04/25	2026/04/25
Spectrum Analyzer	Rohde & Schwarz	FSV40	101456	2025/06/05	2026/06/05
Microflex Cable (1m)	EMCI	EMCI02-KM-KM-1000	180524	2025/08/01	2026/08/01
Microflex Cable (2m)	EMCI	EMCI06-SM-SM-2000	180516	2025/08/01	2026/08/01
Microflex Cable (8m)	UTIFLEX	UFA210A-1-3149-300300	MFR 64639 232490-002	2025/08/01	2026/08/01
Software	AUDIX	E3 V9	E3LK-02	N.C.R	N.C.R
-10dB Attenuator	MTJ	MTJ604-10	004	2025/04/07	2026/04/07
Band Reject Filter	MICRO-TRONICS	BRM50702	G613	2025/04/30	2026/04/30
Conducted Room					

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Cable	MTJ	MT40S	620620-MT40S-100	2025/12/26	2026/01/05
Cable	MTJ	MT40S	620620-MT40S-100	2026/01/05	2027/01/05
Signal and Spectrum Analyzer	Rohde & Schwarz	FSV40	101457	2024/12/04	2025/12/04
Signal and Spectrum Analyzer	Rohde & Schwarz	FSV40	101457	2025/12/03	2026/12/03
USB Wideband Power Sensor	AGILENT	U2021XA	MY54080011	2025/08/26	2026/08/26

***Statement of Traceability:** BACL Corp. attests that all of the calibrations on the equipment items listed above were traceable to the SI System of Units via the R.O.C. Center for Measurement Standards of the Electronics Testing Center, Taiwan (ETC) or to another internationally recognized National Metrology Institute (NMI), and were compliant with the current Taiwan Accreditation Foundation (TAF) requirements

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

5 RSS-GEN §6.8 – Antenna Requirements

5.1 Applicable Standard

According to RSS-Gen 6.8:

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

5.2 Antenna List and Details

Manufacturer	Model	Antenna Type	Antenna Gain
Aristotle	RFA-27-H60-U-GB70	Dipole Antenna	3.3 dBi

Please refer to the antenna specification for detailed information.

Unit uses a unique coupling to the intentional radiator.

2.4 Cable Loss of the Cable used for antenna connection : 1.54 dB

Result: Compliance

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

6 RSS-GEN §8.8 – AC Line Conducted Emissions

6.1 Applicable Standard

According to RSS-GEN §8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50 μH / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56 Note 1	56 to 46 Note 2
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency.


For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

(a)Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.

(b)Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

6.2 EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 measurement procedure. The specification used was with the RSS-GEN limits.

6.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150kHz to 30MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations

Frequency Range	IF B/W
150kHz – 30MHz	9kHz

6.4 Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

6.5 Factor & Over Limit Calculation

The factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The “Over Limit” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of -7 dB means the emission is 7 dB below the limit. The equation for Over Limit calculation is as follows:

Over Limit = Level – Limit Line


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

6.6 Test Results

Test Mode: Transmitting


(Worst case is 802.11ax20 mode, High Channel)

Line	Neutral



Site : Conduction
Condition: Line
Job No : RLK250801005
Test By : Cedric Xu
Power : AC 120V/60Hz
Temp.(℃)/Hum.(%RH): 23.4℃/52%
Mode : WiFi 2.4G-AX20-2462

	Freq	Read Level	Level	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dBuV	dB	
1	0.1514	31.14	51.12	19.98	65.93	-14.81	QP
2	0.1514	16.11	36.09	19.98	55.93	-19.84	Average
3	0.2610	14.73	34.73	20.00	61.40	-26.67	QP
4	0.2610	5.99	25.99	20.00	51.40	-25.41	Average
5	0.3374	11.06	31.08	20.02	59.27	-28.19	QP
6	0.3374	4.50	24.52	20.02	49.27	-24.75	Average
7	0.3550	8.99	29.01	20.02	58.84	-29.83	QP
8	0.3550	1.90	21.92	20.02	48.84	-26.92	Average
9	0.4898	12.48	32.51	20.03	56.17	-23.66	QP
10	0.4898	5.11	25.14	20.03	46.17	-21.03	Average
11	1.5064	8.86	28.92	20.06	56.00	-27.08	QP
12	1.5064	4.87	24.93	20.06	46.00	-21.07	Average




Site : Conduction
Condition: Neutral
Job No : RLK250801005
Test By : Cedric Xu
Power : AC 120V/60Hz
Temp.(℃)/Hum.(%RH): 23.4℃/52%
Mode : WiFi 2.4G-AX20-2462

	Freq	Read Level	Level	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dBuV	dB	
1	0.1571	29.04	49.04	20.00	65.62	-16.58	QP
2	0.1571	13.34	33.34	20.00	55.62	-22.28	Average
3	0.2049	21.84	41.82	19.98	63.41	-21.59	QP
4	0.2049	10.17	30.15	19.98	53.41	-23.26	Average
5	0.4869	12.71	32.70	19.99	56.22	-23.52	QP
6	0.4869	4.56	24.55	19.99	46.22	-21.67	Average
7	1.1582	6.37	26.39	20.02	56.00	-29.61	QP
8	1.1582	2.00	22.02	20.02	46.00	-23.98	Average
9	1.4663	9.16	29.20	20.04	56.00	-26.80	QP
10	1.4663	5.21	25.25	20.04	46.00	-20.75	Average
11	2.2853	0.69	20.74	20.05	56.00	-35.26	QP
12	2.2853	-3.94	16.11	20.05	46.00	-29.89	Average


(Worst case is BLE 1M mode, Low Channel)

Line	Neutral



Site : Conduction
Condition: Line
Job No : RLK250801005
Test By : Cedric Xu
Power : AC 120V/60Hz
Temp.(℃)/Hum.(%RH): 23.4℃/52%
Mode : BLE 1M-TX-2402

	Freq	Read Level	Level	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dBuV	dB	
1	0.1593	29.48	49.46	19.98	65.50	-16.04	QP
2	0.1593	12.79	32.77	19.98	55.50	-22.73	Average
3	0.1774	26.00	45.98	19.98	64.61	-18.63	QP
4	0.1774	11.64	31.62	19.98	54.61	-22.99	Average
5	0.2219	18.46	38.44	19.98	62.75	-24.31	QP
6	0.2219	5.49	25.47	19.98	52.75	-27.28	Average
7	0.2336	17.71	37.70	19.99	62.32	-24.62	QP
8	0.2336	6.25	26.24	19.99	52.32	-26.08	Average
9	0.4706	12.24	32.27	20.03	56.50	-24.23	QP
10	0.4706	5.53	25.56	20.03	46.50	-20.94	Average
11	0.8616	6.90	26.94	20.04	56.00	-29.06	QP
12	0.8616	1.54	21.58	20.04	46.00	-24.42	Average



Site : Conduction
Condition: Neutral
Job No : RLK250801005
Test By : Cedric Xu
Power : AC 120V/60Hz
Temp.(℃)/Hum.(%RH): 23.4℃/52%
Mode : BLE 1M-TX-2402

	Freq	Read Level	Level	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dBuV	dB	
1	0.1526	31.78	51.79	20.01	65.86	-14.07	QP
2	0.1526	16.53	36.54	20.01	55.86	-19.32	Average
3	0.1686	27.38	47.38	20.00	65.03	-17.65	QP
4	0.1686	11.17	31.17	20.00	55.03	-23.86	Average
5	0.2105	20.32	40.30	19.98	63.19	-22.89	QP
6	0.2105	5.86	25.84	19.98	53.19	-27.35	Average
7	0.2746	13.60	33.58	19.98	60.98	-27.40	QP
8	0.2746	5.94	25.92	19.98	50.98	-25.06	Average
9	0.3035	12.27	32.25	19.98	60.15	-27.90	QP
10	0.3035	5.11	25.09	19.98	50.15	-25.06	Average
11	0.4687	12.50	32.49	19.99	56.54	-24.05	QP
12	0.4687	6.12	26.11	19.99	46.54	-20.43	Average

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = (LISN, ISN, PLC or current probe) Factor + Cable Loss + Attenuator

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

7 RSS-GEN §8.9, §8.10 – Spurious Emissions

7.1 Applicable Standard

As per RSS-Gen 8.10,

Restricted frequency bands, identified in table 7, are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following conditions related to the restricted frequency bands apply:

(a)The transmit frequency, including fundamental components of modulation, of licence-exempt radio apparatus shall not fall within the restricted frequency bands listed in table 7 except for apparatus compliant with RSS-287, Emergency Position Indicating Radio Beacons (EPIRB), Emergency Locator Transmitters (ELT), Personal Locator Beacons (PLB), and Maritime Survivor Locator Devices (MSLD).

(b)Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table 5 and table 6.

(c)Unwanted emissions that do not fall within the restricted frequency bands listed in table 7 shall comply either with the limits specified in the applicable RSS or with those specified in table 5 and table 6.

Table 7 – Restricted frequency bands Note 1

MHz	MHz	MHz	GHz
0.090 – 0.110	16.42 – 16.423	608 – 614	4. 5 – 5. 15
0.495 – 0.505	16.69475 – 16.69525	960 – 1240	5. 35 – 5. 46
2.1735 – 2.1905	16.80425 – 16.80475	1300 – 1427	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1435 – 1626.5	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1645.5 – 1646.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1660 – 1710	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1718.8 – 1722.2	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	2200 – 2300	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2310 – 2390	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2483.5 – 2500	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2690 – 2900	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	3260 – 3267	22.01 – 23.12
8.41425 – 8.41475	162.0125 –167.17	3.332 – 3.339	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3 3458 – 3 358	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3.600 – 4.400	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4		Above 38.6
13.36 – 13.41	399.9 – 410		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

As per RSS-GEN §8.9: Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Table 5 – General field strength limits at frequencies above 30 MHz	
Frequency (MHz)	**Field Strength (μV/m at 3 m)**
30 - 88	100
88 - 216	150
216 - 960	200
Above 960	500

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency (MHz)	**Field Strength (H-Field) (μA/m)**	**Measurement distance (m)**
9 - 490 kHz[Note 1]	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

Note 2: The limit was added 51.5dB to convert the limit from dBuA/m to dBuV/m.

According to ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024, section 5.3.3 Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field, and the emissions to be measured can be detected by the measurement equipment (see 4.3.4). Measurements shall not be performed at a distance greater than 30 m for frequencies above 30 MHz, unless it can be further demonstrated that measurements at a distance of 30 m or less are impractical. Measurements from 18 GHz to 40 GHz are typically made at distances significantly less than 3 m from the EUT. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade of distance (inverse of linear distance for field-strength measurements or inverse of linear distance-squared for power-density measurements).


As per RSS-247 6.6,

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum device, digitally modulated device, or hybrid system is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power – based on either an RF conducted or a radiated measurement – provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 6.3.2, the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

7.2 EUT Setup


9kHz-30MHz:




30MHz- 1GHz:



1-18 GHz:



18-26.5 GHz:



Radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024. The specification used was the RSS-247 and RSS-GEN Limits.

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

7.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 26.5 GHz. During the radiated emission test, the EMI test receiver was set with the following configurations measurement method 6.3 in ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024

Frequency Range	RBW	VBW	Duty cycle	Measurement method	Detector
9 kHz - 150 kHz	200 Hz/300 Hz	1 kHz	/	QP/AV	QP/AV
150 kHz - 30 MHz	9 kHz/10 kHz	30 kHz	/	QP/AV	QP/AV
30-1000 MHz	120 kHz	500 kHz	/	QP	QP
Above 1 GHz	Pre-scan :				
	1 MHz	3 MHz	/	PK	PK
	1 MHz	1 kHz	>98%	Ave	PK
	1 MHz	≥ 1/Ton, not less than 1 Hz	<98%	Ave	PK
	Final measurement for emission identified during pre-scan :				
	1 MHz	3 MHz	/	PK	PK
	1 MHz	10 Hz	>98%	Ave	PK
	1 MHz	≥ 1/Ton	<98%	Ave	PK

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

7.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in Quasi-peak and average detector mode from 9 kHz to 30 MHz, Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

7.5 Factor & Over Limit Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Factor = Antenna Factor + Cable Loss – Amplifier Gain

The “Over Limit” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of -7 dB means the emission is 7 dB below the limit. The equation for Over Limit calculation is as follows:

Over Limit = Level – Limit Line

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

7.6 Test Results

Test Mode: Transmitting

(Pre-scan with three orthogonal axis, and worse case as Z axis.)

Test EUT Mode : RRQ61051-009


9kHz-30MHz:

(Worst case is 802.11ax20 mode, High Channel)

(Pre-scan using three directional polarities, worst case as parallel.)

High channel


9kHz-150kHz



Site : 966B Chamber
Condition: 3m
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 19.5℃/ 45%
Memo : AX20-TX-2462
RBW/VBW : QP:300Hz/1k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	0.015	14.18	13.53	27.71	124.34	-96.63	QP
2	0.049	11.51	13.18	24.69	113.79	-89.10	QP
3	0.069	11.98	11.67	23.65	110.77	-87.12	QP
4	0.099	11.82	11.58	23.40	107.71	-84.31	QP
5	0.111	12.30	11.61	23.91	106.71	-82.80	QP
6	0.128	12.01	11.70	23.71	105.47	-81.76	QP

150kHz-30MHz



Site : 966B Chamber
Condition: 3m
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 19.5℃/ 45%
Memo : AX20-TX-2462
RBW/VBW : QP:10k/30k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	0.489	28.53	11.68	40.21	93.81	-53.60	QP
2	8.469	15.16	11.72	26.88	69.54	-42.66	QP
3	17.577	14.64	11.94	26.58	69.54	-42.96	QP
4	21.148	15.31	11.61	26.92	69.54	-42.62	QP
5	27.155	20.52	11.63	32.15	69.54	-37.39	QP
6	29.798	23.85	11.05	34.90	69.54	-34.64	QP

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


Test EUT Mode : RRQ61051-009

(Worst case is BLE(1M) mode, Low Channel)

(Pre-scan with three orthogonal axis, and worse case as Z axis.)


(Pre-scan using three directional polarities, worst case as parallel.)

Low channel	
9kHz-150kHz	150kHz-30MHz




```
Site     : 966B Chamber
Condition: 3m
Job No   : RLK250801005
Model    : RRQ61051-009
Power    : From Test Development Board
Tester   : Derek
Temp./ Hum.: 19.5℃/ 45%
Memo     : BLE-1M-TX-2402
RBW/VBW  : QP:300Hz/1k
```

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	0.014	14.45	13.52	27.97	124.48	-96.51	QP
2	0.052	11.68	12.98	24.66	113.31	-88.65	QP
3	0.071	11.96	11.62	23.58	110.62	-87.04	QP
4	0.100	13.13	11.56	24.69	107.59	-82.90	QP
5	0.110	11.43	11.61	23.04	106.77	-83.73	QP
6	0.137	11.40	11.74	23.14	104.89	-81.75	QP




```
Site     : 966B Chamber
Condition: 3m
Job No   : RLK250801005
Model    : RRQ61051-009
Power    : From Test Development Board
Tester   : Derek
Temp./ Hum.: 19.5℃/ 45%
Memo     : BLE-1M-TX-2402
RBW/VBW  : QP:10k/30k
```

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	0.973	30.53	11.48	42.01	67.84	-25.83	QP
2	1.946	24.91	11.02	35.93	69.54	-33.61	QP
3	8.381	17.84	11.73	29.57	69.54	-39.97	QP
4	16.674	18.35	11.80	30.15	69.54	-39.39	QP
5	24.935	11.23	12.32	23.55	69.54	-45.99	QP
6	28.180	17.99	11.37	29.36	69.54	-40.18	QP

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Test EUT Mode : RRQ61051-010


9kHz-30MHz:

(Worst case is 802.11ax20 mode, High Channel)

(Pre-scan using three directional polarities, worst case as parallel.)

High channel


9kHz-150kHz




```
Site     : 966B Chamber
Condition: 3m
Job No   : RLK250801005
Model    : RRQ61051-010
Power    : From Test Development Board
Tester   : Derek
Temp./ Hum.: 20.7℃/ 53%
Memo     : AX20-TX-2462
Memo     : RBW/VBW: QP:0.3k/1k
```

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	0.015	15.34	13.54	28.88	124.32	-95.44	QP
2	0.046	14.33	12.92	27.25	114.31	-87.06	QP
3	0.094	15.01	11.68	26.69	108.15	-81.46	QP
4	0.100	14.65	11.57	26.22	107.64	-81.42	QP
5	0.127	13.08	11.69	24.77	105.55	-80.78	QP
6	0.144	12.48	11.78	24.26	104.43	-80.17	QP

150kHz-30MHz




```
Site     : 966B Chamber
Condition: 3m
Job No   : RLK250801005
Model    : RRQ61051-010
Power    : From Test Development Board
Tester   : Derek
Temp./ Hum.: 20.7℃/ 53%
Memo     : AX20-TX-2462
Memo     : RBW/VBW: QP:10k/30k
```

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	0.509	29.77	11.66	41.43	73.47	-32.04	QP
2	1.913	25.88	11.03	36.91	69.54	-32.63	QP
3	5.692	16.64	11.71	28.35	69.54	-41.19	QP
4	15.364	12.43	11.60	24.03	69.54	-45.51	QP
5	21.504	11.39	11.48	22.87	69.54	-46.67	QP
6	27.213	14.20	11.62	25.82	69.54	-43.72	QP

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Test EUT Mode : RRQ61051-010


(Worst case is BLE(1M) mode, Low Channel)

(Pre-scan with three orthogonal axis, and worse case as Z axis.)

(Pre-scan using three directional polarities, worst case as parallel.)


Low channel

9kHz-150kHz	150kHz-30MHz



Site : 966B Chamber
Condition: 3m
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 53%
Memo : BLE-1M-TX-2402
Memo : RBW/VBW: QP:0.3k/1k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	0.015	15.85	13.56	29.41	124.05	-94.64	QP
2	0.032	11.61	12.69	24.30	117.59	-93.29	QP
3	0.047	13.19	12.97	26.16	114.20	-88.04	QP
4	0.062	14.16	11.74	25.90	111.75	-85.85	QP
5	0.095	14.15	11.66	25.81	108.05	-82.24	QP
6	0.127	12.64	11.69	24.33	105.54	-81.21	QP



Site : 966B Chamber
Condition: 3m
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 53%
Memo : BLE-1M-TX-2402
Memo : RBW/VBW: QP:10k/30k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	0.417	29.74	11.75	41.49	95.21	-53.72	QP
2	3.441	20.84	10.85	31.69	69.54	-37.85	QP
3	7.721	14.92	11.82	26.74	69.54	-42.80	QP
4	15.386	13.48	11.60	25.08	69.54	-44.46	QP
5	21.787	11.29	11.39	22.68	69.54	-46.86	QP
6	27.617	14.20	11.50	25.70	69.54	-43.84	QP

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Test EUT Mode : RRQ61051-009

30MHz-1GHz:


(worst case is 802.11 ax20 mode, High Channel)

High channel	
Horizontal	**Vertical**




```
Site     : 966B Chamber
Condition: 3m horizontal
Job No   : RLK250801005
Model    : RRQ61051-009
Power    : From Test Development Board
Tester   : Derek
Temp./ Hum.: 24.5℃/ 51%
Memo     : AX20-TX-2462
RBW/VBW  : QP:120k/500k
```

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1 !	32.975	42.39	-4.53	37.86	40.00	-2.14	QP
2 !	215.981	58.10	-15.64	42.46	43.50	-1.04	QP
3	311.979	54.99	-12.41	42.58	46.00	-3.42	QP
4 !	407.977	54.60	-10.11	44.49	46.00	-1.51	QP
5	504.007	48.26	-8.10	40.16	46.00	-5.84	QP
6	551.989	46.31	-7.28	39.03	46.00	-6.97	QP




```
Site     : 966B Chamber
Condition: 3m vertical
Job No   : RLK250801005
Model    : RRQ61051-009
Power    : From Test Development Board
Tester   : Derek
Temp./ Hum.: 24.5℃/ 51%
Memo     : AX20-TX-2462
RBW/VBW  : QP:120k/500k
```

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	215.981	55.16	-15.64	39.52	43.50	-3.98	QP
2	311.979	50.43	-12.41	38.02	46.00	-7.98	QP
3	408.009	46.38	-10.11	36.27	46.00	-9.73	QP
4	504.007	46.56	-8.10	38.46	46.00	-7.54	QP
5	696.002	43.25	-5.06	38.19	46.00	-7.81	QP
6	792.000	43.83	-3.78	40.05	46.00	-5.95	QP

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Test EUT Mode : RRQ61051-009

(Worst case is BLE(1M) mode, Low Channel)

Low channel


Horizontal



Site : 966B Chamber
Condition: 3m horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 19.5℃/ 45%
Memo : BLE-1M-TX-2402
RBW/VBW : QP:120k/500k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	215.981	54.54	-15.64	38.90	43.50	-4.60	QP
2	311.979	52.00	-12.41	39.59	46.00	-6.41	QP
3	407.977	52.72	-10.11	42.61	46.00	-3.39	QP
4	504.007	47.97	-8.10	39.87	46.00	-6.13	QP
5	792.000	41.89	-3.78	38.11	46.00	-7.89	QP
6	887.997	41.67	-2.73	38.94	46.00	-7.06	QP

Vertical



Site : 966B Chamber
Condition: 3m vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 19.5℃/ 45%
Memo : BLE-1M-TX-2402
RBW/VBW : QP:120k/500k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	215.981	49.69	-15.64	34.05	43.50	-9.45	QP
2	311.979	47.44	-12.41	35.03	46.00	-10.97	QP
3	407.977	46.63	-10.11	36.52	46.00	-9.48	QP
4	504.007	43.16	-8.10	35.06	46.00	-10.94	QP
5	696.002	39.65	-5.06	34.59	46.00	-11.41	QP
6	792.000	39.46	-3.78	35.68	46.00	-10.32	QP

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Test EUT Mode : RRQ61051-010

30MHz-1GHz:


(worst case is 802.11 ax20 mode, High Channel)

High channel	
Horizontal	**Vertical**



Site : 966B Chamber
Condition: 3m horizontal
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 53%
Memo : AX20-TX-2462
Memo : RBW/VBW: QP:120k/500k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	30.388	38.59	-3.04	35.55	40.00	-4.45	QP
2	119.984	45.89	-12.30	33.59	43.50	-9.91	QP
3	311.979	49.00	-12.41	36.59	46.00	-9.41	QP
4	408.009	50.12	-10.11	40.01	46.00	-5.99	QP
5	504.007	42.57	-8.10	34.47	46.00	-11.53	QP
6	696.002	41.01	-5.06	35.95	46.00	-10.05	QP



Site : 966B Chamber
Condition: 3m vertical
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 53%
Memo : AX20-TX-2462
Memo : RBW/VBW: QP:120k/500k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	30.453	37.93	-3.06	34.87	40.00	-5.13	QP
2	119.984	40.85	-12.30	28.55	43.50	-14.95	QP
3	311.979	43.60	-12.41	31.19	46.00	-14.81	QP
4	407.977	43.39	-10.11	33.28	46.00	-12.72	QP
5	504.007	40.26	-8.10	32.16	46.00	-13.84	QP
6	696.002	37.02	-5.06	31.96	46.00	-14.04	QP


Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Test EUT Mode : RRQ61051-010


(Worst case is BLE(1M) mode, Low Channel)

Low channel	
Horizontal	**Vertical**



Site : 966B Chamber
Condition: 3m horizontal
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 53%
Memo : BLE-1M-TX-2402
Memo : RBW/VBW: QP:120k/500k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	30.162	38.19	-2.92	35.27	40.00	-4.73	QP
2	119.984	45.62	-12.30	33.32	43.50	-10.18	QP
3	311.979	48.00	-12.41	35.59	46.00	-10.41	QP
4	407.977	49.62	-10.11	39.51	46.00	-6.49	QP
5	696.002	41.29	-5.06	36.23	46.00	-9.77	QP
6	792.000	38.24	-3.78	34.46	46.00	-11.54	QP



Site : 966B Chamber
Condition: 3m vertical
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 53%
Memo : BLE-1M-TX-2402
Memo : RBW/VBW: QP:120k/500k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	31.067	37.42	-3.36	34.06	40.00	-5.94	QP
2	311.979	42.20	-12.41	29.79	46.00	-16.21	QP
3	408.009	43.76	-10.11	33.65	46.00	-12.35	QP
4	503.974	40.10	-8.10	32.00	46.00	-14.00	QP
5	696.002	36.18	-5.06	31.12	46.00	-14.88	QP
6	936.012	32.48	-1.90	30.58	46.00	-15.42	QP

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


Test EUT Mode : RRQ61051-009

802.11b Mode

1GHz-18GHz:

Low channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : B-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2110.667	53.04	-1.37	51.67	74.00	-22.33	Peak
2	2110.667	45.20	-1.37	43.83	54.00	-10.17	Average
3	3015.067	52.77	-0.18	52.59	86.85	-34.26	Peak
4	3015.067	46.76	-0.18	46.58	66.85	-20.27	Average
5	3215.667	62.44	0.34	62.78	86.85	-24.07	Peak
6	3215.667	62.80	0.34	63.14	66.85	-3.71	Average
7	4824.000	51.33	3.27	54.60	74.00	-19.40	Peak
8 !	4824.000	49.96	3.27	53.23	54.00	-0.77	Average
9	7236.000	44.42	9.42	53.84	74.00	-20.16	Peak
10	7237.000	31.54	9.43	40.97	54.00	-13.03	Average

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : B-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	3216.233	51.29	0.35	51.64	74.00	-22.36	Peak
2	3216.233	41.39	0.35	41.74	54.00	-12.26	Average
3	4824.000	42.85	3.27	46.12	74.00	-27.88	Peak
4	4824.000	39.73	3.27	43.00	54.00	-11.00	Average
5	7236.000	41.25	9.42	50.67	74.00	-23.33	Peak
6	7236.000	28.61	9.42	38.03	54.00	-15.97	Average

Middle channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : B-TX-2437
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2132.200	54.20	-1.68	52.52	74.00	-21.48	Peak
2	2132.200	46.31	-1.68	44.63	54.00	-9.37	Average
3	3249.667	57.76	0.55	58.31	86.48	-28.17	Peak
4	3249.667	55.68	0.55	56.23	66.48	-10.25	Average
5	4874.000	48.55	3.43	51.98	74.00	-22.02	Peak
6	4874.000	46.93	3.43	50.36	54.00	-3.64	Average
7	7311.000	43.13	9.60	52.73	74.00	-21.27	Peak
8	7311.000	30.66	9.60	40.26	54.00	-13.74	Average

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : B-TX-2437
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	4874.000	44.74	3.43	48.17	74.00	-25.83	Peak
2	4874.000	41.24	3.43	44.67	54.00	-9.33	Average
3	7311.000	40.21	9.60	49.81	74.00	-24.19	Peak
4	7311.000	27.06	9.60	36.66	54.00	-17.34	Average


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

High channel	
Horizontal	**Vertical**



Trace: 1
Site : 966B Chamber
Condition: 3m horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : B-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2154.300	53.71	-1.96	51.75	74.00	-22.25	Peak
2	2154.300	48.14	-1.96	46.18	54.00	-7.82	Average
3	2769.700	52.40	-0.89	51.51	74.00	-22.49	Peak
4	2769.700	43.72	-0.89	42.83	54.00	-11.17	Average
5	3282.533	56.61	0.57	57.18	74.00	-16.82	Peak
6 !	3282.533	52.61	0.57	53.18	54.00	-0.82	Average
7	4924.000	49.10	3.54	52.64	74.00	-21.36	Peak
8 !	4924.000	47.94	3.54	51.48	54.00	-2.52	Average
9	7386.000	42.56	9.77	52.33	74.00	-21.67	Peak
10	7386.000	30.35	9.77	40.12	54.00	-13.88	Average



Trace: 1
Site : 966B Chamber
Condition: 3m vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : B-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2154.300	50.42	-1.96	48.46	74.00	-25.54	Peak
2	2154.300	29.99	-1.96	28.03	54.00	-25.97	Average
3	4924.000	42.15	3.54	45.69	74.00	-28.31	Peak
4	4924.000	39.18	3.54	42.72	54.00	-11.28	Average
5	7386.000	39.40	9.77	49.17	74.00	-24.83	Peak
6	7386.000	27.54	9.77	37.31	54.00	-16.69	Average

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain
For Not Restricted bands of operation Limit.
Convert the Main Frequency Peak Power -20dB=Peak Limit
Convert the Main Frequency Peak Power -40dB=Average Limit
802.11b Low channel Horizontal For Not Restricted bands of operation Limit :
Peak Limit =106.85dB -20dB=86.85 dBuV/m
Average Limit =106.85dB -40dB=66.85dBuV/m
802.11b Middle channel Horizontal For Not Restricted bands of operation Limit :
Peak Limit =106.48dB -20dB=86.48 dBuV/m
Average Limit =106.48dB -40dB=66.48 dBuV/m


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

802.11g Mode

1GHz-18GHz:

Low channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : G-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2110.100	51.23	-1.36	49.87	74.00	-24.13	Peak
2	2110.100	45.67	-1.36	44.31	54.00	-9.69	Average
3	3215.233	57.59	0.34	57.93	66.00	-8.07	Average
4	3216.233	60.17	0.35	60.52	86.00	-25.48	Peak
5	4824.000	49.90	3.27	53.17	74.00	-20.83	Peak
6	4824.000	38.31	3.27	41.58	54.00	-12.42	Average
7	7236.000	36.52	9.42	45.94	74.00	-28.06	Peak
8	7236.000	27.97	9.42	37.39	54.00	-16.61	Average

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : G-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	3216.233	40.61	0.35	40.96	54.00	-13.04	Average
2	3216.233	47.72	0.35	48.07	74.00	-25.93	Peak
3	4824.000	27.37	3.27	30.64	54.00	-23.36	Average
4	4824.000	37.38	3.27	40.65	74.00	-33.35	Peak
5	7236.000	25.70	9.42	35.12	54.00	-18.88	Average
6	7236.000	35.80	9.42	45.22	74.00	-28.78	Peak

Middle channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : G-TX-2437
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2132.200	55.40	-1.68	53.72	74.00	-20.28	Peak
2	2132.200	50.70	-1.68	49.02	54.00	-4.98	Average
3	2438.767	50.09	-2.08	48.01	74.00	-25.99	Peak
4	2438.767	38.53	-2.08	36.45	54.00	-17.55	Average
5	3249.100	58.81	0.54	59.35	86.47	-27.12	Peak
6	3249.100	56.28	0.54	56.82	66.47	-9.65	Average
7	4874.000	46.25	3.43	49.68	74.00	-24.32	Peak
8	4874.000	35.81	3.43	39.24	54.00	-14.76	Average
9	7311.000	40.45	9.60	50.05	74.00	-23.95	Peak
10	7311.000	27.18	9.60	36.78	54.00	-17.22	Average

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : G-TX-2437
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	3249.667	40.31	0.55	40.86	54.00	-13.14	Average
2	3249.667	47.48	0.55	48.03	74.00	-25.97	Peak
3	4874.000	27.22	3.43	30.65	54.00	-23.35	Average
4	4874.000	35.84	3.43	39.27	74.00	-34.73	Peak
5	7311.000	25.52	9.60	35.12	54.00	-18.88	Average
6	7311.000	34.76	9.60	44.36	74.00	-29.64	Peak

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

High channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : G-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2154.300	49.35	-1.96	47.39	54.00	-6.61	Average
2	2154.300	54.22	-1.96	52.26	74.00	-21.74	Peak
3	2772.533	42.91	-0.91	42.00	54.00	-12.00	Average
4	2772.533	50.94	-0.91	50.03	74.00	-23.97	Peak
5 !	3282.533	51.49	0.57	52.06	54.00	-1.94	Average
6	3282.533	56.30	0.57	56.87	74.00	-17.13	Peak
7	4924.000	35.33	3.54	38.87	54.00	-15.13	Average
8	4924.000	46.00	3.54	49.54	74.00	-24.46	Peak
9	7386.000	24.98	9.77	34.75	54.00	-19.25	Average
10	7386.000	39.38	9.77	49.15	74.00	-24.85	Peak

Vertical



Trace: 1
Site : 966B Chamber
Condition: 3m vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : G-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	4924.000	27.26	3.54	30.80	54.00	-23.20	Average
2	4924.000	35.90	3.54	39.44	74.00	-34.56	Peak
3	7386.000	25.27	9.77	35.04	54.00	-18.96	Average
4	7386.000	35.54	9.77	45.31	74.00	-28.69	Peak

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain
For Not Restricted bands of operation Limit.
Convert the Main Frequency Peak Power -20dB=Peak Limit
Convert the Main Frequency Peak Power -40dB=Average Limit
802.11g Low channel Horizontal For Not Restricted bands of operation Limit :
Peak Limit =106.00dB -20dB=86.00 dBuV/m
Average Limit =106.00dB -40dB=66.00dBuV/m
802.11g Middle channel Horizontal For Not Restricted bands of operation Limit :
Peak Limit =106.47dB -20dB=86.47 dBuV/m
Average Limit =106.47dB -40dB=66.47 dBuV/m


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

802.11n HT20 Mode

1GHz-18GHz:

Low channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : N20-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/5k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2110.667	52.19	-1.37	50.82	74.00	-23.18	Peak
2	2110.667	44.83	-1.37	43.46	54.00	-10.54	Average
3	3216.233	61.37	0.35	61.72	84.37	-22.65	Peak
4	3216.233	57.44	0.35	57.79	64.37	-6.58	Average
5	4824.000	47.99	3.27	51.26	74.00	-22.74	Peak
6	4824.000	38.08	3.27	41.35	54.00	-12.65	Average
7	7236.000	36.97	9.42	46.39	74.00	-27.61	Peak
8	7236.000	27.92	9.42	37.34	54.00	-16.66	Average

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : N20-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/5k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	4824.000	36.97	3.27	40.24	74.00	-33.76	Peak
2	4824.000	28.23	3.27	31.50	54.00	-22.50	Average
3	7236.000	37.35	9.42	46.77	74.00	-27.23	Peak
4	7236.000	25.84	9.42	35.26	54.00	-18.74	Average

Middle channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : N20-TX-2437
Memo : RBW/VBW: PK:1M/3M; AV:1M/5k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2132.200	54.34	-1.68	52.66	74.00	-21.34	Peak
2	2132.200	48.97	-1.68	47.29	54.00	-6.71	Average
3	3249.100	58.35	0.54	58.89	74.00	-15.11	Peak
4 !	3249.100	53.06	0.54	53.60	54.00	-0.40	Average
5	4874.000	46.68	3.43	50.11	74.00	-23.89	Peak
6	4874.000	36.49	3.43	39.92	54.00	-14.08	Average
7	7311.000	35.75	9.60	45.35	74.00	-28.65	Peak
8	7311.000	26.34	9.60	35.94	54.00	-18.06	Average

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : N20-TX-2437
Memo : RBW/VBW: PK:1M/3M; AV:1M/5k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2000.167	48.55	-1.75	46.80	74.00	-27.20	Peak
2	2000.167	28.37	-1.75	26.62	54.00	-27.38	Average
3	4874.000	38.18	3.43	41.61	74.00	-32.39	Peak
4	4874.000	28.23	3.43	31.66	54.00	-22.34	Average
5	7311.000	34.64	9.60	44.24	74.00	-29.76	Peak
6	7311.000	25.58	9.60	35.18	54.00	-18.82	Average

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

High channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : N20-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/5k

		Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1		2154.300	56.89	-1.96	54.93	74.00	-19.07	Peak
2		2154.300	49.73	-1.96	47.77	54.00	-6.23	Average
3		2771.967	52.07	-0.90	51.17	74.00	-22.83	Peak
4		2771.967	42.24	-0.90	41.34	54.00	-12.66	Average
5	!	3282.100	51.53	0.57	52.10	54.00	-1.90	Average
6		3283.100	56.83	0.57	57.40	74.00	-16.60	Peak
7		4924.000	45.75	3.54	49.29	74.00	-24.71	Peak
8		4924.000	34.82	3.54	38.36	54.00	-15.64	Average
9		7386.000	36.96	9.77	46.73	74.00	-27.27	Peak
10		7386.000	24.84	9.77	34.61	54.00	-19.39	Average

Vertical



Trace: 1
Site : 966B Chamber
Condition: 3m vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : N20-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/5k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	4924.000	37.22	3.54	40.76	74.00	-33.24	Peak
2	4924.000	25.15	3.54	28.69	54.00	-25.31	Average
3	7386.000	35.06	9.77	44.83	74.00	-29.17	Peak
4	7386.000	25.38	9.77	35.15	54.00	-18.85	Average

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain
For Not Restricted bands of operation Limit.
Convert the Main Frequency Peak Power -20dB=Peak Limit
Convert the Main Frequency Peak Power -40dB=Average Limit
802.11n20 Low channel Horizontal For Not Restricted bands of operation Limit :
Peak Limit =104.37dB -20dB=84.37 dBuV/m
Average Limit =104.37dB -40dB=64.37dBuV/m


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

802.11ax HE20 Mode

1GHz-18GHz:

Low channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : AX20-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2110.100	50.61	-1.36	49.25	74.00	-24.75	Peak
2	2110.100	44.00	-1.36	42.64	54.00	-11.36	Average
3	3216.233	60.19	0.35	60.54	87.83	-27.29	Peak
4	3216.233	55.24	0.35	55.59	67.83	-12.24	Average
5	4824.000	48.91	3.27	52.18	74.00	-21.82	Peak
6	4824.000	38.51	3.27	41.78	54.00	-12.22	Average
7	7236.000	35.47	9.42	44.89	74.00	-29.11	Peak
8	7236.000	26.79	9.42	36.21	54.00	-17.79	Average

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : AX20-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	3215.667	36.18	0.34	36.52	54.00	-17.48	Average
2	3215.667	46.91	0.34	47.25	74.00	-26.75	Peak
3	4824.000	27.03	3.27	30.30	54.00	-23.70	Average
4	4824.000	36.46	3.27	39.73	74.00	-34.27	Peak
5	7236.000	25.94	9.42	35.36	54.00	-18.64	Average
6	7236.000	35.72	9.42	45.14	74.00	-28.86	Peak

Middle channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : AX20-TX-2437
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2132.767	54.49	-1.70	52.79	74.00	-21.21	Peak
2	2132.767	50.02	-1.70	48.32	54.00	-5.68	Average
3	3249.100	61.71	0.54	62.25	88.64	-26.39	Peak
4	3249.100	55.29	0.54	55.83	68.64	-12.81	Average
5	4874.000	44.08	3.43	47.51	74.00	-26.49	Peak
6	4874.000	35.79	3.43	39.22	54.00	-14.78	Average
7	7311.000	36.66	9.60	46.26	74.00	-27.74	Peak
8	7311.000	25.72	9.60	35.32	54.00	-18.68	Average

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : AX20-TX-2437
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	3249.667	37.53	0.55	38.08	54.00	-15.92	Average
2	3249.667	48.61	0.55	49.16	74.00	-24.84	Peak
3	4874.000	26.29	3.43	29.72	54.00	-24.28	Average
4	4874.000	37.08	3.43	40.51	74.00	-33.49	Peak
5	7311.000	25.54	9.60	35.14	54.00	-18.86	Average
6	7311.000	35.60	9.60	45.20	74.00	-28.80	Peak

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

High channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2154.300	49.80	-1.96	47.84	54.00	-6.16	Average
2	2154.300	54.99	-1.96	53.03	74.00	-20.97	Peak
3	2463.133	38.12	-2.32	35.80	54.00	-18.20	Average
4	2463.133	49.73	-2.32	47.41	74.00	-26.59	Peak
5	2772.533	42.24	-0.91	41.33	54.00	-12.67	Average
6	2772.533	51.22	-0.91	50.31	74.00	-23.69	Peak
7 !	3282.533	51.46	0.57	52.03	54.00	-1.97	Average
8	3282.533	57.34	0.57	57.91	74.00	-16.09	Peak
9	4924.000	35.25	3.54	38.79	54.00	-15.21	Average
10	4924.000	43.02	3.54	46.56	74.00	-27.44	Peak
11	7386.000	25.18	9.77	34.95	54.00	-19.05	Average
12	7386.000	36.46	9.77	46.23	74.00	-27.77	Peak

Vertical



Trace: 1
Site : 966B Chamber
Condition: 3m vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	4924.000	26.64	3.54	30.18	54.00	-23.82	Average
2	4924.000	37.33	3.54	40.87	74.00	-33.13	Peak
3	7386.000	25.04	9.77	34.81	54.00	-19.19	Average
4	7386.000	34.77	9.77	44.54	74.00	-29.46	Peak

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain
For Not Restricted bands of operation Limit.
Convert the Main Frequency Peak Power -20dB=Peak Limit
Convert the Main Frequency Peak Power -40dB=Average Limit
802.11ax20 Low channel Horizontal For Not Restricted bands of operation Limit :
Peak Limit =107.83dB -20dB=87.83 dBuV/m
Average Limit =107.83dB -40dB=67.83 dBuV/m
802.11 ax 20 Middle channel Horizontal For Not Restricted bands of operation Limit :
Peak Limit =108.64dB -20dB=88.64 dBuV/m
Average Limit =108.64dB -40dB=68.64dBuV/m


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Test EUT Mode : RRQ61051-009

Main Frequency Power

802.11b


Low channel Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : B-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2389.180	52.84	-2.04	50.80	54.00	-3.20	Average
2	2389.180	63.12	-2.04	61.08	74.00	-12.92	Peak
3	2411.674	104.40	-2.12	102.28	------	------	Average
4	2411.674	108.97	-2.12	106.85	------	------	Peak

Middle channel Horizontal




Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : B-TX-2437
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2437.459	108.56	-2.08	106.48	------	------	Peak

802.11g


Low channel Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : See Ch 1
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : G-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1 !	2389.938	75.25	-2.02	73.23	74.00	-0.77	Peak
2 !	2389.938	55.78	-2.02	53.76	54.00	-0.24	Average
3	2410.244	108.10	-2.10	106.00	------	------	Peak
4	2413.940	97.64	-2.14	95.50	------	------	Average

Middle channel Horizontal




Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : G-TX-2437
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2435.093	108.55	-2.08	106.47	------	------	Peak

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

802.11n20

Low channel Horizontal




Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : N20-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/5k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2388.896	70.89	-2.04	68.85	74.00	-5.15	Peak
2	2388.896	51.94	-2.04	49.90	54.00	-4.10	Average
3	2389.725	63.30	-2.03	61.27	74.00	-12.73	Peak
4 !	2389.725	53.35	-2.03	51.32	54.00	-2.68	Average
5	2410.875	106.47	-2.10	104.37	------	------	Peak
6	2410.875	96.18	-2.11	94.07	------	------	Average

802.11ax20


Low channel Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : AX20-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1 !	2388.714	54.43	-2.05	52.38	54.00	-1.62	Average
2 !	2388.714	75.36	-2.05	73.31	74.00	-0.69	Peak
3 !	2389.960	55.74	-2.02	53.72	54.00	-0.28	Average
4	2389.960	68.07	-2.02	66.05	74.00	-7.95	Peak
5	2413.122	96.29	-2.13	94.16	------	------	Average
6	2413.122	109.96	-2.13	107.83	------	------	Peak

Middle channel Horizontal



Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : AX20-TX-2437
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2434.976	110.72	-2.08	108.64	------	------	Peak


Test EUT Mode : RRQ61051-009

BLE(1M) Mode

1GHz-18GHz:

Low channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.6℃/ 59%
Memo : BLE-1M-TX-2402
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	1000.000	58.66	-7.95	50.71	74.00	-23.29	Peak
2	1000.000	42.87	-7.95	34.92	54.00	-19.08	Average
3	4804.000	45.08	3.18	48.26	74.00	-25.74	Peak
4	4804.000	40.85	3.18	44.03	54.00	-9.97	Average
5	7206.000	36.34	9.27	45.61	74.00	-28.39	Peak
6	7206.000	26.12	9.27	35.39	54.00	-18.61	Average

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.6℃/ 59%
Memo : BLE-1M-TX-2402
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	4804.000	40.14	3.18	43.32	74.00	-30.68	Peak
2	4804.000	35.03	3.18	38.21	54.00	-15.79	Average
3	7206.000	36.84	9.27	46.11	74.00	-27.89	Peak
4	7206.000	25.88	9.27	35.15	54.00	-18.85	Average

Middle channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.6℃/ 59%
Memo : BLE-1M-TX-2440
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	4880.000	42.91	3.44	46.35	74.00	-27.65	Peak
2	4880.000	38.95	3.44	42.39	54.00	-11.61	Average
3	7320.000	37.15	9.63	46.78	74.00	-27.22	Peak
4	7320.000	25.35	9.63	34.98	54.00	-19.02	Average

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.6℃/ 59%
Memo : BLE-1M-TX-2440
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	4880.000	37.11	3.44	40.55	74.00	-33.45	Peak
2	4880.000	31.86	3.44	35.30	54.00	-18.70	Average
3	7320.000	35.60	9.63	45.23	74.00	-28.77	Peak
4	7320.000	25.66	9.63	35.29	54.00	-18.71	Average


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

High channel	
Horizontal	**Vertical**



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.6℃/ 59%
Memo : BLE-1M-TX-2480
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	4960.000	42.16	3.62	45.78	74.00	-28.22	Peak
2	4960.000	36.92	3.62	40.54	54.00	-13.46	Average
3	7440.000	35.93	9.93	45.86	74.00	-28.14	Peak
4	7440.000	25.40	9.93	35.33	54.00	-18.67	Average



Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.6℃/ 59%
Memo : BLE-1M-TX-2480
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	4960.000	37.53	3.62	41.15	74.00	-32.85	Peak
2	4960.000	32.13	3.62	35.75	54.00	-18.25	Average
3	7440.000	34.78	9.93	44.71	74.00	-29.29	Peak
4	7440.000	25.41	9.93	35.34	54.00	-18.66	Average


Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Test EUT Mode : RRQ61051-009


18GHz-26.5GHz:

WiFi 2.4G High channel	
Horizontal	**Vertical**



Trace: 1
Site : 966B Chamber
Condition: 1.5m horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 19.5℃/ 45%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	22359.370	48.49	1.01	49.50	80.00	-30.50	Peak
2	22359.370	35.38	1.01	36.39	60.00	-23.61	Average



Trace: 1
Site : 966B Chamber
Condition: 1.5m vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 19.5℃/ 45%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	22141.480	35.08	0.78	35.86	60.00	-24.14	Average
2	22141.480	49.09	0.78	49.87	80.00	-30.13	Peak


Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain
For 18-26.5GHz Convert the test distance limit of 3 meters to a limit of 1.5 meter:
Conversion factor = 20 log (1.5m/3m) = 6 dB,
Average Limit = 54+6 = 60 dBuV/m@1.5m , Peak Limit = 60+20 = 80 dBuV/m@1.5m

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Test EUT Mode : RRQ61051-009


18GHz-26.5GHz:

BLE(1M) Low channel	
Horizontal	**Vertical**



Trace: 1
Site : 966B Chamber
Condition: 1.5m horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 19.5℃/ 45%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	22359.370	48.49	1.01	49.50	80.00	-30.50	Peak
2	22359.370	35.38	1.01	36.39	60.00	-23.61	Average



Trace: 1
Site : 966B Chamber
Condition: 1.5m vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 19.5℃/ 45%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	22141.480	35.08	0.78	35.86	60.00	-24.14	Average
2	22141.480	49.09	0.78	49.87	80.00	-30.13	Peak

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain
For 18-26.5GHz Convert the test distance limit of 3 meters to a limit of 1.5 meter:
Conversion factor = 20 log (1.5m/3m) = 6 dB,
Average Limit = 54+6 = 60 dBuV/m@1.5m , Peak Limit = 60+20 = 80 dBuV/m@1.5m

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


Test EUT Mode : RRQ61051-010

802.11ax HE20 Mode (Worst case is 802.11ax20 mode, High Channel)

1GHz-26.5GHz:

High channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m horizontal
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 57%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2154.300	54.83	-1.96	52.87	74.00	-21.13	Peak
2	2154.300	48.80	-1.96	46.84	54.00	-7.16	Average
3	2460.300	47.78	-2.36	45.42	74.00	-28.58	Peak
4	2460.300	39.43	-2.36	37.07	54.00	-16.93	Average
5	2775.367	53.88	-0.93	52.95	74.00	-21.05	Peak
6	2775.367	44.15	-0.93	43.22	54.00	-10.78	Average
7	3282.533	56.37	0.57	56.94	74.00	-17.06	Peak
8 !	3282.533	51.49	0.57	52.06	54.00	-1.94	Average
9	4924.000	45.06	3.54	48.60	74.00	-25.40	Peak
10	4924.000	34.79	3.54	38.33	54.00	-15.67	Average
11	7386.000	35.00	9.77	44.77	74.00	-29.23	Peak
12	7386.000	24.80	9.77	34.57	54.00	-19.43	Average


Vertical



Trace: 1
Site : 966B Chamber
Condition: 3m vertical
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 57%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	4924.000	40.32	3.54	43.86	74.00	-30.14	Peak
2	4924.000	31.05	3.54	34.59	54.00	-19.41	Average
3	7386.000	34.72	9.77	44.49	74.00	-29.51	Peak
4	7386.000	23.69	9.77	33.46	54.00	-20.54	Average


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 1.5m horizontal
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 57%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	24284.050	48.80	1.79	50.59	80.00	-29.41	Peak
2	24284.050	34.30	1.79	36.09	60.00	-23.91	Average

Vertical



Trace: 1
Site : 966B Chamber
Condition: 1.5m vertical
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 57%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	22060.170	49.08	0.67	49.75	80.00	-30.25	Peak
2	22060.170	34.99	0.67	35.66	60.00	-24.34	Average

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain
For 18-26.5GHz Convert the test distance limit of 3 meters to a limit of 1.5 meter:
Conversion factor = 20 log (1.5m/3m) = 6 dB,
Average Limit = 54+6 = 60 dBuV/m@1.5m , Peak Limit = 60+20 = 80 dBuV/m@1.5m

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


Test EUT Mode : RRQ61051-010

BLE(1M) Mode (Worst case is BLE(1M) mode, Low Channel)

1GHz-26.5GHz:

Low channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 57%
Memo : BLE-1M-TX-2402
Memo : RBW/VBW: PK:1M/3M AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	3215.667	45.68	0.34	46.02	74.00	-27.98	Peak
2	3215.667	38.87	0.34	39.21	54.00	-14.79	Average
3	4804.000	41.68	3.18	44.86	74.00	-29.14	Peak
4	4804.000	37.65	3.18	40.83	54.00	-13.17	Average
5	7206.000	35.31	9.27	44.58	74.00	-29.42	Peak
6	7206.000	25.54	9.27	34.81	54.00	-19.19	Average


Vertical



Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 57%
Memo : BLE-1M-TX-2402
Memo : RBW/VBW: PK:1M/3M AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	3215.667	45.81	0.34	46.15	74.00	-27.85	Peak
2	3215.667	29.61	0.34	29.95	74.00	-44.05	Peak
3	4804.000	38.72	3.18	41.90	74.00	-32.10	Peak
4	4804.000	33.63	3.18	36.81	54.00	-17.19	Average
5	7206.000	35.80	9.27	45.07	74.00	-28.93	Peak
6	7206.000	25.28	9.27	34.55	54.00	-19.45	Average


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 1.5m horizontal
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 57%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	24284.050	48.80	1.79	50.59	80.00	-29.41	Peak
2	24284.050	34.30	1.79	36.09	60.00	-23.91	Average

Vertical



Trace: 1
Site : 966B Chamber
Condition: 1.5m vertical
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 57%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	22060.170	49.08	0.67	49.75	80.00	-30.25	Peak
2	22060.170	34.99	0.67	35.66	60.00	-24.34	Average

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain
For 18-26.5GHz Convert the test distance limit of 3 meters to a limit of 1.5 meter:
Conversion factor = 20 log (1.5m/3m) = 6 dB,
Average Limit = 54+6 = 60 dBuV/m@1.5m , Peak Limit = 60+20 = 80 dBuV/m@1.5m

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


Band-Edge:

Test EUT Mode : RRQ61051-009

802.11b Mode

Low channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : B-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2389.180	52.84	-2.04	50.80	54.00	-3.20	Average
2	2389.180	63.12	-2.04	61.08	74.00	-12.92	Peak
3	2411.674	104.40	-2.12	102.28	------	------	Average
4	2411.674	108.97	-2.12	106.85	------	------	Peak

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : B-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2389.094	46.09	-2.04	44.05	54.00	-9.95	Average
2	2389.094	54.19	-2.04	52.15	74.00	-21.85	Peak
3	2389.976	44.30	-2.02	42.28	54.00	-11.72	Average
4	2389.976	56.49	-2.02	54.47	74.00	-19.53	Peak
5	2412.450	98.97	-2.12	96.85	------	------	Average
6	2412.450	104.07	-2.12	101.95	------	------	Peak

High channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : B-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2461.768	102.74	-2.33	100.41	------	------	Average
2	2461.768	107.85	-2.33	105.52	------	------	Peak
3	2484.902	49.11	-2.08	47.03	54.00	-6.97	Average
4	2484.902	61.55	-2.08	59.47	74.00	-14.53	Peak
5	2491.024	50.32	-2.03	48.29	54.00	-5.71	Average
6	2491.024	58.47	-2.03	56.44	74.00	-17.56	Peak

Vertical



Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : B-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2461.606	92.56	-2.33	90.23	------	------	Average
2	2461.606	98.24	-2.33	95.91	------	------	Peak
3	2487.237	37.48	-2.06	35.42	54.00	-18.58	Average
4	2487.237	50.67	-2.06	48.61	74.00	-25.39	Peak
5	2491.392	38.31	-2.03	36.28	54.00	-17.72	Average
6	2491.392	46.65	-2.03	44.62	74.00	-29.38	Peak


Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

802.11g Mode

Low channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : G-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1 !	2389.938	55.78	-2.02	53.76	54.00	-0.24	Average
2 !	2389.938	75.25	-2.02	73.23	74.00	-0.77	Peak
3	2410.244	97.60	-2.10	95.50	------	------	Average
4	2410.244	108.10	-2.10	106.00	------	------	Peak

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : G-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2388.964	47.44	-2.04	45.40	54.00	-8.60	Average
2	2388.964	66.42	-2.04	64.38	74.00	-9.62	Peak
3	2389.938	49.02	-2.02	47.00	54.00	-7.00	Average
4	2389.938	60.65	-2.02	58.63	74.00	-15.37	Peak
5	2414.511	93.07	-2.15	90.92	------	------	Average
6	2414.511	102.26	-2.15	100.11	------	------	Peak

High channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : G-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2459.920	98.27	-2.36	95.91	------	------	Average
2	2459.920	107.63	-2.36	105.27	------	------	Peak
3 !	2483.694	54.65	-2.09	52.56	54.00	-1.44	Average
4	2483.694	73.00	-2.09	70.91	74.00	-3.09	Peak
5 !	2484.281	55.51	-2.09	53.42	54.00	-0.58	Average
6	2484.281	67.32	-2.09	65.23	74.00	-8.77	Peak

Vertical



Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : G-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2460.202	89.14	-2.36	86.78	------	------	Average
2	2460.202	98.92	-2.36	96.56	------	------	Peak
3	2483.500	41.13	-2.10	39.03	54.00	-14.97	Average
4	2483.500	50.02	-2.10	47.92	74.00	-26.08	Peak
5	2488.152	38.89	-2.05	36.84	54.00	-17.16	Average
6	2488.152	55.21	-2.05	53.16	74.00	-20.84	Peak


Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

802.11n HT20 Mode

Low channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : N20-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/5k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2388.896	70.89	-2.04	68.85	74.00	-5.15	Peak
2	2388.896	51.94	-2.04	49.90	54.00	-4.10	Average
3	2389.725	63.30	-2.03	61.27	74.00	-12.73	Peak
4 !	2389.725	53.35	-2.03	51.32	54.00	-2.68	Average
5	2410.875	106.47	-2.10	104.37	------	------	Peak
6	2410.875	96.18	-2.11	94.07	------	------	Average

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61001-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : N20-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/5k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2389.307	61.19	-2.03	59.16	74.00	-14.84	Peak
2	2389.307	46.03	-2.03	44.00	54.00	-10.00	Average
3	2413.574	100.53	-2.10	98.43	------	------	Peak
4	2413.574	91.01	-2.14	88.87	------	------	Average

High channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61001-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : N20-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/5k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2463.846	105.95	-2.32	103.63	------	------	Peak
2	2463.846	96.67	-2.31	94.36	------	------	Average
3	2483.584	63.06	-2.09	60.97	74.00	-13.03	Peak
4 !	2483.584	54.05	-2.09	51.96	54.00	-2.04	Average
5	2485.994	70.14	-2.07	68.07	74.00	-5.93	Peak
6	2485.994	51.97	-2.07	49.90	54.00	-4.10	Average

Vertical



Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61001-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : N20-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/5k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2460.229	97.11	-2.36	94.75	------	------	Peak
2	2460.229	87.62	-2.36	85.26	------	------	Average
3	2483.757	55.45	-2.09	53.36	74.00	-20.64	Peak
4	2483.757	40.63	-2.09	38.54	54.00	-15.46	Average


Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

802.11ax HE20 Mode

Low channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : AX20-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1 !	2388.714	54.43	-2.05	52.38	54.00	-1.62	Average
2 !	2388.714	75.36	-2.05	73.31	74.00	-0.69	Peak
3 !	2389.960	55.74	-2.02	53.72	54.00	-0.28	Average
4	2389.960	68.07	-2.02	66.05	74.00	-7.95	Peak
5	2413.122	96.29	-2.13	94.16	------	------	Average
6	2413.122	109.96	-2.13	107.83	------	------	Peak

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : AX20-TX-2412
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2389.206	47.94	-2.04	45.90	54.00	-8.10	Average
2	2389.206	68.13	-2.04	66.09	74.00	-7.91	Peak
3	2389.875	48.95	-2.02	46.93	54.00	-7.07	Average
4	2389.875	63.06	-2.02	61.04	74.00	-12.96	Peak
5	2412.868	91.48	-2.13	89.35	------	------	Average
6	2412.868	104.16	-2.13	102.03	------	------	Peak

High channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2463.066	96.71	-2.32	94.39	------	------	Average
2	2463.066	109.73	-2.32	107.41	------	------	Peak
3 !	2483.829	55.78	-2.09	53.69	54.00	-0.31	Average
4 !	2483.829	73.43	-2.09	71.34	74.00	-2.66	Peak
5 !	2485.430	54.20	-2.08	52.12	54.00	-1.88	Average
6 !	2485.430	74.82	-2.08	72.74	74.00	-1.26	Peak

Vertical



Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 22.1℃/ 54%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2459.875	88.18	-2.36	85.82	------	------	Average
2	2459.875	100.88	-2.36	98.52	------	------	Peak
3	2483.792	42.34	-2.09	40.25	54.00	-13.75	Average
4	2483.792	59.80	-2.09	57.71	74.00	-16.29	Peak

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Test EUT Mode : RRQ61051-009

BLE(1M) Mode

Low channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.6℃/ 59%
Memo : BLE-1M-TX-2402
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2384.633	35.94	-2.13	33.81	74.00	-40.19	Peak
2	2384.633	29.25	-2.13	27.12	54.00	-26.88	Average
3	2389.743	50.15	-2.03	48.12	74.00	-25.88	Peak
4	2389.743	27.00	-2.03	24.97	54.00	-29.03	Average
5	2402.150	91.19	-2.03	89.16	------	------	Peak
6	2402.150	90.29	-2.03	88.26	------	------	Average

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.6℃/ 59%
Memo : BLE-1M-TX-2402
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2324.980	38.96	-2.23	36.73	74.00	-37.27	Peak
2	2324.980	25.38	-2.23	23.15	54.00	-30.85	Average
3	2350.293	36.71	-1.95	34.76	74.00	-39.24	Peak
4	2350.293	26.03	-1.95	24.08	54.00	-29.92	Average
5	2402.163	80.11	-2.03	78.08	------	------	Peak
6	2402.163	79.05	-2.03	77.02	------	------	Average

High channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.6℃/ 59%
Memo : BLE-1M-TX-2480
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2480.136	89.79	-2.14	87.65	------	------	Peak
2	2480.136	88.82	-2.14	86.68	------	------	Average
3	2483.530	40.71	-2.09	38.62	74.00	-35.38	Peak
4	2483.530	31.06	-2.09	28.97	54.00	-25.03	Average
5	2484.191	47.34	-2.09	45.25	74.00	-28.75	Peak
6	2484.191	27.86	-2.09	25.77	54.00	-28.23	Average

Vertical



Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-009
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.6℃/ 59%
Memo : BLE-1M-TX-2480
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2480.156	74.47	-2.14	72.33	------	------	Peak
2	2480.156	73.47	-2.14	71.33	------	------	Average
3	2494.786	38.77	-2.02	36.75	74.00	-37.25	Peak
4	2494.786	25.01	-2.02	22.99	54.00	-31.01	Average
5	2496.533	33.72	-2.02	31.70	74.00	-42.30	Peak
6	2496.533	26.10	-2.02	24.08	54.00	-29.92	Average

Note:
Level = Read Level + Factor
Over Limit = Level – Limit Line
Factor = Antenna Factor + Cable Loss – Amplifier Gain


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Test EUT Mode : RRQ61051-010

802.11ax HE20 Mode (Worst case is 802.11ax20 mode, High Channel)

High channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 18.7℃/ 49%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2460.760	92.01	-2.35	89.66	------	------	Peak
2	2460.760	111.25	-2.31	108.94	------	------	Peak
3 !	2483.904	73.22	-2.09	71.13	74.00	-2.87	Peak
4 !	2483.904	54.06	-2.09	51.97	54.00	-2.03	Average

Vertical




Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 18.7℃/ 49%
Memo : AX20-TX-2462
Memo : RBW/VBW: PK:1M/3M; AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2460.552	100.81	-2.32	98.49	------	------	Peak
2	2460.552	82.69	-2.35	80.34	------	------	Average
3	2483.811	62.14	-2.09	60.05	74.00	-13.95	Peak
4	2483.811	46.71	-2.09	44.62	54.00	-9.38	Average

BLE(1M) Mode (Worst case is BLE(1M) mode, Low Channel)

Low channel


Horizontal



Trace: 1
Site : 966B Chamber
Condition: 3m Horizontal
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 57%
Memo : BLE-TX-1M-2402
Memo : RBW/VBW: PK:1M/3M AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2384.303	35.27	-2.13	33.14	74.00	-40.86	Peak
2	2384.303	26.69	-2.13	24.56	54.00	-29.44	Average
3	2389.837	40.89	-2.02	38.87	74.00	-35.13	Peak
4	2389.837	25.85	-2.02	23.83	54.00	-30.17	Average
5	2402.010	88.43	-2.03	86.40	------	------	Average
6	2402.010	89.29	-2.03	87.26	------	------	Average

Vertical



Trace: 1
Site : 966B Chamber
Condition: 3m Vertical
Job No : RLK250801005
Model : RRQ61051-010
Power : From Test Development Board
Tester : Derek
Temp./ Hum.: 20.7℃/ 57%
Memo : BLE-TX-1M-2402
Memo : RBW/VBW: PK:1M/3M AV:1M/3k

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2348.007	39.18	-2.00	37.18	74.00	-36.82	Peak
2	2348.007	25.62	-2.00	23.62	54.00	-30.38	Average
3	2351.260	34.79	-1.95	32.84	74.00	-41.16	Peak
4	2351.260	26.68	-1.95	24.73	54.00	-29.27	Average
5	2402.013	78.74	-2.03	76.71	------	------	Peak
6	2402.013	77.81	-2.03	75.78	------	------	Average

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


Conducted Spurious Emissions:

Channel	Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)	Result
b Mode				
Low	2412	33.49	≥ 20	PASS
Mid	2437	35.47	≥ 20	PASS
High	2462	35.27	≥ 20	PASS
g Mode				
Low	2412	32.77	≥ 20	PASS
Mid	2437	30.66	≥ 20	PASS
High	2462	33.3	≥ 20	PASS
n20 Mode				
Low	2412	37.55	≥ 20	PASS
Mid	2437	35.31	≥ 20	PASS
High	2462	37.17	≥ 20	PASS
ax20 Mode				
Low	2412	32.95	≥ 20	PASS
Mid	2437	32.14	≥ 20	PASS
High	2462	32.34	≥ 20	PASS
BLE Mode				
Low	2402	51.61	≥ 20	PASS
Mid	2440	51.91	≥ 20	PASS
High	2480	51.37	≥ 20	PASS

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


b Mode

Low Channel



Date: 20.OCT.2025 11:57:46


Middle Channel



Date: 20.OCT.2025 12:11:48

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


High Channel



Date: 20.OCT.2025 12:25:08

g Mode


Low Channel



Date: 20.OCT.2025 16:38:16


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Middle Channel



Date: 20.OCT.2025 16:39:59

High Channel




Date: 20.OCT.2025 16:54:56

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


n20 Mode

Low Channel



Date: 20.OCT.2025 10:44:37


Middle Channel



Date: 20.OCT.2025 10:46:00

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


High Channel



Date: 20.OCT.2025 10:50:42

ax20 Mode


Low Channel



Date: 20.OCT.2025 12:37:37


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Middle Channel



Date: 20.OCT.2025 11:15:00

High Channel




Date: 20.OCT.2025 11:42:29

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


BLE (1M) Mode

Low Channel



Date: 28.OCT.2025 15:22:12


Middle Channel



Date: 28.OCT.2025 15:24:26

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

High Channel



Date: 28.OCT.2025 15:26:26

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

8 RSS-247 §6.3.1 (b), RSS-GEN §6.7) – 6 dB Emission Bandwidth & Occupied Bandwidth

8.1 Applicable Standard

According to RSS-GEN §6.7

The occupied bandwidth or the "99% emission bandwidth" is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

According to RSS-247 §6.3.1 (a)

The minimum 6 dB bandwidth shall be 500 kHz.

8.2 Test Procedure

According to ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024, section 11.8

The steps for the first option are as follows:

a) Set RBW = 100 kHz.

b) Set the VBW ≥ [3 × RBW].

c) Detector = peak.

d) Trace mode = max hold.

e) Sweep = auto couple.

f) Allow the trace to stabilize.

g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

According to ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 Section 6.9.3

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

8.3 Test Results

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit (kHz)	Result
b Mode					
Low	2412	8.03	14.27	> 500	PASS
Middle	2437	6.03	14.19	> 500	PASS
High	2462	7.55	14.07	> 500	PASS
g Mode					
Low	2412	15.16	16.82	> 500	PASS
Middle	2437	15.32	16.90	> 500	PASS
High	2462	16.08	16.70	> 500	PASS
	n20 Mode				
Low	2412	17.36	17.70	> 500	PASS
Middle	2437	17.40	17.94	> 500	PASS
High	2462	17.16	17.74	> 500	PASS
ax20 Mode					
Low	2412	18.28	18.86	> 500	PASS
Middle	2437	18.28	18.94	> 500	PASS
High	2462	17.64	18.86	> 500	PASS
BLE(1M) Mode					
Low	2402	0.756	1.073	> 500	PASS
Middle	2440	0.762	1.076	> 500	PASS
High	2480	0.753	1.079	> 500	PASS


Please refer to the following plots

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

6 dB Emission Bandwidth


b Mode

Low Channel



Date: 20.OCT.2025 12:31:39


Middle Channel



Date: 20.OCT.2025 12:08:06

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


High Channel



Date: 20.OCT.2025 12:18:58

g Mode


Low Channel



Date: 20.OCT.2025 15:36:58


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Middle Channel



Date: 20.OCT.2025 15:37:59

High Channel




Date: 20.OCT.2025 15:35:59

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


n20 Mode

Low Channel



Date: 20.OCT.2025 15:43:17


Middle Channel



Date: 20.OCT.2025 15:40:30

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


High Channel



Date: 20.OCT.2025 15:41:45

ax20 Mode


Low Channel



Date: 20.OCT.2025 15:44:28


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Middle Channel



Date: 20.OCT.2025 15:46:51

High Channel




Date: 20.OCT.2025 15:45:36

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


BLE (1M) Mode

Low Channel



Date: 28.OCT.2025 15:20:18


Middle Channel



Date: 28.OCT.2025 15:22:58

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

High Channel




Date: 28.OCT.2025 15:25:03

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

99%Occupied Bandwidth:


b Mode

Low Channel



Date: 20.OCT.2025 12:01:57


Middle Channel



Date: 20.OCT.2025 11:45:54

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


High Channel



Date: 20.OCT.2025 12:22:29

g Mode


Low Channel



Date: 20.OCT.2025 16:34:13


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Middle Channel



Date: 20.OCT.2025 16:44:45

High Channel




Date: 20.OCT.2025 16:45:50

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


n20 Mode

Low Channel



Date: 20.OCT.2025 17:01:44


Middle Channel



Date: 20.OCT.2025 17:02:58

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


High Channel



Date: 20.OCT.2025 10:56:37

ax20 Mode


Low Channel



Date: 20.OCT.2025 11:07:33


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Middle Channel



Date: 20.OCT.2025 11:31:38

High Channel




Date: 20.OCT.2025 11:33:28

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


BLE (1M) Mode

Low Channel



Date: 28.OCT.2025 15:20:42


Middle Channel



Date: 28.OCT.2025 15:23:23

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

High Channel



Date: 28.OCT.2025 15:25:27

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

9 RSS-247 §6.3.2 – Maximum Output Power

9.1 Applicable Standard

According to RSS-247 §6.3.2

For DTS operating in the band 902-928 MHz, the maximum peak conducted output power shall not exceed 1W, and the e.i.r.p. shall not exceed 4 W.

For DTS operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W, and the e.i.r.p. shall not exceed 4 W, except as provided in section 6.5 a) and b).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power.

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

9.2 Test Procedure

According to ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 ,section 11.9.1.2

According to ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 ,section 11.9.2.3.1

1. Place the EUT on a bench and set it in transmitting mode.

2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to measuring equipment.

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

9.3 Test Results

Conducted Peak Output Power

Test EUT Mode : RRQ61051-009

Channel	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)	Limit (dBm)	Antenna Gain (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Result
b Mode								
Low	2412	16.29	19.59	30	3.3	22.89	36	PASS
Middle	2437	15.38	18.71	30	3.3	22.01	36	PASS
High	2462	14.32	17.64	30	3.3	20.94	36	PASS
g Mode								
Low	2412	14.41	19.45	30	3.3	22.75	36	PASS
Middle	2437	14.93	19.52	30	3.3	22.82	36	PASS
High	2462	14.98	19.62	30	3.3	22.92	36	PASS
n20 Mode								
Low	2412	13.56	19.53	30	3.3	22.83	36	PASS
Middle	2437	14.00	19.54	30	3.3	22.84	36	PASS
High	2462	14.60	19.61	30	3.3	22.91	36	PASS
ax20 Mode								
Low	2412	13.80	19.54	30	3.3	22.84	36	PASS
Middle	2437	14.00	19.64	30	3.3	22.94	36	PASS
High	2462	14.10	19.68	30	3.3	22.98	36	PASS
BLE(1M) Mode								
Low	2402	1.33	1.42	30	3.3	4.72	36	PASS
Middle	2440	1.05	1.14	30	3.3	4.44	36	PASS
High	2480	0.84	0.93	30	3.3	4.23	36	PASS

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Test EUT Mode : RRQ61051-010

Channel	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)	Limit (dBm)	Antenna Gain (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Result
b Mode								
Low	2412	15.71	18.39	30	3.3	21.69	36	PASS
Middle	2437	13.47	17.54	30	3.3	20.84	36	PASS
High	2462	13.60	16.63	30	3.3	19.93	36	PASS
g Mode								
Low	2412	13.62	18.38	30	3.3	21.68	36	PASS
Middle	2437	13.80	18.52	30	3.3	21.82	36	PASS
High	2462	12.99	18.50	30	3.3	21.80	36	PASS
n20 Mode								
Low	2412	11.90	18.41	30	3.3	21.71	36	PASS
Middle	2437	13.76	18.54	30	3.3	21.84	36	PASS
High	2462	12.30	18.72	30	3.3	22.02	36	PASS
ax20 Mode								
Low	2412	12.59	18.42	30	3.3	21.72	36	PASS
Middle	2437	13.75	18.56	30	3.3	21.86	36	PASS
High	2462	13.72	18.60	30	3.3	21.90	36	PASS
BLE(1M) Mode								
Low	2402	1.32	1.41	30	3.3	4.71	36	PASS
Middle	2440	1.01	1.12	30	3.3	4.42	36	PASS
High	2480	0.81	0.90	30	3.3	4.20	36	PASS

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

10 RSS-247 §6.6 – 100 kHz Bandwidth of Frequency Band Edge

10.1 Applicable Standard

According to RSS-247 §6.6.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum device, digitally modulated device, or hybrid system is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power – based on either an RF conducted or a radiated measurement – provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 6.3.2, the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

10.2 Test Procedure

According to ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 Section 11.11

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

10.3 Test Results


WIFI 2.4G

Channel	Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)	Result
b Mode				
Low	2412	39.55	≥ 20	PASS
High	2462	49.49	≥ 20	PASS
g Mode				
Low	2412	27.02	≥ 20	PASS
High	2462	40.84	≥ 20	PASS
n20 Mode				
Low	2412	31.86	≥ 20	PASS
High	2462	40.95	≥ 20	PASS
ax20 Mode				
Low	2412	27.32	≥ 20	PASS
High	2462	37.11	≥ 20	PASS
BLE(1M) Mode				
Low	2402	38.88	≥ 20	PASS
High	2480	47.40	≥ 20	PASS

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


b Mode

Band Edge, Left Side



Date: 20.OCT.2025 12:03:43

Band Edge, Right Side




Date: 20.OCT.2025 12:26:32

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


g Mode

Band Edge, Left Side



Date: 20.OCT.2025 16:35:55

Band Edge, Right Side




Date: 20.OCT.2025 16:51:48

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


n20 Mode

Band Edge, Left Side



Date: 20.OCT.2025 17:01:05

Band Edge, Right Side




Date: 20.OCT.2025 10:58:21

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


ax20 Mode

Band Edge, Left Side



Date: 20.OCT.2025 11:08:33

Band Edge, Right Side




Date: 20.OCT.2025 11:41:15

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


BLE (1M) Mode

Band Edge, Left Side



Date: 28.OCT.2025 15:20:58

Band Edge, Right Side



Date: 28.OCT.2025 15:25:43

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

11 RSS-247 §6.3.1(b) – Power Spectral Density

11.1 Applicable Standard

According to RSS-247 §6.3.1(b).

The transmitter power spectral density conducted from the transmitter to the antenna(s) shall not be greater than 8 dBm/3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 6.3.2 The power spectral density shall be determined using the same method as is used to determine the maximum conducted output power.

11.2 Test Procedure

According to ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 , section 11.10.2

a) Set analyzer center frequency to DTS channel center frequency.

b) Set the span > 1.5 times the DTS bandwidth.

c) Set the RBW to 3 kHz ≤ RBW ≤ 100 kHz.

d) Set the VBW ≥ [3 × RBW].

e) Detector = peak.

f) Sweep time = auto couple.

g) Trace mode = max hold.

h) Allow trace to fully stabilize.

i) Use the peak marker function to determine the maximum amplitude level within the RBW.

j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


11.3 Test Results

Channel	Frequency (MHz)	Power Spectral Density (dBm/3 kHz)	Limit (dBm/3 kHz)	Result
b Mode				
Low	2412	0.18	8	PASS
Middle	2437	-3.21	8	PASS
High	2462	-1.27	8	PASS
g Mode				
Low	2412	-7.75	8	PASS
Middle	2437	-6.84	8	PASS
High	2462	-7.73	8	PASS
n20 Mode				
Low	2412	-9.60	8	PASS
Middle	2437	-7.57	8	PASS
High	2462	-9.71	8	PASS
ax20 Mode				
Low	2422	-10.10	8	PASS
Middle	2437	-8.98	8	PASS
High	2452	-9.68	8	PASS
BLE(1M) Mode				
Low	2402	-14.90	8	PASS
Middle	2440	-15.28	8	PASS
High	2480	-15.67	8	PASS

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


b Mode

Low Channel



Date: 20.OCT.2025 12:00:27


Middle Channel



Date: 20.OCT.2025 12:09:38

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


High Channel



Date: 20.OCT.2025 12:21:12

g Mode


Low Channel



Date: 20.OCT.2025 15:37:19


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Middle Channel



Date: 20.OCT.2025 15:38:48

High Channel




Date: 20.OCT.2025 15:36:27

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


n20 Mode

Low Channel



Date: 20.OCT.2025 15:43:42


Middle Channel



Date: 20.OCT.2025 15:41:01

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


High Channel



Date: 20.OCT.2025 15:42:01

ax20 Mode


Low Channel



Date: 20.OCT.2025 15:44:58


Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Middle Channel



Date: 20.OCT.2025 15:47:22

High Channel




Date: 20.OCT.2025 15:46:15

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)


BLE (1M) Mode

Low Channel



Date: 28.OCT.2025 20:59:15


Middle Channel



Date: 28.OCT.2025 20:57:42

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

High Channel



Date: 28.OCT.2025 20:58:29

******* END OF REPORT *******

Note: It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)