

QC-BEKITPOC2Z

QuickConnect Beginners Kit V2.0

Introduction

This application note provides step-by-step guidance using the QuickConnect Beginners Kit V2.0 for three projects: Blinky, Smart Temperature Data Logger, and BLE-based Asset Tracker. Each project includes detailed instructions for hardware setup, software configuration, and result analysis. The document also suggests possible customizations to help users modify and expand the project outcomes.

All applications are developed using the QuickConnect Studio alongside the Beginners Kit V2.0 hardware enabling rapid and flexible prototype development. To ensure proper setup, follow the Quick Start Procedure at the beginning of this document.

These labs offer hands-on experience that guides users through both hardware assembly and software development for embedded system prototyping. The QuickConnect platform streamlines the design process allowing users to move from concept to prototype in just minutes. Code generation, compilation, customization, and debugging are all seamlessly managed through a single, unified interface.

Note: To ensure the projects are set up correctly, complete the steps in the order listed in this document.

Contents

1. Kit Information	2
1.1 Kit Contents	2
2. Hardware Description.....	3
2.1 BGK-RA6E2.....	3
2.1.1 Block Diagram	4
2.1.2 Board Specifications	4
2.2 DA16600 PMOD	7
2.3 DA14531 PMOD	8
2.4 Humidity and Temperature Sensor PMOD	8
3. QuickConnect Studio	9
4. Prerequisites	9
5. Getting Started	11
5.1 Launch QuickConnect Studio Workspace	11
5.2 Create a New Project.....	12
6. Project 1 – Blinky.....	13
6.1 Create the Project.....	13
6.2 Programming Hardware and Viewing Results	16
7. Project 2 - Smart Temperature Data Logger.....	17
7.1 Steps to Create the Project.....	17
7.2 Programming Hardware and Viewing Results	23
8. Project 3 - BLE-based Asset Tracker	27
8.1 Steps to Create the Project.....	27
8.2 Programming Hardware and Viewing Results	30
9. Debugging on QuickConnect Studio	34
9.1 Remote Debugging.....	34
10. Appendix	37
10.1 Flashing Code to the Hardware using SEGGER J-Flash Lite.....	37
10.2 Enable Data log	38

10.3	Customization	41
10.3.1	Foundation for Customization	41
10.3.2	Customize Blinky application	44
10.3.3	Customize Sensor Data to AWS Cloud application	82
10.3.4	Customize Sensor Data to BLE application	93
11.	References	110
12.	Revision History	110

1. Kit Information

1.1 Kit Contents

Orderable Part Number – QC-BEKITPOC2Z

Hardware Components – BGK-RA6E2 (R7FA6E2BB3CFM) MCU board

- PMOD Board with Ultra-Low Power Wi-Fi + Bluetooth® Low Energy Combo Module, DA16600MOD
- PMOD Board with Low Power Bluetooth, DA14531MOD
- PMOD Board with Relative Humidity and Temperature Sensor (HS4001)

Note: While the sensor used on the board (HS4001) is marked as NRND (Not Recommended for New Designs), users can still run the examples in this document and fully experience QuickConnect Studio without any issues.

2. Hardware Description

2.1 BGK-RA6E2


The BGK-RA6E2 Board provides an entry point for evaluation, prototyping, and development with the RA6E2 MCU. Also, because this board incorporates an emulator circuit, it can be used for designing user applications without the requirement of making further investments in tools. This product includes through-holes for pin headers that allow access to all MCU signal pins, which allows easy prototyping with a breadboard.

Table 1. Board Specifications

Item	Specification
Evaluation MCU	Part No: R7FA6E2BB3CFM; package: 64-pin LQFP
	On-chip memory: 256KB code flash, 40KB SRAM, 4KB data flash memory
Board size	Size: 53mm × 85mm; thickness: 1.6mm
Power-supply voltage	Board supply: 5V. VCC: 3.3V. MCU operation voltage range 2.7V to 3.6V
Power-supply circuit	USB connector: VBUS (5V input); VBUS is converted to 3.3V by LDO
	2-pin external power-supply header*1
Push switch	Reset switch x 1, user switch x 1
LED	Power indicator: green x 1, user: green x 2, On-board debugger ACT: yellow x 1
USB connector	Connector: micro-USB type B
PMOD™ connector	Connector: angle type, 12-pin x 2
Arduino™ connector	Connector: 6-pin x 1, 8-pin x 2, 10-pin x 1
	The interface is compatible with Arduino™ Uno R3
MCU header ¹	Header: 32 pins x 2
Emulator	J-Link on-board programmer / debugger

1. This part is not mounted.

2.1.1 Block Diagram



2.1.2 Board Specifications




Figure 1. BGK-RA6E2 MCU Board Layout

2.1.2.1 Arduino Interface




Figure 2. BGK-RA6E2 MCU Board Arduino Interface

2.1.2.2 PMOD Interface

The QC Beginner Kit RA6E2 MCU Board has two PMOD connectors. PMOD 1 supports the Type 2A interfaces and can also be configured for Type 3A. PMOD 2 supports Type 6A interfaces and can also be configured for Type 2A, Type 3A, and Type 7A.

The default setting for PMOD 1 is SPI/UART interfaces.




Figure 3. PMOD 1 Interface

The default setting for PMOD 2 is I2C interfaces.




Figure 4. PMOD 2 Interface

2.1.2.3 Copper Jumpers

Two types of copper jumpers are provided on the RA6E2 MCU board, designated trace-cut and solder-bridge with E.

A trace-cut jumper is provided with a narrow copper trace connecting its pads. The silkscreen overlay printing around a trace-cut jumper is a solid box. To isolate the pads, cut the trace between pads adjacent to each pad, and remove the connecting copper foil either mechanically or with the assistance of heat. When the etched copper trace is removed, the trace-cut jumper is turned into a solder-bridge jumper for any later changes.

A solder-bridge jumper is provided with two isolated pads can be joined together by either of the three methods:

- Solder can be applied to both pads to develop a bulge on each and the bulges joined by touching a soldering iron across the two pads.
- A small wire can be placed across the two pads and soldered in place.
- A SMD resistor, size 0805, 0603, or 0402, can be placed across the two pads and soldered in place. A 0Ω resistor shorts the pads together.

For any copper jumper, the connection is considered closed if there is an electrical connection between the pads (default for trace-cut jumpers.) The connection is considered open if there is no electrical connection between the pads (default for the solder-bridge jumpers).



Figure 5. Copper Jumpers

2.2 DA16600 PMOD

The [US159-DA16600EVZ](#) is a PMOD board for the DA16600MOD. It is a Wi-Fi BLE module (802.11 b/g/n and Bluetooth V5.1). The DA16600 addresses the requirement of battery-use devices that require minimal power consumption and reliable operation. It can be used with a MCU board that supports Type 3A PMOD. In the following projects, this module is used for Wi-Fi communication.




Figure 6. US159-DA16600EVZ PMOD Board




Figure 7. Evaluation Kit Details

2.3 DA14531 PMOD

The [US159-DA14531EVZ](#) is a PMOD board with DA14531MOD. It is a low power Bluetooth 5.1 SOC module. In this document, this module is used for BLE based projects.



Figure 8. DA14531 Evaluation Board (Top)



Figure 9. DA14531 Evaluation Board (Bottom)

2.4 Humidity and Temperature Sensor PMOD

The humidity and temperature PMOD board with a digital I²C humidity and temperature sensor is used in the following labs.




Figure 10. Humidity and Temperature Sensor Board Layout




Figure 11. Sensor PMOD Application Schematic

3. QuickConnect Studio

The QuickConnect Studio (QCStudio) is an online, cloud-based embedded system design platform that enables users to graphically drag-and-drop eval boards to build custom prototypes. Users can generate, compile, customize, and debug the base system code on a single browser window without installing multiple applications. This reduces the complexity to build and test embedded system prototypes and increases the time to market.

3.1 Key Features

The following list highlights key features supported on QuickConnect platform.

- QuickConnect supports a broad portfolio of Renesas and Partner boards and devices
- Real-time code customization
- QuickConnect debugging by connecting to remote board farms deployed globally
- Multi-region deployment to increase connection speed from anywhere in the world
- Support for multiple concurrent users globally
- Real-time monitoring for cyber security threats

For more details, refer to the [QuickConnect Studio](#) landing page.

4. Prerequisites

Before you begin this lab, ensure you have the following items:

- QuickConnect Beginners Kit V2.0 – The kit includes all the hardware components needed for this lab.
- Windows PC – A computer running Windows operating system. Renesas recommends using a system running Windows 10 or later versions, equipped with at least one available USB port.

- Web Browser – Ensure a web browser is installed on a Windows PC. For optimal performance, it is advised to use Google Chrome.
- MyRenesas Registration – An active MyRenesas account must be obtained to access QuickConnect. If you do not have one, register on the [MyRenesas](#) page.
- Internet Connection: A stable internet connection is required to access online resources and download necessary files.
- Segger J-link flasher – [SEGGER - The Embedded Experts - Downloads - J-Link / J-Trace](#). To flash the boards, Renesas recommends downloading and installing the 64-bit installer, ensuring it is the latest version compatible with the user's device.
- QuickConnect Sandbox application – For applications based on Bluetooth connectivity, download and install the QuickConnect Mobile Sandbox application for [Android](#) or [iOS](#). It can support Android versions up to 14 and iOS 10.0 or later versions.
- Wi-Fi security requirements – The DA16xxx series Wi-Fi modules support the following WiFi security types: 0 (OPEN), 1 (WEP), 2 (WPA), 3 (WPA2), 4 (WPA+WPA2), 5 (WPA3 OWE), 6 (WPA3 SAE), 7 (WPA2 RSN and WPA3 SAE). The "Sensor Data to AWS IoT" application used in this lab uses WPA2 security type by default. Verify that the security setting on the Wi-Fi access point(AP)/router matches this requirement. If not, update the settings accordingly either in the application or on the Wi-Fi AP/router.
- RTT Viewer – Download and install the RTT Viewer application (version 8.24) which is used to view the debug logs from the Renesas365 Dev Kit. Download link: [About the RTT Viewer](#)
- MQTT Explorer – Download and install the MQTT Explorer application, which is used to view the MQTT messages published by the Renesas365 Dev Kit to AWS IoT. Download link: [MQTT Explorer | An all-round MQTT client that provides a structured topic overview](#)

5. Getting Started

5.1 Launch QuickConnect Studio Workspace

1. Launch the QuickConnect Studio platform in a PC browser window.
 - a. To launch a QuickConnect Studio user workspace, visit the [QuickConnect Studio](#).
 - b. Click on the **Launch QuickConnect Studio** button to launch a unique workspace in a browser window.

QuickConnect Platform

Overview | Get Started | Find a QuickConnect Board | Videos | News & Blog Posts

Redefining System Design: Co-Develop Hardware and Software with QuickConnect

QuickConnect simplifies the development of electronic systems by using standardized hardware and software building blocks.

QuickConnect Studio, a cloud-based design platform, facilitates visual construction of hardware and software, accelerating prototype validation and product development. Engineers can drag and drop hardware device blocks, and the platform auto-generates code. Additionally, it supports real-time code customization and remote debugging, enabling iterative testing before deploying physical boards.

QuickConnect Boards are the physical boards with standardized connectors that enable rapid prototyping and testing by eliminating compatibility issues.

QuickConnect Platform Overview

Discover Renesas' QuickConnect Platform consisting of standardized... [Share](#)

[renesas.com/quickconnect](#)

- ALL-IN-ONE SYSTEM DESIGN PLATFORM
- EASY TO USE
- CONNECT ANYWHERE, ANYTIME
- FLEXIBLE AND SCALABLE

Rapid Prototyping

Access a fast, modular system of sensors, connectivity and MCU/MPU evaluation boards for rapid prototyping.

Hardware Compatibility

Enjoy hardware compatibility with standardized PMOD, mikroBUS™ and Arduino interfaces that eliminate compatibility issues and simplify the design process.

Reduce Code Development

Save time and effort with pre-integrated sensor libraries and automatic code generation.

[Launch QuickConnect Studio](#)

2. At the following screen, click on the **MyRenesas** button to log in using MyRenesas login credentials.

Sign in to your account

Username or email

Password


Sign In

Or sign in with


MyRenesas

5.2 Create a New Project

1. Click on **Create QuickConnect Studio Configuration Project**.




2. Enter the project name in the field that appears and press the **Enter** key.




6. Project 1 – Blinky

6.1 Create the Project


1. Follow the steps in Section 5 to launch and create a new project.




2. Drag and drop the MCU board from the QCC tool palette. Hover the cursor over the MCU to view its features. In this example, BGK-RA6E2 is used.




3. Select the MCU and then choose **Application Configuration**.




4. In the Application Configuration window, select **IoT > Other > Blink LEDs**.




5. Click on **Build Project**. The build progress is displayed in the output log.



6. After the project is built, a notification appears stating “QCStudio project build finished successfully”. The **Readme.md** file opens for further instructions.




7. Go to Explorer, expand the project, expand **Debug**, select the **.srec** file, right-click, and select **Download**.



6.2 Programming Hardware and Viewing Results

1. Connect the BGK-RA6E2 to a laptop using a USB cable. Refer to the section, Flashing Code to the Hardware using SEGGER J-Flash Lite, to flash the code.




2. Observe the output - LED 1 and 2 blinking in a pattern.




7. Project 2 - Smart Temperature Data Logger

7.1 Steps to Create the Project


1. Follow the steps in the **Getting Started** section to create a new workspace and a project.




2. Drag and drop the MCU board from the QCC tool palette. In this example, BGK-RA6E2 is used.




3. In the Application Configuration window, select market segment as **IoT**, then **Other**, and finally **Sensor Data to AWS Cloud (MQTT onchip)**.




4. Drag and drop the connectivity module DA16600




- a. Based on the chosen board and application, the QuickConnect tool automatically suggests the PMOD connector compatible with the wi-fi module board.




5. Drag and drop the humidity and temperature sensor board.




6. To generate and build project, click on the Generate/Build QCS Project icon on the top left-hand side corner. QuickConnect Studio automatically generates the required software package including drivers, middleware, and network stacks required for the user-created system solution.




7. To run the application project, refer to the instructions in the **README.md** file located in the project directory. In this example, the Wi-Fi SSID and password must be entered, along with the username and AWS endpoint, should be edited in user.h.



8. Additionally, certificate.h must be updated by adding the device certificate, private key, and Amazon root CA. Refer to the workflow below for setting up an MQTT Thing in AWS IoT Core.




9. The user.h file must be updated with Wi-Fi SSID, Wi-Fi password, IO Username, and MQTT host (AWS data endpoint). For AWS endpoint, Login to the AWS account > select **AWS IOT** > Go to **Settings** > Expand **Domain configuration** > Copy domain **Name**.




Note: Renesas recommends not to edit the User_LED_Topic or define the sensor topic, as the tool automatically takes care of it.

10. Update the downloaded certificates in the **certificate.h** file. Make sure to download the Root CA, Client Certificate (that is, device certificate), and Private Key file. Additionally, ensure that the macros are edited before uploading.




Note: The certificate values or lines provided in above screenshot are just for sample. Refer to the attached screenshot only to ensure the correct format.

11. After making changes in the corresponding .c and .h files, rebuild the application project by selecting **Build QCStudio Project** from the drop-down menu.




7.2 Programming Hardware and Viewing Results

1. Follow the steps in the section, Steps to Create the Project, to create the solution.
2. The application project output files can be found under the **bgk_ra6e2_freertos** > **Debug** folder.
3. Right-click on the .srec file and download it to the local PC.




4. Connect the BGK-RA6E2 to the laptop using a USB cable. Refer to the section, Flashing Code to the Hardware using SEGGER J-Flash Lite, to flash the code.



5. Use Jlink Flash programmer to program the .srec file into the required MCU kit (QuickConnect Beginner kit). Reference section, Flashing Code to the Hardware using SEGGER J-Flash Lite, to flash the code.
6. View the output on the AWS MQTT test client by subscribing and publishing the data.


Steps to be followed:

- Log in to the AWS account and open [AWS IoT Core](#). Follow the instructions according to **README.md** to create a thing.
- In the left console, under **Test**, click on **MQTT test client**. A window appears for subscribing and publishing a topic.




Note: Ensure by subscribing to the topic # and check the connection details.

- In the topic filter, enter "UserName/feeds/humidity" and click **Subscribe** to see the humidity values.





- d. Similarly, enter "UserName/feeds/temperature" and click **Subscribe** to see the temperature values.




Note: The username should be the same as what was entered in the **user.h** file in the QuickConnect Studio.

- e. Observe the output humidity and temperature values.






- f. The feature to publish to a topic can also be used by giving the topic name as "UserName/feeds/led" with the message payload set to 0 to turn off the LED and 1 to turn on the LED.




8. Project 3 - BLE-based Asset Tracker

8.1 Steps to Create the BLE-based Project


1. Follow the Steps to Create the Project section to create a new project.




2. Drag and drop the MCU from the QCC tool palette. In this example, BGK-RA6E2 is used.




- Choose the Application Configuration. In the **Application Configuration** window, first select **IoT**, **Other**, and finally **Sensor Data over BLE**.




- Choose the Bluetooth module **DA14531**.




- a. Based on the chosen board, the QuickConnect tool automatically suggests the PMOD connection compatibility



5. Drag and drop the Humidity and Temperature sensor in the reference application (HS4001 is used).




- To generate and build project, click on the Generate/Build QCS Project icon on the top left-hand side corner. QuickConnect Studio automatically generates the required software package including drivers, middleware, and network stacks required for the user-created system solution.




8.2 Programming Hardware and Viewing Results


- Follow the steps in the Steps to Create the Project section to create the solution.
- The application project output files is found under the **Debug** folder. Right-click on the **.srec** file and download it to a local PC.




3. Use the J-link Flash programmer to program the **.srec** file into the desired MCU kit. Refer to the Flashing Code to the Hardware using SEGGER J-Flash Lite section.




4. View the output on QC Sandbox by downloading the QC Sandbox app.
5. As soon as the application is open, it asks you to select either **Bluetooth Low Energy (BLE)** or **Wi-Fi Provisioning**. For this reference example, select **Bluetooth Low Energy (BLE)**.




6. To view the output:
 - b. Turn on Bluetooth on the device.




7. Scan to connect and click on the **Connect** button.



8. Select the **LED** option on the QC Sandbox app and toggle the **LED** switch to turn it on and off. Observe the output.



9. Select the sensor **HS4001** on the mobile app to see the humidity and temperature sensor values.



9. Debugging on QuickConnect Studio


9.1 Remote Debugging

Projects can be debugged remotely when it is preferred to validate the generated reference application onto the target hardware before obtaining the boards, and remote board farms deployed globally can be used. The remote debugging feature is supported for the QuickConnect beginners Kit for Blinky, sensor data over BLE, and sensor data over AWS applications.


At this stage, it is assumed the user followed the steps to successfully build a project on QuickConnect.

Follow the proceeding steps for remote debugging.


1. Build the application.
2. To remotely connect to the remote boards, click on the Debug icon as follows:



3. Enable the debug console window to capture the debug log message when connecting to the remote board farm. Click the **View** option and select **Debug Console**.




4. It is important to select the project and configuration that requires debugging.




5. The QCStudio platform automatically generates the **launch.json** with the debug configuration settings for the targeted hardware used in the design. To check the **launch.json** file, click on the settings icon.

Note: Ensure that the selected configuration is correct in **launch.json**. If there is any old project remnant data, clear the **launch.json**, rebuild the project, and select the correct configuration.



6. Click on the green play button as to initiate the debug connection to the remote board farm. The QCStudio platform automatically routes the user to the nearest board farms that have the requested board configurations.

Note: If the board is not available or cannot establish a connection, it might be because the board is in use by others and currently unavailable. Try using it at a later time.



7. On successful connection to the remote board, the QCStudio platform programs the board with the application image and halts on the **main.c** file.
8. After a debug session starts, the Debug toolbar appears supporting the following actions.



Action	Icon	Explanation
Continue/Pause		Continue: Resume normal program/script execution (up to the next breakpoint). Pause: Inspect code executing at the current line and debug line-by-line.
Step Over		Execute the next instruction as a single command without inspecting or following its component steps.
Step Into		Enter the next instruction to follow its execution line-by-line.
Step Out		When inside a method or subroutine, return to the earlier execution context by completing the remaining lines of the current method as though it were a single command.
Restart		Terminate the current program execution and start debugging again using the current run configuration.
Stop		Terminate the current program execution


After debugging the reference application, the user must terminate the debug connection by pressing the **Stop** button from the **Debug** toolbar.

10. Appendix


10.1 Flashing Code to the Hardware using SEGGER J-Flash Lite

Download the Segger software to the local PC if it is not already installed. According to the device compatibility, choose the installer under J-Link Software and Documentation Pack, Renesas recommends installing the 64-bit installer.

1. Open SEGGER J-Flash Lite:
 - a. Navigate to the **Program Files** on the PC.
 - b. Open the **SEGGER – Jlink** folder.
 - c. Launch **JFlashLite.exe**.
2. Select Target Device:
 - a. In the J-Flash Lite window, click on the (...) button next to the **Target Device** field.
 - b. A new window appears. Here, the user can select the manufacturer and device.
 - c. For this project, the **RA6E2 MCU** is used, search for the part number **R7FA6E2BB**.
 - d. Select the target device and click **OK**.
 - e. Ensure the target interface is set to **SWD**.
 - f. Click **OK**.




3. Import the **.srec** File:
 - a. In the main J-Flash Lite window, locate the **Data File (bin / Hex / mot / srec / ...)** section.
 - b. Click on the (...) button to import the **.srec** file.
 - c. Select the **.srec** file that was downloaded by following the steps in the Quick Start procedure.



4. Program the Device:
 - a. Click on Program Device.
 - b. A prompt can appear asking if an update to the latest firmware version is required. Select **No**.
 - c. The code now flashes to the MCU.


- d. After the process is complete, the log section of the screen displays **Done**.



10.2 Enable Data log


RTT debug logging is a debugging method that is already available in the project generated from the QCS. Enabling this will provide some predefined debugging points through which mistakes in the project can be identified. This is basically some serial messages printed from the application. Complete the following steps to enable this:

1. Go to the **src/main_thread_entry.c** file and make the following changes in the header file inclusion section.




This essentially enables the debug messages on this file. The same can also be followed for sensor files (src/sensor/hs4001_sensor.c).


2. Re-compile the project by clicking **Build QCStudio Project**.




3. Go to **Debug** folder in the repository and open the ***.map** file. This file has the same name as the **srec** file, but the extension is **.map**.
4. Inside the file, search for the word **_segger** and the following appears:




5. A similar address appears in the map file. Copy that address.
6. Flash the **.srec** file to the board.
7. Search the PC for the **JLink RTT Viewer** application and open it.
8. Select the three dots by the Target Device selection.




9. On the next window, under Device type **A6E2**, four devices are listed. Select **R7FA6E2BB** and click **OK**.



10. R7FA6E2BB is now selected as the device in first window (see step 8).
 11. Under **RTT Control Block**, select **Address** and enter the address copied from step 5.



12. Click **OK** and press No if asked for software update.
 13. A window appears:



10.3 Customization

Customization refers to making modifications to the applications. To perform this exercise, it is assumed that the user has built the basic blink, smart temperature data logger, and BLE-based asset tracker.

10.3.1 Foundation for Customization

To update the **QCS project** with modification within the scope of the application, follow these steps:

1. Create the necessary folders in the project to organize and upload the new files.
2. Upload the required files to their corresponding paths within the project structure.
3. Replace any existing files that need to be updated with the new versions.


10.3.1.1 Create the Required Folders/files



To organize and upload the new files, the user needs to create folders/files as required. For example, the **gpt_timer.c** file should be placed at the path: **bgk_ra6e2_baremetal/src/gpt_timer.c**

However, in the existing Blinky project, this folder structure does currently exist. Therefore, the user must create the **gpt_timer.c** file under the specified path.

A **new folder/file** can be created by following these steps:

1. Click on the project folder (highlighted in the green box).
2. Navigate to the target path folder (highlighted in the blue box).
3. Right-click on the folder where the new folder needs to be created.
4. Select the **New Folder/New File** option from the context menu (highlighted in the red box in the image).
5. Edit the **folder/File Name** as required.
6. After creating the required file at specified path, a user can paste or edit the content in the file as required.







10.3.1.2 Upload the Required Files

To upload the required files to the **QCS project**, complete the following steps:

1. Open the QCS project in the browser.
2. Click on the generated project folder (highlighted with a green box in the image below).
3. Right-click on the folder where the files need to be uploaded (Blue box), select the **Upload Files** option (highlighted in red box in the image).

This opens a file browser window on the local PC, allowing for selecting and uploading the required files, as shown in the second image.





10.3.1.3 Replace Any Existing Files

Similar to how new files are uploaded, existing files can require updates.

While uploading an existing file, a pop-up window appears with the message, "Do you want to replace it?".

In this case, click on **Replace** to overwrite the old version with the updated one.



10.3.2 Customize Blinky application

This section includes some optional customization users can implement on the Blinky Project.

10.3.2.1 Update the Blinky Application to Code the Desired LED to Blink.

If the user wants to control which LED should be enabled in the code, they can do so by defining macros in the **main_application.h** file:

To enable or disable a specific LED, simply comment or uncomment the corresponding macro.

For example, to disable LED1, comment out the **ENABLE_LED1** macro. To enable it again, uncomment the line.

```

#ifndef __MAIN_APPLICATION_H
#define __MAIN_APPLICATION_H

#include "common_utils.h"
+ #define ENABLE_LED1    // enable or disable the code for LED1 using this macro

+ #define ENABLE_LED2    // enable or disable the code for LED2 using this macro
/* Function declaration */
void main_application(void);

#endif /* __MAIN_APPLICATION_H */

```

Code Block 1 main_application.h

After defining the macros, the user should update the **main_application.c** file accordingly. Lines marked with a + symbol indicate the additions made to support this configuration.


```

void main_application(void) {
// Start of autogenerated code
while(true)
{
+ #ifdef ENABLE_LED1
+     utils_set_LED(LED1_LED, BSP_IO_LEVEL_HIGH);
+     utils_delay_ms(250);
+     log_debug("*** LED1 ON ** \r\n");
+ #endif
+ #ifdef ENABLE_LED2
+     utils_set_LED(LED2_LED, BSP_IO_LEVEL_HIGH);
+     utils_delay_ms(250);
+     log_debug("*** LED2 ON ** \r\n");
+ #endif
+ #ifdef ENABLE_LED1
+     utils_set_LED(LED1_LED, BSP_IO_LEVEL_LOW);
+     utils_delay_ms(250);
+     log_debug("*** LED1 OFF ** \r\n");
+ #endif
+ #ifdef ENABLE_LED2
+     utils_set_LED(LED2_LED, BSP_IO_LEVEL_LOW);
+     utils_delay_ms(250);
+     log_debug("*** LED2 OFF ** \r\n");
+ #endif
}
// End of autogenerated code
}

```

Expected Output RTT Logs:

Check the following logs for the expected behavior and also observe LED toggle on Board.

A screenshot of the J-Link RTT Viewer V8.10h application. The window has a menu bar with 'File', 'Terminals', 'Input', 'Logging', and 'Help'. Below the menu bar is a tabbed interface with 'All Terminals' and 'Terminal 0'. The 'Terminal 0' tab is active, displaying a log of debug messages. The messages are formatted as '00> DEBUG:../src/main_application.c ** LED1 ON **' followed by a blank line, then '00> DEBUG:../src/main_application.c ** LED2 ON **' followed by a blank line, and so on, alternating between LED1 and LED2 being turned ON and OFF. The log shows a sequence of 16 messages: LED1 ON, LED2 ON, LED1 OFF, LED2 OFF, LED1 ON, LED2 ON, LED1 OFF, LED2 OFF, LED1 ON, LED2 ON, LED1 OFF, LED2 OFF, LED1 ON, LED2 ON, LED1 OFF, and LED2 OFF. The background of the terminal window is black with white text.

```
00> DEBUG:../src/main_application.c ** LED1 ON **
00>
00> DEBUG:../src/main_application.c ** LED2 ON **
00>
00> DEBUG:../src/main_application.c ** LED1 OFF **
00>
00> DEBUG:../src/main_application.c ** LED2 OFF **
00>
00> DEBUG:../src/main_application.c ** LED1 ON **
00>
00> DEBUG:../src/main_application.c ** LED2 ON **
00>
00> DEBUG:../src/main_application.c ** LED1 OFF **
00>
00> DEBUG:../src/main_application.c ** LED2 OFF **
00>
00> DEBUG:../src/main_application.c ** LED1 ON **
00>
00> DEBUG:../src/main_application.c ** LED2 ON **
00>
00> DEBUG:../src/main_application.c ** LED1 OFF **
00>
```

10.3.2.2 Toggle LED using GPIO button

If the user wants to control the on-board LEDs (that is LED1 and LED2) using the GPIO switch S1 (connected to pin **P304** on the **BGK-RA6E2** board), the first step is to enable the **External Interrupt (ICU) stack** in the code by editing the **configuration.xml** file.

In the updated file:

- Lines starting with + indicate new additions.
- Lines starting with # indicate modifications to the existing default configuration.

```

<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<raConfiguration version="9">
  <generalSettings>
    <option key="#Board#" value="board.bgk_ra6e2"/>
    <option key="CPU" value="RA6E2"/>
    <option key="Core" value="CM33"/>
    <option key="#TargetName#" value="R7FA6E2BB3CFM"/>
    <option key="#TargetARCHITECTURE#" value="cortex-m33"/>
    <option key="#DeviceCommand#" value="R7FA6E2BB"/>
    <option key="#RTOS#" value="_none"/>
    <option key="#pinconfiguration#" value="R7FA6E2BB3CFM.pincfg"/>
    <option key="#FSPVersion#" value="5.5.0"/>
    <option key="#ConfigurationFragments#" value="Renesas##BSP##Board##ra6e2_bgk##"/>
    <option key="#SELECTED_TOOLCHAIN#" value="gcc-arm-embedded"/>
    <option key="#ToolchainVersion#" value="13.2.1.arm-13-7"/>
  </generalSettings>
  <raBspConfiguration>
    <config id="config.bsp.ra6e2.R7FA6E2BB3CFM">
      <property id="config.bsp.part_number" value="config.bsp.part_number.value"/>
      <property id="config.bsp.rom_size_bytes" value="config.bsp.rom_size_bytes.value"/>
      <property id="config.bsp.rom_size_bytes_hidden" value="262144"/>
      <property id="config.bsp.ram_size_bytes" value="config.bsp.ram_size_bytes.value"/>
      <property id="config.bsp.data_flash_size_bytes"
value="config.bsp.data_flash_size_bytes.value"/>
      <property id="config.bsp.package_style" value="config.bsp.package_style.value"/>
      <property id="config.bsp.package_pins" value="config.bsp.package_pins.value"/>
      <property id="config.bsp.irq_count_hidden" value="96"/>
    </config>
    <config id="config.bsp.ra6e2">
      <property id="config.bsp.series" value="config.bsp.series.value"/>
    </config>
    <config id="config.bsp.ra6e2.fsp">
      <property id="config.bsp.fsp.inline_irq_functions"
value="config.bsp.common.inline_irq_functions.enabled"/>
      <property id="config.bsp.fsp.tz.exception_response"
value="config.bsp.fsp.tz.exception_response.nmi"/>
      <property id="config.bsp.fsp.tz.cmsis.bfhfnmins"
value="config.bsp.fsp.tz.cmsis.bfhfnmins.secure"/>
      <property id="config.bsp.fsp.tz.cmsis.sysresetreqs"
value="config.bsp.fsp.tz.cmsis.sysresetreqs.secure_only"/>
      <property id="config.bsp.fsp.tz.cmsis.s_priority_boost"
value="config.bsp.fsp.tz.cmsis.s_priority_boost.disabled"/>
      <property id="config.bsp.fsp.tz.csar" value="config.bsp.fsp.tz.csar.both"/>
      <property id="config.bsp.fsp.tz.rstsar" value="config.bsp.fsp.tz.rstsar.both"/>
      <property id="config.bsp.fsp.tz.bbfsar" value="config.bsp.fsp.tz.bbfsar.both"/>
      <property id="config.bsp.fsp.tz.sramsar.sramprcr"
value="config.bsp.fsp.tz.sramsar.sramprcr.both"/>
      <property id="config.bsp.fsp.tz.sramsar.sramecc"
value="config.bsp.fsp.tz.sramsar.sramecc.both"/>
      <property id="config.bsp.fsp.tz.stbramsar"
value="config.bsp.fsp.tz.stbramsar.both"/>
      <property id="config.bsp.fsp.tz.bussara" value="config.bsp.fsp.tz.bussara.both"/>
      <property id="config.bsp.fsp.tz.bussarb" value="config.bsp.fsp.tz.bussarb.both"/>
      <property id="config.bsp.fsp.tz.uninitialized_ns_application_fallback"
value="config.bsp.fsp.tz.uninitialized_ns_application_fallback.enabled"/>
      <property id="config.bsp.fsp.cache_line_size"
value="config.bsp.fsp.cache_line_size.32"/>
      <property id="config.bsp.fsp.OFS0.iwdt_start_mode"
value="config.bsp.fsp.OFS0.iwdt_start_mode.disabled"/>
      <property id="config.bsp.fsp.OFS0.iwdt_timeout"
value="config.bsp.fsp.OFS0.iwdt_timeout.2048"/>
      <property id="config.bsp.fsp.OFS0.iwdt_divisor"
value="config.bsp.fsp.OFS0.iwdt_divisor.128"/>
      <property id="config.bsp.fsp.OFS0.iwdt_window_end"
value="config.bsp.fsp.OFS0.iwdt_window_end.0"/>
    </config>
  </raBspConfiguration>
</raConfiguration>

```



```

    <property id="config.bsp.fsp.OFS0.iwdt_window_start"
value="config.bsp.fsp.OFS0.iwdt_window_start.100"/>
    <property id="config.bsp.fsp.OFS0.iwdt_reset_interrupt"
value="config.bsp.fsp.OFS0.iwdt_reset_interrupt.Reset"/>
    <property id="config.bsp.fsp.OFS0.iwdt_stop_control"
value="config.bsp.fsp.OFS0.iwdt_stop_control.stops"/>
    <property id="config.bsp.fsp.OFS0.wdt_start_mode"
value="config.bsp.fsp.OFS0.wdt_start_mode.register"/>
    <property id="config.bsp.fsp.OFS0.wdt_timeout"
value="config.bsp.fsp.OFS0.wdt_timeout.16384"/>
    <property id="config.bsp.fsp.OFS0.wdt_divisor"
value="config.bsp.fsp.OFS0.wdt_divisor.128"/>
    <property id="config.bsp.fsp.OFS0.wdt_window_end"
value="config.bsp.fsp.OFS0.wdt_window_end.0"/>
    <property id="config.bsp.fsp.OFS0.wdt_window_start"
value="config.bsp.fsp.OFS0.wdt_window_start.100"/>
    <property id="config.bsp.fsp.OFS0.wdt_reset_interrupt"
value="config.bsp.fsp.OFS0.wdt_reset_interrupt.Reset"/>
    <property id="config.bsp.fsp.OFS0.wdt_stop_control"
value="config.bsp.fsp.OFS0.wdt_stop_control.stops"/>
    <property id="config.bsp.fsp.OFS1.voltage_detection0.start"
value="config.bsp.fsp.OFS1.voltage_detection0.start.disabled"/>
    <property id="config.bsp.fsp.OFS1.voltage_detection0_level"
value="config.bsp.fsp.OFS1.voltage_detection0_level.280"/>
    <property id="config.bsp.fsp.OFS1.hoco_osc"
value="config.bsp.fsp.OFS1.hoco_osc.disabled"/>
    <property id="config.bsp.fsp.BPS.BPS0" value=""/>
    <property id="config.bsp.fsp.PBPS.PBPS0" value=""/>
    <property id="config.bsp.fsp.hoco_fll" value="config.bsp.fsp.hoco_fll.disabled"/>
    <property id="config.bsp.common.main_osc_wait"
value="config.bsp.common.main_osc_wait.wait_8163"/>
    <property id="config.bsp.fsp.mcu.adc.max_freq_hz" value="50000000"/>
    <property id="config.bsp.fsp.mcu.sci_uart.max_baud" value="16666666"/>
    <property id="config.bsp.fsp.mcu.adc.sample_and_hold" value="1"/>
    <property id="config.bsp.fsp.mcu.sci_spi.max_bitrate" value="25000000"/>
    <property id="config.bsp.fsp.mcu.spi.max_bitrate" value="50000000"/>
    <property id="config.bsp.fsp.mcu.iic_master.rate.rate_fastplus" value="1"/>
    <property id="config.bsp.fsp.mcu.canfd.num_channels" value="1"/>
    <property id="config.bsp.fsp.mcu.canfd.rx_fifos" value="2"/>
    <property id="config.bsp.fsp.mcu.canfd.buffer_ram" value="1216"/>
    <property id="config.bsp.fsp.mcu.canfd.afl_rules" value="32"/>
    <property id="config.bsp.fsp.mcu.canfd.afl_rules_each_chnl" value="32"/>
    <property id="config.bsp.fsp.mcu.canfd.max_data_rate_hz" value="5"/>
    <property id="config.bsp.fsp.mcu.sci_uart.cstpen_channels" value="0x0201"/>
    <property id="config.bsp.fsp.mcu.gpt.pin_count_source_channels" value="0xFFFF"/>
    <property id="config.bsp.common.id_mode"
value="config.bsp.common.id_mode.unlocked"/>
    <property id="config.bsp.common.id_code"
value="FFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFF"/>
    <property id="config.bsp.common.id1" value=""/>
    <property id="config.bsp.common.id2" value=""/>
    <property id="config.bsp.common.id3" value=""/>
    <property id="config.bsp.common.id4" value=""/>
    <property id="config.bsp.common.id_fixed" value=""/>
    <property id="config.bsp.fsp.mcu.adc_dmac.samples_per_channel" value="32767"/>
</config>
<config id="config.bsp.ra">
    <property id="config.bsp.common.main" value="1024"/>
    <property id="config.bsp.common.heap" value="1024"/>
    <property id="config.bsp.common.vcc" value="3300"/>
    <property id="config.bsp.common.checking"
value="config.bsp.common.checking.disabled"/>
    <property id="config.bsp.common.assert" value="config.bsp.common.assert.none"/>
    <property id="config.bsp.common.error_log"
value="config.bsp.common.error_log.none"/>

```

```

    <property id="config.bsp.common.soft_reset"
value="config.bsp.common.soft_reset.disabled"/>
    <property id="config.bsp.common.main_osc_populated"
value="config.bsp.common.main_osc_populated.disabled"/>
    <property id="config.bsp.common.pfs_protect"
value="config.bsp.common.pfs_protect.enabled"/>
    <property id="config.bsp.common.c_runtime_init"
value="config.bsp.common.c_runtime_init.enabled"/>
    <property id="config.bsp.common.early_init"
value="config.bsp.common.early_init.disabled"/>
    <property id="config.bsp.common.main_osc_clock_source"
value="config.bsp.common.main_osc_clock_source.crystal"/>
    <property id="config.bsp.common.subclock_populated"
value="config.bsp.common.subclock_populated.enabled"/>
    <property id="config.bsp.common.subclock_drive"
value="config.bsp.common.subclock_drive.standard"/>
    <property id="config.bsp.common.subclock_stabilization_ms" value="1000"/>
  </config>
</raBspConfiguration>
<raClockConfiguration>
  <node id="board.clock.xtal.freq" mul="200000000" option="_edit"/>
  <node id="board.clock.hoco.freq" option="board.clock.hoco.freq.20m"/>
  <node id="board.clock.loco.freq" option="board.clock.loco.freq.32768"/>
  <node id="board.clock.moco.freq" option="board.clock.moco.freq.8m"/>
  <node id="board.clock.subclk.freq" option="board.clock.subclk.freq.32768"/>
  <node id="board.clock.pll.source" option="board.clock.pll.source.hoco"/>
  <node id="board.clock.pll.div" option="board.clock.pll.div.1"/>
  <node id="board.clock.pll.mul" option="board.clock.pll.mul.100"/>
  <node id="board.clock.pll.display" option="board.clock.pll.display.value"/>
  <node id="board.clock.clock.source" option="board.clock.clock.source.pll"/>
  <node id="board.clock.clkout.source" option="board.clock.clkout.source.disabled"/>
  <node id="board.clock.uclk.source" option="board.clock.uclk.source.disabled"/>
  <node id="board.clock.canfdclk.source"
option="board.clock.canfdclk.source.disabled"/>
  <node id="board.clock.cccclk.source" option="board.clock.cccclk.source.disabled"/>
  <node id="board.clock.i3cclk.source" option="board.clock.i3cclk.source.disabled"/>
  <node id="board.clock.iclk.div" option="board.clock.iclk.div.1"/>
  <node id="board.clock.pclka.div" option="board.clock.pclka.div.2"/>
  <node id="board.clock.pclkb.div" option="board.clock.pclkb.div.4"/>
  <node id="board.clock.pclkc.div" option="board.clock.pclkc.div.4"/>
  <node id="board.clock.pclkd.div" option="board.clock.pclkd.div.2"/>
  <node id="board.clock.fclk.div" option="board.clock.fclk.div.4"/>
  <node id="board.clock.clkout.div" option="board.clock.clkout.div.1"/>
  <node id="board.clock.uclk.div" option="board.clock.uclk.div.5"/>
  <node id="board.clock.canfdclk.div" option="board.clock.canfdclk.div.6"/>
  <node id="board.clock.cccclk.div" option="board.clock.cccclk.div.1"/>
  <node id="board.clock.i3cclk.div" option="board.clock.i3cclk.div.1"/>
  <node id="board.clock.iclk.display" option="board.clock.iclk.display.value"/>
  <node id="board.clock.pclka.display" option="board.clock.pclka.display.value"/>
  <node id="board.clock.pclkb.display" option="board.clock.pclkb.display.value"/>
  <node id="board.clock.pclkc.display" option="board.clock.pclkc.display.value"/>
  <node id="board.clock.pclkd.display" option="board.clock.pclkd.display.value"/>
  <node id="board.clock.fclk.display" option="board.clock.fclk.display.value"/>
  <node id="board.clock.clkout.display" option="board.clock.clkout.display.value"/>
  <node id="board.clock.uclk.display" option="board.clock.uclk.display.value"/>
  <node id="board.clock.canfdclk.display"
option="board.clock.canfdclk.display.value"/>
  <node id="board.clock.cccclk.display" option="board.clock.cccclk.display.value"/>
  <node id="board.clock.i3cclk.display" option="board.clock.i3cclk.display.value"/>
</raClockConfiguration>
<raComponentSelection>
  <component apiversion="" class="Common" condition="" group="all"
subgroup="fsp_common" variant="" vendor="Renesas" version="5.5.0">
    <description>Board Support Package Common Files</description>
    <originalPack>Renesas.RA.5.5.0.pack</originalPack>
  </component>

```

```

+   <component apiversion="" class="HAL Drivers" condition="" group="all"
subgroup="r_icu" variant="" vendor="Renesas" version="5.5.0">
+   <description>External Interrupt</description>
+   <originalPack>Renesas.RA.5.5.0.pack</originalPack>
+   </component>
+   <component apiversion="" class="HAL Drivers" condition="" group="all"
subgroup="r_ioport" variant="" vendor="Renesas" version="5.5.0">
+   <description>I/O Port</description>
+   <originalPack>Renesas.RA.5.5.0.pack</originalPack>
+   </component>
+   <component apiversion="" class="CMSIS" condition="" group="CMSIS5" subgroup="CoreM"
variant="" vendor="Arm" version="6.1.0+fsp.5.5.0">
+   <description>Arm CMSIS Version 6 - Core (M)</description>
+   <originalPack>Arm.CMSIS6.6.1.0+fsp.5.5.0.pack</originalPack>
+   </component>
+   <component apiversion="" class="BSP" condition="" group="Board" subgroup="ra6e2_bgk"
variant="" vendor="Renesas" version="5.5.0">
+   <description>RA6E2-BGK Board Support Files</description>
+   <originalPack>Renesas.RA_board_ra6e2_bgk.5.5.0.pack</originalPack>
+   </component>
+   <component apiversion="" class="BSP" condition="" group="ra6e2" subgroup="device"
variant="R7FA6E2BB3CFM" vendor="Renesas" version="5.5.0">
+   <description>Board support package for R7FA6E2BB3CFM</description>
+   <originalPack>Renesas.RA_mcu_ra6e2.5.5.0.pack</originalPack>
+   </component>
+   <component apiversion="" class="BSP" condition="" group="ra6e2" subgroup="device"
variant="" vendor="Renesas" version="5.5.0">
+   <description>Board support package for RA6E2</description>
+   <originalPack>Renesas.RA_mcu_ra6e2.5.5.0.pack</originalPack>
+   </component>
+   <component apiversion="" class="BSP" condition="" group="ra6e2" subgroup="fsp"
variant="" vendor="Renesas" version="5.5.0">
+   <description>Board support package for RA6E2 - FSP Data</description>
+   <originalPack>Renesas.RA_mcu_ra6e2.5.5.0.pack</originalPack>
+   </component>
+   <component apiversion="" class="BSP" condition="" group="ra6e2" subgroup="events"
variant="" vendor="Renesas" version="5.5.0">
+   <description>Board support package for RA6E2 - Events</description>
+   <originalPack>Renesas.RA_mcu_ra6e2.5.5.0.pack</originalPack>
+   </component>
</raComponentSelection>
<raElcConfiguration/>
<raIcuConfiguration/>
<raModuleConfiguration>
+   <module id="module.driver.ioport_on_ioport.0">
+   <property id="module.driver.ioport.name" value="g_ioport"/>
+   <property id="module.driver.ioport.elc_trigger_ioport1" value="_disabled"/>
+   <property id="module.driver.ioport.elc_trigger_ioport2" value="_disabled"/>
+   <property id="module.driver.ioport.elc_trigger_ioport3" value="_disabled"/>
+   <property id="module.driver.ioport.elc_trigger_ioport4" value="_disabled"/>
+   <property id="module.driver.ioport.pincfg" value="g_bsp_pin_cfg"/>
+   </module>
+   <module id="module.driver.external_irq_on_icu.431231040">
+   <property id="module.driver.external_irq.name" value="g_external_irq"/>
+   <property id="module.driver.external_irq.channel" value="9"/>
+   <property id="module.driver.external_irq.trigger"
value="module.driver.external_irq.trigger.trig_falling"/>
+   <property id="module.driver.external_irq.filter_enable"
value="module.driver.external_irq.filter_enable.false"/>
+   <property id="module.driver.external_irq.clock_source_div"
value="module.driver.external_irq.clock_source_div.clock_source_div_by_64"/>
+   <property id="module.driver.external_irq.p_callback"
value="user_button_callback"/>
+   <property id="module.driver.external_irq.ipl"
value="board.icu.common_irq.priority12"/>
+   </module>

```

```

    <context id="_hal.0">
      <stack module="module.driver.ioport_on_ioport.0"/>
+     <stack module="module.driver.external_irq_on_icu.431231040"/>
    </context>
    <config id="config.driver.ioport">
      <property id="config.driver.ioport.checking"
value="config.driver.ioport.checking.system"/>
+     </config>
+     <config id="config.driver.icu">
+       <property id="config.driver.icu.param_checking_enable"
value="config.driver.icu.param_checking_enable.bsp"/>
      </config>
    </raModuleConfiguration>
    <raPinConfiguration>
      <symbolicName propertyId="p000.symbolic_name" value="ARDUINO_A0"/>
      <symbolicName propertyId="p001.symbolic_name" value="ARDUINO_A1"/>
      <symbolicName propertyId="p002.symbolic_name" value="ARDUINO_A2"/>
      <symbolicName propertyId="p003.symbolic_name" value="ARDUINO_A4"/>
      <symbolicName propertyId="p004.symbolic_name" value="ARDUINO_A3"/>
      <symbolicName propertyId="p005.symbolic_name" value="PMOD1_RESET"/>
      <symbolicName propertyId="p006.symbolic_name" value="ARDUINO_D8"/>
      <symbolicName propertyId="p008.symbolic_name" value="ARDUINO_D7"/>
      <symbolicName propertyId="p013.symbolic_name" value="ARDUINO_A5"/>
      <symbolicName propertyId="p014.symbolic_name" value="PMOD2_GPIO1"/>
      <symbolicName propertyId="p015.symbolic_name" value="PMOD2_GPIO2"/>
      <symbolicName propertyId="p100.symbolic_name" value="PMOD2_SCL0_ARDUINO_SCL"/>
      <symbolicName propertyId="p101.symbolic_name" value="PMOD2_SDA0_ARDUINO_SDA"/>
      <symbolicName propertyId="p104.symbolic_name" value="LED1"/>
      <symbolicName propertyId="p105.symbolic_name" value="ARDUINO_D2"/>
      <symbolicName propertyId="p106.symbolic_name" value="PMOD1_GPIO1"/>
      <symbolicName propertyId="p107.symbolic_name" value="PMOD1_GPIO2"/>
      <symbolicName propertyId="p108.symbolic_name" value="DEBUG_SWDI0"/>
      <symbolicName propertyId="p109.symbolic_name" value="PMOD1_TX_ARDUINO_D11"/>
      <symbolicName propertyId="p110.symbolic_name" value="PMOD1_RX_ARDUINO_D12"/>
      <symbolicName propertyId="p111.symbolic_name" value="PMOD1_RSPCK_ARDUINO_D13"/>
      <symbolicName propertyId="p112.symbolic_name" value="LED2"/>
      <symbolicName propertyId="p113.symbolic_name" value="ARDUINO_D6"/>
      <symbolicName propertyId="p205.symbolic_name" value="PMOD2_IRQ"/>
      <symbolicName propertyId="p206.symbolic_name" value="PMOD2_SSIDATA"/>
      <symbolicName propertyId="p207.symbolic_name" value="PMOD2_SSICLK"/>
      <symbolicName propertyId="p208.symbolic_name" value="ARDUINO_RESET"/>
      <symbolicName propertyId="p300.symbolic_name" value="DEBUG_SWDCCLK"/>
      <symbolicName propertyId="p301.symbolic_name" value="ARDUINO_D10"/>
      <symbolicName propertyId="p402.symbolic_name" value="PMOD1_IRQ"/>
      <symbolicName propertyId="p403.symbolic_name" value="ARDUINO_D9"/>
      <symbolicName propertyId="p407.symbolic_name" value="PMOD2_SSIBCK"/>
      <symbolicName propertyId="p408.symbolic_name" value="ARDUINO_D3"/>
      <symbolicName propertyId="p409.symbolic_name" value="ARDUINO_D5"/>
      <symbolicName propertyId="p410.symbolic_name" value="PMOD2_MISO_ARDUINO_D0"/>
      <symbolicName propertyId="p411.symbolic_name"
value="PMOD2_SENSOR_RESET_ARDUINO_D1"/>
      <symbolicName propertyId="p500.symbolic_name" value="ARDUINO_D4"/>
      <pincfg active="true" name="BGK_RA6E2.pincfg" selected="true"
symbol="g_bsp_pin_cfg">
        <configSetting altId="adc0.an000.p000" configurationId="adc0.an000"/>
        <configSetting altId="adc0.an001.p001" configurationId="adc0.an001"/>
        <configSetting altId="adc0.an002.p002" configurationId="adc0.an002"/>
        <configSetting altId="adc0.an004.p004" configurationId="adc0.an004"/>
        <configSetting altId="adc0.an007.p003" configurationId="adc0.an007"/>
        <configSetting altId="adc0.an011.p013" configurationId="adc0.an011"/>
        <configSetting altId="adc0.mode.custom.free" configurationId="adc0.mode"/>
+       <configSetting altId="irq.irq9.p304" configurationId="irq.irq9"/>
+       <configSetting altId="irq.mode.custom.free" configurationId="irq.mode"/>

```



```

    <configSetting altId="jtag_fslash_swd.mode.swd.free"
configurationId="jtag_fslash_swd.mode"/>
    <configSetting altId="jtag_fslash_swd.swclk.p300"
configurationId="jtag_fslash_swd.swclk"/>
    <configSetting altId="jtag_fslash_swd.swdio.p108"
configurationId="jtag_fslash_swd.swdio"/>
    <configSetting altId="p000.adc0.an000" configurationId="p000"/>
    <configSetting altId="p000.gpio_mode.gpio_mode_an"
configurationId="p000.gpio_mode"/>
    <configSetting altId="p001.adc0.an001" configurationId="p001"/>
    <configSetting altId="p001.gpio_mode.gpio_mode_an"
configurationId="p001.gpio_mode"/>
    <configSetting altId="p002.adc0.an002" configurationId="p002"/>
    <configSetting altId="p002.gpio_mode.gpio_mode_an"
configurationId="p002.gpio_mode"/>
    <configSetting altId="p003.adc0.an007" configurationId="p003"/>
    <configSetting altId="p003.gpio_mode.gpio_mode_an"
configurationId="p003.gpio_mode"/>
    <configSetting altId="p004.adc0.an004" configurationId="p004"/>
    <configSetting altId="p004.gpio_mode.gpio_mode_an"
configurationId="p004.gpio_mode"/>
    <configSetting altId="p005.output.high" configurationId="p005"/>
    <configSetting altId="p005.gpio_mode.gpio_mode_out.high"
configurationId="p005.gpio_mode"/>
    <configSetting altId="p006.input" configurationId="p006"/>
    <configSetting altId="p006.gpio_mode.gpio_mode_in"
configurationId="p006.gpio_mode"/>
    <configSetting altId="p008.input" configurationId="p008"/>
    <configSetting altId="p008.gpio_mode.gpio_mode_in"
configurationId="p008.gpio_mode"/>
    <configSetting altId="p013.adc0.an011" configurationId="p013"/>
    <configSetting altId="p013.gpio_mode.gpio_mode_an"
configurationId="p013.gpio_mode"/>
    <configSetting altId="p014.input" configurationId="p014"/>
    <configSetting altId="p014.gpio_mode.gpio_mode_in"
configurationId="p014.gpio_mode"/>
    <configSetting altId="p015.input" configurationId="p015"/>
    <configSetting altId="p015.gpio_mode.gpio_mode_in"
configurationId="p015.gpio_mode"/>
    <configSetting altId="p100.sci0.rxd0" configurationId="p100"/>
    <configSetting altId="p100.gpio_mode.gpio_mode_peripheral"
configurationId="p100.gpio_mode"/>
    <configSetting altId="p100.gpio_otype.gpio_otype_n_ch_od"
configurationId="p100.gpio_otype"/>
    <configSetting altId="p101.sci0.txd0" configurationId="p101"/>
    <configSetting altId="p101.gpio_mode.gpio_mode_peripheral"
configurationId="p101.gpio_mode"/>
    <configSetting altId="p101.gpio_otype.gpio_otype_n_ch_od"
configurationId="p101.gpio_otype"/>
    <configSetting altId="p104.output.low" configurationId="p104"/>
    <configSetting altId="p104.gpio_mode.gpio_mode_out.low"
configurationId="p104.gpio_mode"/>
    <configSetting altId="p105.input" configurationId="p105"/>
    <configSetting altId="p105.gpio_mode.gpio_mode_in"
configurationId="p105.gpio_mode"/>
    <configSetting altId="p106.input" configurationId="p106"/>
    <configSetting altId="p106.gpio_mode.gpio_mode_in"
configurationId="p106.gpio_mode"/>
    <configSetting altId="p107.input" configurationId="p107"/>
    <configSetting altId="p107.gpio_mode.gpio_mode_in"
configurationId="p107.gpio_mode"/>
    <configSetting altId="p108.jtag_fslash_swd.swdio" configurationId="p108"/>
    <configSetting altId="p108.gpio_mode.gpio_mode_peripheral"
configurationId="p108.gpio_mode"/>
    <configSetting altId="p109.sci9.txd9" configurationId="p109"/>

```

```

    <configSetting altId="p109.gpio_mode.gpio_mode_peripheral"
configurationId="p109.gpio_mode"/>
    <configSetting altId="p110.sci9.rxd9" configurationId="p110"/>
    <configSetting altId="p110.gpio_mode.gpio_mode_peripheral"
configurationId="p110.gpio_mode"/>
    <configSetting altId="p111.input" configurationId="p111"/>
    <configSetting altId="p111.gpio_mode.gpio_mode_in"
configurationId="p111.gpio_mode"/>
    <configSetting altId="p112.output.low" configurationId="p112"/>
    <configSetting altId="p112.gpio_mode.gpio_mode_out.low"
configurationId="p112.gpio_mode"/>
    <configSetting altId="p113.input" configurationId="p113"/>
    <configSetting altId="p113.gpio_mode.gpio_mode_in"
configurationId="p113.gpio_mode"/>
    <configSetting altId="p205.input" configurationId="p205"/>
    <configSetting altId="p205.gpio_mode.gpio_mode_in"
configurationId="p205.gpio_mode"/>
    <configSetting altId="p206.ssie0.ssidata0" configurationId="p206"/>
    <configSetting altId="p206.gpio_mode.gpio_mode_peripheral"
configurationId="p206.gpio_mode"/>
    <configSetting altId="p207.ssie0.ssilrck0" configurationId="p207"/>
    <configSetting altId="p207.gpio_mode.gpio_mode_peripheral"
configurationId="p207.gpio_mode"/>
    <configSetting altId="p208.input" configurationId="p208"/>
    <configSetting altId="p208.gpio_mode.gpio_mode_in"
configurationId="p208.gpio_mode"/>
    <configSetting altId="p300.jtag_fslash_swd.swclk" configurationId="p300"/>
    <configSetting altId="p300.gpio_mode.gpio_mode_peripheral"
configurationId="p300.gpio_mode"/>
    <configSetting altId="p301.input" configurationId="p301"/>
    <configSetting altId="p301.gpio_mode.gpio_mode_in"
configurationId="p301.gpio_mode"/>
+    <configSetting altId="p304.irq.irq9" configurationId="p304"/>
+    <configSetting altId="p304.gpio_irq.gpio_irq_enabled"
configurationId="p304.gpio_irq"/>
+    <configSetting altId="p304.gpio_mode.gpio_mode_irq"
configurationId="p304.gpio_mode"/>
    <configSetting altId="p402.input" configurationId="p402"/>
    <configSetting altId="p402.gpio_mode.gpio_mode_in"
configurationId="p402.gpio_mode"/>
    <configSetting altId="p403.input" configurationId="p403"/>
    <configSetting altId="p403.gpio_mode.gpio_mode_in"
configurationId="p403.gpio_mode"/>
    <configSetting altId="p407.ssie0.ssibck0" configurationId="p407"/>
    <configSetting altId="p407.gpio_mode.gpio_mode_peripheral"
configurationId="p407.gpio_mode"/>
    <configSetting altId="p408.input" configurationId="p408"/>
    <configSetting altId="p408.gpio_mode.gpio_mode_in"
configurationId="p408.gpio_mode"/>
    <configSetting altId="p409.input" configurationId="p409"/>
    <configSetting altId="p409.gpio_mode.gpio_mode_in"
configurationId="p409.gpio_mode"/>
    <configSetting altId="p410.input" configurationId="p410"/>
    <configSetting altId="p410.gpio_mode.gpio_mode_in"
configurationId="p410.gpio_mode"/>
    <configSetting altId="p411.output.high" configurationId="p411"/>
    <configSetting altId="p411.gpio_mode.gpio_mode_out.high"
configurationId="p411.gpio_mode"/>
    <configSetting altId="p500.input" configurationId="p500"/>
    <configSetting altId="p500.gpio_mode.gpio_mode_in"
configurationId="p500.gpio_mode"/>
    <configSetting altId="sci0.mode.simplei2c.free" configurationId="sci0.mode"/>
    <configSetting altId="sci0.rxd0.p100" configurationId="sci0.rxd0"/>
    <configSetting altId="sci0.txd0.p101" configurationId="sci0.txd0"/>
    <configSetting altId="sci9.mode.asynchronousuart.free"
configurationId="sci9.mode"/>

```



```

        <configSetting altId="sci9.rxd9.p110" configurationId="sci9.rxd9"/>
        <configSetting altId="sci9.txd9.p109" configurationId="sci9.txd9"/>
        <configSetting altId="ssie0.mode.half_dash_duplex.c"
configurationId="ssie0.mode"/>
        <configSetting altId="ssie0.pairing.c" configurationId="ssie0.pairing"/>
        <configSetting altId="ssie0.ssibck0.p407" configurationId="ssie0.ssibck0"/>
        <configSetting altId="ssie0.ssidata0.p206" configurationId="ssie0.ssidata0"/>
        <configSetting altId="ssie0.ssilrck0.p207" configurationId="ssie0.ssilrck0"/>
    </pincfg>
    <pincfg active="false" name="R7FA6E2BB3CFM.pincfg" selected="false" symbol="">
        <configSetting altId="jtag_fslash_swd.mode.swd.free"
configurationId="jtag_fslash_swd.mode"/>
        <configSetting altId="jtag_fslash_swd.swclk.p300"
configurationId="jtag_fslash_swd.swclk"/>
        <configSetting altId="jtag_fslash_swd.swdio.p108"
configurationId="jtag_fslash_swd.swdio"/>
        <configSetting altId="p108.jtag_fslash_swd.swdio" configurationId="p108"/>
        <configSetting altId="p108.gpio_mode.gpio_mode_peripheral"
configurationId="p108.gpio_mode"/>
        <configSetting altId="p300.jtag_fslash_swd.swclk" configurationId="p300"/>
        <configSetting altId="p300.gpio_mode.gpio_mode_peripheral"
configurationId="p300.gpio_mode"/>
    </pincfg>
</raPinConfiguration>
</raConfiguration>

```

Code Block 2 configuration.xml

Files to be added:

To initialize the external interrupt stack (ICU), middleware API support is required. The following are the files responsible for initializing the external interrupt stack. These functions are called in **main_application.c** to initialize the stack.

```

bgk_ra6e2_baremetal/src /icu_ep.c
bgk_ra6e2_baremetal/src /icu_ep.h

```

The following is the content of the file that should be added to the project.

```

/*****
*****
* File Name      : icu_ep.c
* Description    : Contains function definition.

*****
*****/
/*****
*****/
* Copyright (c) 2020 - 2024 Renesas Electronics Corporation and/or its affiliates
*
* SPDX-License-Identifier: BSD-3-Clause
*****
*****/

#include "common_utils.h"
#include "icu_ep.h"
// Uncomment the desired debug level
#include "log_disabled.h"
// #include "log_error.h"
// #include "log_warning.h"
// #include "log_info.h"
// #include "log_debug.h"
/*****
*****//**

* @addtogroup icu_ep
* @{

*****
*****/

/*****
*****//**

* @addtogroup icu_ep
* @{

*****
*****/

/*****
*****//**
* @brief      This functions initializes ICU module.
* @param[IN]   None
* @retval      FSP_SUCCESS          Upon successful open of ICU module
* @retval      Any Other Error code apart from FSP_SUCCESS Unsuccessful open

*****
*****/
fsp_err_t icu_init(void)
{
    fsp_err_t err = FSP_SUCCESS;

    /* Open ICU module */
    err = R_ICU_ExternalIrqOpen(&g_external_irq_ctrl, &g_external_irq_cfg);
    /* Handle error */
    if (FSP_SUCCESS != err)
    {
        /* ICU Open failure message */
        log_error ("R_ICU_ExternalIrqOpen API FAILED");
    }
    return err;
}

```

```

/*****
*****//**
* @brief      This function enables external interrupt for specified channel.
* @param[IN]  None
* @retval     FSP_SUCCESS          Upon successful enable of ICU module
* @retval     Any Other Error code apart from FSP_SUCCESS  Unsuccessful open
*****
*****/
fsp_err_t icu_enable(void)
{
    fsp_err_t err = FSP_SUCCESS;

    /* Enable ICU module */
    err = R_ICU_ExternalIrqEnable(&g_external_irq_ctrl);
    /* Handle error */
    if (FSP_SUCCESS != err)
    {
        /* ICU Enable failure message */
        log_error ("\r\n**R_ICU_ExternalIrqEnable API FAILED**\r\n");
    }
    return err;
}

/*****
*****//**
* @brief      This function closes opened ICU module before the project ends up in an
Error Trap.
* @param[IN]  None
* @retval     None
*****
*****/
void icu_deinit(void)
{
    fsp_err_t err = FSP_SUCCESS;

    /* Close ICU module */
    err = R_ICU_ExternalIrqClose(&g_external_irq_ctrl);
    /* Handle error */
    if (FSP_SUCCESS != err)
    {
        /* ICU Close failure message */
        log_error ("\r\n**R_ICU_ExternalIrqClose API FAILED**\r\n");
    }
}

```

Code Block 3 bgk_ra6e2_baremetal/src /icu_ep.c

```

/*****
*****
* File Name      : icu_ep.h
* Description    : Contains Macros and function declarations.

*****
*****
/
/*****
*****
* Copyright (c) 2020 - 2024 Renesas Electronics Corporation and/or its affiliates
*
* SPDX-License-Identifier: BSD-3-Clause
*****
*****
*/
#ifndef ICU_EP_H_
#define ICU_EP_H_

#define USER_SW1_IRQ_NUMBER    (9)

/* Function declaration */
fsp_err_t icu_init(void);
fsp_err_t icu_enable(void);
void icu_deinit(void);

#endif /* ICU_EP_H_ */

```

Code Block 4 bgk_ra6e2_baremetal/src /icu_ep.h

The user can enable or disable control for each LED based on the macros defined in main_application.h. The process for enabling or disabling these macros has been explained in the previous section.

Files to be updated:

```

/*
 * Copyright (c) 2020 - 2024 Renesas Electronics Corporation and/or its affiliates
 *
 * SPDX-License-Identifier: BSD-3-Clause
 */
#include <stdio.h>
#include "common_utils.h"
#include "main_application.h"
+ #include "icu_ep.h"
// Uncomment the desired debug level
#include "log_disabled.h"
// #include "log_error.h"
// #include "log_warning.h"
// #include "log_info.h"
// #include "log_debug.h"
+ volatile bool g_sw_press = false;

void main_application(void) {

// Start of autogenerated code
+ fsp_err_t err = FSP_SUCCESS;
+ uint8_t led_state = 1;

+ /* Initialize External IRQ driver*/
+ log_debug("*** ICU ICU Stack ** \r\n");
+ err = icu_init();
+ /* Handle error */
+ if(FSP_SUCCESS != err)
+ {
+     log_error("*** ICU INIT FAILED ** \r\n");
+ }

+ /* Enable External IRQ driver*/
+ err = icu_enable();
+ /* Handle error */
+ if(FSP_SUCCESS != err)
+ {
+     log_error("*** ICU ENABLE FAILED ** \r\n");
+     /* Close External IRQ module.*/
+     icu_deinit();
+ }

    while(true)
    {
+         if(g_sw_press == true)
+         {
+ #ifdef ENABLE_LED1
+             if(led_state)
+             {
+                 utils_set_LED(LED1_LED, BSP_IO_LEVEL_HIGH);
+                 log_debug("*** LED1 ON ** \r\n");
+             }
+             else
+             {
+                 utils_set_LED(LED1_LED, BSP_IO_LEVEL_LOW);
+                 log_debug("*** LED1 OFF ** \r\n");
+             }
+         }
+ #endif

+ #ifdef ENABLE_LED2
+             if(led_state)
+             {
+                 utils_set_LED(LED2_LED, BSP_IO_LEVEL_HIGH);

```

```

+         log_debug("*** LED2 ON ** \r\n");
+     }
+     else
+     {
+         utils_set_LED(LED2_LED, BSP_IO_LEVEL_LOW);
+         log_debug("*** LED2 OFF ** \r\n");
+     }
+ #endif
+     led_state= !led_state;
+     g_sw_press = false;
+ }
+ }
+ // End of autogenerated code
+
+ }
+
+ // Start of autogenerated code
+ void user_button_callback( external_irq_callback_args_t * p_args)
+ {
+     if (p_args->channel == USER_SW1_IRQ_NUMBER)
+     {
+         g_sw_press = true;
+         log_debug("*** S1 Switch Pressed ** \r\n");
+     }
+ }
+ // End of autogenerated code


```

Code Block 5 main_application.c

After all the changes are complete, compile and test the code.

Expected Output RTT Logs:

Check the following logs for the expected behavior and also observe LED toggle on board.



```

J-Link RTT Viewer V8.10h
File Terminals Input Logging Help
All Terminals Terminal 0
00> DEBUG:../src/main_application.c ** ICU ICU Stack **
00>
00> DEBUG:../src/main_application.c ** S1 Switch Pressed **
00>
00> DEBUG:../src/main_application.c ** LED1 ON **
00>
00> DEBUG:../src/main_application.c ** LED2 ON **
00>
00> DEBUG:../src/main_application.c ** S1 Switch Pressed **
00>
00> DEBUG:../src/main_application.c ** LED1 OFF **
00>
00> DEBUG:../src/main_application.c ** LED2 OFF **
00>
00> DEBUG:../src/main_application.c ** S1 Switch Pressed **
00>
00> DEBUG:../src/main_application.c ** LED1 ON **
00>
00> DEBUG:../src/main_application.c ** LED2 ON **
00>
00> DEBUG:../src/main_application.c ** S1 Switch Pressed **
00>
00> DEBUG:../src/main_application.c ** LED1 OFF **
00>
00> DEBUG:../src/main_application.c ** LED2 OFF **
00>

```


10.3.2.3 Control the LED using PWM timer.

If controlling the LED is required, enable the Timer PWM feature on the corresponding LED pins. The first step is to enable the Timer PWM Stack in the code by modifying the **configuration.xml** file.

In the updated file:

- Lines starting with + indicate new additions.
- Lines starting with # indicate modifications to the existing default configuration.
- Lines starting with - indicate deletion.

```

<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<raConfiguration version="9">
  <generalSettings>
    <option key="#Board#" value="board.bgk_ra6e2"/>
    <option key="CPU" value="RA6E2"/>
    <option key="Core" value="CM33"/>
    <option key="#TargetName#" value="R7FA6E2BB3CFM"/>
    <option key="#TargetARCHITECTURE#" value="cortex-m33"/>
    <option key="#DeviceCommand#" value="R7FA6E2BB"/>
    <option key="#RTOS#" value="_none"/>
    <option key="#pinconfiguration#" value="R7FA6E2BB3CFM.pincfg"/>
    <option key="#FSPVersion#" value="5.5.0"/>
    <option key="#ConfigurationFragments#" value="Renesas##BSP##Board##ra6e2_bgk##"/>
    <option key="#SELECTED_TOOLCHAIN#" value="gcc-arm-embedded"/>
    <option key="#ToolchainVersion#" value="13.2.1.arm-13-7"/>
  </generalSettings>
  <raBspConfiguration>
    <config id="config.bsp.ra6e2.R7FA6E2BB3CFM">
      <property id="config.bsp.part_number" value="config.bsp.part_number.value"/>
      <property id="config.bsp.rom_size_bytes" value="config.bsp.rom_size_bytes.value"/>
      <property id="config.bsp.rom_size_bytes_hidden" value="262144"/>
      <property id="config.bsp.ram_size_bytes" value="config.bsp.ram_size_bytes.value"/>
      <property id="config.bsp.data_flash_size_bytes"
value="config.bsp.data_flash_size_bytes.value"/>
      <property id="config.bsp.package_style" value="config.bsp.package_style.value"/>
      <property id="config.bsp.package_pins" value="config.bsp.package_pins.value"/>
      <property id="config.bsp.irq_count_hidden" value="96"/>
    </config>
    <config id="config.bsp.ra6e2">
      <property id="config.bsp.series" value="config.bsp.series.value"/>
    </config>
    <config id="config.bsp.ra6e2.fsp">
      <property id="config.bsp.fsp.inline_irq_functions"
value="config.bsp.common.inline_irq_functions.enabled"/>
      <property id="config.bsp.fsp.tz.exception_response"
value="config.bsp.fsp.tz.exception_response.nmi"/>
      <property id="config.bsp.fsp.tz.cmsis.bfhfnmins"
value="config.bsp.fsp.tz.cmsis.bfhfnmins.secure"/>
      <property id="config.bsp.fsp.tz.cmsis.sysresetreqs"
value="config.bsp.fsp.tz.cmsis.sysresetreqs.secure_only"/>
      <property id="config.bsp.fsp.tz.cmsis.s_priority_boost"
value="config.bsp.fsp.tz.cmsis.s_priority_boost.disabled"/>
      <property id="config.bsp.fsp.tz.csar" value="config.bsp.fsp.tz.csar.both"/>
      <property id="config.bsp.fsp.tz.rstsar" value="config.bsp.fsp.tz.rstsar.both"/>
      <property id="config.bsp.fsp.tz.bbfsar" value="config.bsp.fsp.tz.bbfsar.both"/>
      <property id="config.bsp.fsp.tz.sramsar.sramprcr"
value="config.bsp.fsp.tz.sramsar.sramprcr.both"/>
      <property id="config.bsp.fsp.tz.sramsar.sramecc"
value="config.bsp.fsp.tz.sramsar.sramecc.both"/>
      <property id="config.bsp.fsp.tz.stbramsar"
value="config.bsp.fsp.tz.stbramsar.both"/>
      <property id="config.bsp.fsp.tz.bussara" value="config.bsp.fsp.tz.bussara.both"/>
      <property id="config.bsp.fsp.tz.bussarb" value="config.bsp.fsp.tz.bussarb.both"/>
      <property id="config.bsp.fsp.tz.uninitialized_ns_application_fallback"
value="config.bsp.fsp.tz.uninitialized_ns_application_fallback.enabled"/>
      <property id="config.bsp.fsp.cache_line_size"
value="config.bsp.fsp.cache_line_size.32"/>
      <property id="config.bsp.fsp.OFS0.iwdt_start_mode"
value="config.bsp.fsp.OFS0.iwdt_start_mode.disabled"/>
      <property id="config.bsp.fsp.OFS0.iwdt_timeout"
value="config.bsp.fsp.OFS0.iwdt_timeout.2048"/>
      <property id="config.bsp.fsp.OFS0.iwdt_divisor"
value="config.bsp.fsp.OFS0.iwdt_divisor.128"/>
      <property id="config.bsp.fsp.OFS0.iwdt_window_end"
value="config.bsp.fsp.OFS0.iwdt_window_end.0"/>
    </config>
  </raBspConfiguration>
</raConfiguration>

```

```

    <property id="config.bsp.fsp.OFS0.iwdt_window_start"
value="config.bsp.fsp.OFS0.iwdt_window_start.100"/>
    <property id="config.bsp.fsp.OFS0.iwdt_reset_interrupt"
value="config.bsp.fsp.OFS0.iwdt_reset_interrupt.Reset"/>
    <property id="config.bsp.fsp.OFS0.iwdt_stop_control"
value="config.bsp.fsp.OFS0.iwdt_stop_control.stops"/>
    <property id="config.bsp.fsp.OFS0.wdt_start_mode"
value="config.bsp.fsp.OFS0.wdt_start_mode.register"/>
    <property id="config.bsp.fsp.OFS0.wdt_timeout"
value="config.bsp.fsp.OFS0.wdt_timeout.16384"/>
    <property id="config.bsp.fsp.OFS0.wdt_divisor"
value="config.bsp.fsp.OFS0.wdt_divisor.128"/>
    <property id="config.bsp.fsp.OFS0.wdt_window_end"
value="config.bsp.fsp.OFS0.wdt_window_end.0"/>
    <property id="config.bsp.fsp.OFS0.wdt_window_start"
value="config.bsp.fsp.OFS0.wdt_window_start.100"/>
    <property id="config.bsp.fsp.OFS0.wdt_reset_interrupt"
value="config.bsp.fsp.OFS0.wdt_reset_interrupt.Reset"/>
    <property id="config.bsp.fsp.OFS0.wdt_stop_control"
value="config.bsp.fsp.OFS0.wdt_stop_control.stops"/>
    <property id="config.bsp.fsp.OFS1.voltage_detection0.start"
value="config.bsp.fsp.OFS1.voltage_detection0.start.disabled"/>
    <property id="config.bsp.fsp.OFS1.voltage_detection0_level"
value="config.bsp.fsp.OFS1.voltage_detection0_level.280"/>
    <property id="config.bsp.fsp.OFS1.hoco_osc"
value="config.bsp.fsp.OFS1.hoco_osc.disabled"/>
    <property id="config.bsp.fsp.BPS.BPS0" value=""/>
    <property id="config.bsp.fsp.PBPS.PBPS0" value=""/>
    <property id="config.bsp.fsp.hoco_fll" value="config.bsp.fsp.hoco_fll.disabled"/>
    <property id="config.bsp.common.main_osc_wait"
value="config.bsp.common.main_osc_wait.wait_8163"/>
    <property id="config.bsp.fsp.mcu.adc.max_freq_hz" value="50000000"/>
    <property id="config.bsp.fsp.mcu.sci_uart.max_baud" value="16666666"/>
    <property id="config.bsp.fsp.mcu.adc.sample_and_hold" value="1"/>
    <property id="config.bsp.fsp.mcu.sci_spi.max_bitrate" value="25000000"/>
    <property id="config.bsp.fsp.mcu.spi.max_bitrate" value="50000000"/>
    <property id="config.bsp.fsp.mcu.iic_master.rate.rate_fastplus" value="1"/>
    <property id="config.bsp.fsp.mcu.canfd.num_channels" value="1"/>
    <property id="config.bsp.fsp.mcu.canfd.rx_fifos" value="2"/>
    <property id="config.bsp.fsp.mcu.canfd.buffer_ram" value="1216"/>
    <property id="config.bsp.fsp.mcu.canfd.afl_rules" value="32"/>
    <property id="config.bsp.fsp.mcu.canfd.afl_rules_each_chnl" value="32"/>
    <property id="config.bsp.fsp.mcu.canfd.max_data_rate_hz" value="5"/>
    <property id="config.bsp.fsp.mcu.sci_uart.cstpen_channels" value="0x0201"/>
    <property id="config.bsp.fsp.mcu.gpt.pin_count_source_channels" value="0xFFFF"/>
    <property id="config.bsp.common.id_mode"
value="config.bsp.common.id_mode.unlocked"/>
    <property id="config.bsp.common.id_code"
value="FFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFF"/>
    <property id="config.bsp.common.id1" value=""/>
    <property id="config.bsp.common.id2" value=""/>
    <property id="config.bsp.common.id3" value=""/>
    <property id="config.bsp.common.id4" value=""/>
    <property id="config.bsp.common.id_fixed" value=""/>
    <property id="config.bsp.fsp.mcu.adc_dmac.samples_per_channel" value="32767"/>
</config>
<config id="config.bsp.ra">
    <property id="config.bsp.common.main" value="1024"/>
    <property id="config.bsp.common.heap" value="1024"/>
    <property id="config.bsp.common.vcc" value="3300"/>
    <property id="config.bsp.common.checking"
value="config.bsp.common.checking.disabled"/>
    <property id="config.bsp.common.assert" value="config.bsp.common.assert.none"/>
    <property id="config.bsp.common.error_log"
value="config.bsp.common.error_log.none"/>

```

```

    <property id="config.bsp.common.soft_reset"
value="config.bsp.common.soft_reset.disabled"/>
    <property id="config.bsp.common.main_osc_populated"
value="config.bsp.common.main_osc_populated.disabled"/>
    <property id="config.bsp.common.pfs_protect"
value="config.bsp.common.pfs_protect.enabled"/>
    <property id="config.bsp.common.c_runtime_init"
value="config.bsp.common.c_runtime_init.enabled"/>
    <property id="config.bsp.common.early_init"
value="config.bsp.common.early_init.disabled"/>
    <property id="config.bsp.common.main_osc_clock_source"
value="config.bsp.common.main_osc_clock_source.crystal"/>
    <property id="config.bsp.common.subclock_populated"
value="config.bsp.common.subclock_populated.enabled"/>
    <property id="config.bsp.common.subclock_drive"
value="config.bsp.common.subclock_drive.standard"/>
    <property id="config.bsp.common.subclock_stabilization_ms" value="1000"/>
  </config>
</raBspConfiguration>
<raClockConfiguration>
  <node id="board.clock.xtal.freq" mul="20000000" option="_edit"/>
  <node id="board.clock.hoco.freq" option="board.clock.hoco.freq.20m"/>
  <node id="board.clock.loco.freq" option="board.clock.loco.freq.32768"/>
  <node id="board.clock.moco.freq" option="board.clock.moco.freq.8m"/>
  <node id="board.clock.subclk.freq" option="board.clock.subclk.freq.32768"/>
  <node id="board.clock.pll.source" option="board.clock.pll.source.hoco"/>
  <node id="board.clock.pll.div" option="board.clock.pll.div.1"/>
  <node id="board.clock.pll.mul" option="board.clock.pll.mul.100"/>
  <node id="board.clock.pll.display" option="board.clock.pll.display.value"/>
  <node id="board.clock.clock.source" option="board.clock.clock.source.pll"/>
  <node id="board.clock.clkout.source" option="board.clock.clkout.source.disabled"/>
  <node id="board.clock.uclk.source" option="board.clock.uclk.source.disabled"/>
  <node id="board.clock.canfdclk.source"
option="board.clock.canfdclk.source.disabled"/>
  <node id="board.clock.cccclk.source" option="board.clock.cccclk.source.disabled"/>
  <node id="board.clock.i3cclk.source" option="board.clock.i3cclk.source.disabled"/>
  <node id="board.clock.iclk.div" option="board.clock.iclk.div.1"/>
  <node id="board.clock.pclka.div" option="board.clock.pclka.div.2"/>
  <node id="board.clock.pclkb.div" option="board.clock.pclkb.div.4"/>
  <node id="board.clock.pclkc.div" option="board.clock.pclkc.div.4"/>
  <node id="board.clock.pclkd.div" option="board.clock.pclkd.div.2"/>
  <node id="board.clock.fclk.div" option="board.clock.fclk.div.4"/>
  <node id="board.clock.clkout.div" option="board.clock.clkout.div.1"/>
  <node id="board.clock.uclk.div" option="board.clock.uclk.div.5"/>
  <node id="board.clock.canfdclk.div" option="board.clock.canfdclk.div.6"/>
  <node id="board.clock.cccclk.div" option="board.clock.cccclk.div.1"/>
  <node id="board.clock.i3cclk.div" option="board.clock.i3cclk.div.1"/>
  <node id="board.clock.iclk.display" option="board.clock.iclk.display.value"/>
  <node id="board.clock.pclka.display" option="board.clock.pclka.display.value"/>
  <node id="board.clock.pclkb.display" option="board.clock.pclkb.display.value"/>
  <node id="board.clock.pclkc.display" option="board.clock.pclkc.display.value"/>
  <node id="board.clock.pclkd.display" option="board.clock.pclkd.display.value"/>
  <node id="board.clock.fclk.display" option="board.clock.fclk.display.value"/>
  <node id="board.clock.clkout.display" option="board.clock.clkout.display.value"/>
  <node id="board.clock.uclk.display" option="board.clock.uclk.display.value"/>
  <node id="board.clock.canfdclk.display"
option="board.clock.canfdclk.display.value"/>
  <node id="board.clock.cccclk.display" option="board.clock.cccclk.display.value"/>
  <node id="board.clock.i3cclk.display" option="board.clock.i3cclk.display.value"/>
</raClockConfiguration>
<raComponentSelection>
  <component apiversion="" class="Common" condition="" group="all"
subgroup="fsp_common" variant="" vendor="Renesas" version="5.5.0">
    <description>Board Support Package Common Files</description>
    <originalPack>Renesas.RA.5.5.0.pack</originalPack>
  </component>

```

```

+   <component apiversion="" class="HAL Drivers" condition="" group="all"
subgroup="r_gpt" variant="" vendor="Renesas" version="5.5.0">
+   <description>General PWM Timer</description>
+   <originalPack>Renesas.RA.5.5.0.pack</originalPack>
+   </component>
  <component apiversion="" class="HAL Drivers" condition="" group="all"
subgroup="r_ioport" variant="" vendor="Renesas" version="5.5.0">
    <description>I/O Port</description>
    <originalPack>Renesas.RA.5.5.0.pack</originalPack>
  </component>
  <component apiversion="" class="CMSIS" condition="" group="CMSIS5" subgroup="CoreM"
variant="" vendor="Arm" version="6.1.0+fsp.5.5.0">
    <description>Arm CMSIS Version 6 - Core (M)</description>
    <originalPack>Arm.CMSIS6.6.1.0+fsp.5.5.0.pack</originalPack>
  </component>
  <component apiversion="" class="BSP" condition="" group="Board" subgroup="ra6e2_bgk"
variant="" vendor="Renesas" version="5.5.0">
    <description>RA6E2-BGK Board Support Files</description>
    <originalPack>Renesas.RA_board_ra6e2_bgk.5.5.0.pack</originalPack>
  </component>
  <component apiversion="" class="BSP" condition="" group="ra6e2" subgroup="device"
variant="R7FA6E2BB3CFM" vendor="Renesas" version="5.5.0">
    <description>Board support package for R7FA6E2BB3CFM</description>
    <originalPack>Renesas.RA_mcu_ra6e2.5.5.0.pack</originalPack>
  </component>
  <component apiversion="" class="BSP" condition="" group="ra6e2" subgroup="device"
variant="" vendor="Renesas" version="5.5.0">
    <description>Board support package for RA6E2</description>
    <originalPack>Renesas.RA_mcu_ra6e2.5.5.0.pack</originalPack>
  </component>
  <component apiversion="" class="BSP" condition="" group="ra6e2" subgroup="fsp"
variant="" vendor="Renesas" version="5.5.0">
    <description>Board support package for RA6E2 - FSP Data</description>
    <originalPack>Renesas.RA_mcu_ra6e2.5.5.0.pack</originalPack>
  </component>
  <component apiversion="" class="BSP" condition="" group="ra6e2" subgroup="events"
variant="" vendor="Renesas" version="5.5.0">
    <description>Board support package for RA6E2 - Events</description>
    <originalPack>Renesas.RA_mcu_ra6e2.5.5.0.pack</originalPack>
  </component>
</raComponentSelection>
<raElcConfiguration/>
<raIcuConfiguration/>
<raModuleConfiguration>
  <module id="module.driver.ioport_on_ioport.0">
    <property id="module.driver.ioport.name" value="g_ioport"/>
    <property id="module.driver.ioport.elc_trigger_ioport1" value="_disabled"/>
    <property id="module.driver.ioport.elc_trigger_ioport2" value="_disabled"/>
    <property id="module.driver.ioport.elc_trigger_ioport3" value="_disabled"/>
    <property id="module.driver.ioport.elc_trigger_ioport4" value="_disabled"/>
    <property id="module.driver.ioport.pincfg" value="g_bsp_pin_cfg"/>
  </module>
  <module id="module.driver.timer_on_gpt.1083164079">
    <property id="module.driver.timer.name" value="g_timer_pwm_led1"/>
    <property id="module.driver.timer.channel" value="1"/>
    <property id="module.driver.timer.mode"
value="module.driver.timer.mode.mode_pwm"/>
    <property id="module.driver.timer.period" value="1"/>
    <property id="module.driver.timer.compare_match.a.status"
value="module.driver.timer.compare_match.a.status.disabled"/>
    <property id="module.driver.timer.compare_match.a.value" value="0"/>
    <property id="module.driver.timer.compare_match.b.status"
value="module.driver.timer.compare_match.b.status.disabled"/>
    <property id="module.driver.timer.compare_match.b.value" value="0"/>
    <property id="module.driver.timer.unit"
value="module.driver.timer.unit.unit_period_sec"/>

```



```

        <property id="module.driver.timer.gtior.gtioa.initial_output_level"
value="module.driver.timer.gtior.gtioa.initial_output_level.low"/>
        <property id="module.driver.timer.gtior.gtioa.cycle_end_output_level"
value="module.driver.timer.gtior.gtioa.cycle_end_output_level.retain"/>
        <property id="module.driver.timer.gtior.gtioa.compare_match_output_level"
value="module.driver.timer.gtior.gtioa.compare_match_output_level.retain"/>
        <property id="module.driver.timer.gtior.gtioa.count_stop_retain"
value="module.driver.timer.gtior.gtioa.count_stop_retain.disabled"/>
        <property id="module.driver.timer.gtior.gtioa.initial_output_level"
value="module.driver.timer.gtior.gtioa.initial_output_level.low"/>
        <property id="module.driver.timer.gtior.gtioa.cycle_end_output_level"
value="module.driver.timer.gtior.gtioa.cycle_end_output_level.retain"/>
        <property id="module.driver.timer.gtior.gtioa.compare_match_output_level"
value="module.driver.timer.gtior.gtioa.compare_match_output_level.retain"/>
        <property id="module.driver.timer.gtior.gtioa.count_stop_retain"
value="module.driver.timer.gtior.gtioa.count_stop_retain.disabled"/>
        <property id="module.driver.timer.gtior.gtioa.custom_waveform_enable"
value="module.driver.timer.gtior.gtioa.custom_waveform_enable.disabled"/>
        <property id="module.driver.timer.duty_cycle" value="50"/>
        <property id="module.driver.timer.gtioa_output_enabled"
value="module.driver.timer.gtioa_output_enabled.false"/>
        <property id="module.driver.timer.gtioa_stop_level"
value="module.driver.timer.gtioa_stop_level.pin_level_low"/>
        <property id="module.driver.timer.gtioa_output_enabled"
value="module.driver.timer.gtioa_output_enabled.true"/>
        <property id="module.driver.timer.gtioa_stop_level"
value="module.driver.timer.gtioa_stop_level.pin_level_low"/>
        <property id="module.driver.timer.count_up_source" value=""/>
        <property id="module.driver.timer.count_down_source" value=""/>
        <property id="module.driver.timer.start_source" value=""/>
        <property id="module.driver.timer.stop_source" value=""/>
        <property id="module.driver.timer.clear_source" value=""/>
        <property id="module.driver.timer.capture_a_source" value=""/>
        <property id="module.driver.timer.capture_b_source" value=""/>
        <property id="module.driver.timer.gtioa_filter"
value="module.driver.timer.gtioa_filter.gtioa_filter_none"/>
        <property id="module.driver.timer.gtioa_filter"
value="module.driver.timer.gtioa_filter.gtioa_filter_none"/>
        <property id="module.driver.timer.p_callback" value="NULL"/>
        <property id="module.driver.timer.ipl" value="_disabled"/>
        <property id="module.driver.timer.capture_a_ipl" value="_disabled"/>
        <property id="module.driver.timer.capture_b_ipl" value="_disabled"/>
        <property id="module.driver.timer.trough_ipl" value="_disabled"/>
        <property id="module.driver.timer.extra"
value="module.driver.timer.extra.disabled"/>
        <property id="module.driver.timer.poeg_link"
value="module.driver.timer.poeg_link.poeg_link_poeg0"/>
        <property id="module.driver.timer.output_disable" value=""/>
        <property id="module.driver.timer.adc_trigger" value=""/>
        <property id="module.driver.timer.adc_a_compare_match" value="0"/>
        <property id="module.driver.timer.adc_b_compare_match" value="0"/>
        <property id="module.driver.timer.dead_time_count_up" value="0"/>
        <property id="module.driver.timer.dead_time_count_down" value="0"/>
        <property id="module.driver.timer.interrupt_skip.source"
value="module.driver.timer.interrupt_skip.source.none"/>
        <property id="module.driver.timer.interrupt_skip.count"
value="module.driver.timer.interrupt_skip.count.count_0"/>
        <property id="module.driver.timer.interrupt_skip.adc"
value="module.driver.timer.interrupt_skip.adc.none"/>
        <property id="module.driver.timer.gtioa_disable_setting"
value="module.driver.timer.gtioa_disable_setting.gtioa_disable_prohibited"/>
        <property id="module.driver.timer.gtioa_disable_setting"
value="module.driver.timer.gtioa_disable_setting.gtioa_disable_prohibited"/>
        </module>
+   <module id="module.driver.timer_on_gpt.230584519">
+       <property id="module.driver.timer.name" value="g_timer_pwm_led2"/>

```



```

+      <property id="module.driver.timer.channel" value="3"/>
+      <property id="module.driver.timer.mode"
value="module.driver.timer.mode.mode_pwm"/>
+      <property id="module.driver.timer.period" value="1"/>
+      <property id="module.driver.timer.compare_match.a.status"
value="module.driver.timer.compare_match.a.status.disabled"/>
+      <property id="module.driver.timer.compare_match.a.value" value="0"/>
+      <property id="module.driver.timer.compare_match.b.status"
value="module.driver.timer.compare_match.b.status.disabled"/>
+      <property id="module.driver.timer.compare_match.b.value" value="0"/>
+      <property id="module.driver.timer.unit"
value="module.driver.timer.unit.unit_period_sec"/>
+      <property id="module.driver.timer.gtior.gtioa.initial_output_level"
value="module.driver.timer.gtior.gtioa.initial_output_level.low"/>
+      <property id="module.driver.timer.gtior.gtioa.cycle_end_output_level"
value="module.driver.timer.gtior.gtioa.cycle_end_output_level.retain"/>
+      <property id="module.driver.timer.gtior.gtioa.compare_match_output_level"
value="module.driver.timer.gtior.gtioa.compare_match_output_level.retain"/>
+      <property id="module.driver.timer.gtior.gtioa.count_stop_retain"
value="module.driver.timer.gtior.gtioa.count_stop_retain.disabled"/>
+      <property id="module.driver.timer.gtior.gtioa.initial_output_level"
value="module.driver.timer.gtior.gtioa.initial_output_level.low"/>
+      <property id="module.driver.timer.gtior.gtioa.cycle_end_output_level"
value="module.driver.timer.gtior.gtioa.cycle_end_output_level.retain"/>
+      <property id="module.driver.timer.gtior.gtioa.compare_match_output_level"
value="module.driver.timer.gtior.gtioa.compare_match_output_level.retain"/>
+      <property id="module.driver.timer.gtior.gtioa.count_stop_retain"
value="module.driver.timer.gtior.gtioa.count_stop_retain.disabled"/>
+      <property id="module.driver.timer.gtior.gtioa.custom_waveform_enable"
value="module.driver.timer.gtior.custom_waveform_enable.disabled"/>
+      <property id="module.driver.timer.duty_cycle" value="50"/>
+      <property id="module.driver.timer.gtioca_output_enabled"
value="module.driver.timer.gtioca_output_enabled.false"/>
+      <property id="module.driver.timer.gtioca_stop_level"
value="module.driver.timer.gtioca_stop_level.pin_level_low"/>
+      <property id="module.driver.timer.gtiocb_output_enabled"
value="module.driver.timer.gtiocb_output_enabled.true"/>
+      <property id="module.driver.timer.gtiocb_stop_level"
value="module.driver.timer.gtiocb_stop_level.pin_level_low"/>
+      <property id="module.driver.timer.count_up_source" value=""/>
+      <property id="module.driver.timer.count_down_source" value=""/>
+      <property id="module.driver.timer.start_source" value=""/>
+      <property id="module.driver.timer.stop_source" value=""/>
+      <property id="module.driver.timer.clear_source" value=""/>
+      <property id="module.driver.timer.capture_a_source" value=""/>
+      <property id="module.driver.timer.capture_b_source" value=""/>
+      <property id="module.driver.timer.gtioca_filter"
value="module.driver.timer.gtioc_filter.gtioc_filter_none"/>
+      <property id="module.driver.timer.gtiocb_filter"
value="module.driver.timer.gtioc_filter.gtioc_filter_none"/>
+      <property id="module.driver.timer.p_callback" value="NULL"/>
+      <property id="module.driver.timer.ipl" value="_disabled"/>
+      <property id="module.driver.timer.capture_a_ipl" value="_disabled"/>
+      <property id="module.driver.timer.capture_b_ipl" value="_disabled"/>
+      <property id="module.driver.timer.trough_ipl" value="_disabled"/>
+      <property id="module.driver.timer.extra"
value="module.driver.timer.extra.disabled"/>
+      <property id="module.driver.timer.poeg_link"
value="module.driver.timer.poeg_link.poeg_link_poeg0"/>
+      <property id="module.driver.timer.output_disable" value=""/>
+      <property id="module.driver.timer.adc_trigger" value=""/>
+      <property id="module.driver.timer.adc_a_compare_match" value="0"/>
+      <property id="module.driver.timer.adc_b_compare_match" value="0"/>
+      <property id="module.driver.timer.dead_time_count_up" value="0"/>
+      <property id="module.driver.timer.dead_time_count_down" value="0"/>

```

```

+      <property id="module.driver.timer.interrupt_skip.source"
value="module.driver.timer.interrupt_skip.source.none"/>
+      <property id="module.driver.timer.interrupt_skip.count"
value="module.driver.timer.interrupt_skip.count.count_0"/>
+      <property id="module.driver.timer.interrupt_skip.adc"
value="module.driver.timer.interrupt_skip.skip_sources.interrupt_skip.adc.none"/>
+      <property id="module.driver.timer.gtioca_disable_setting"
value="module.driver.timer.gtioca_disable_setting.gtioc_disable_prohibited"/>
+      <property id="module.driver.timer.gtiocb_disable_setting"
value="module.driver.timer.gtiocb_disable_setting.gtioc_disable_prohibited"/>
+    </module>
    <context id="_hal.0">
      <stack module="module.driver.ioport_on_ioport.0"/>
+      <stack module="module.driver.timer_on_gpt.1083164079"/>
+      <stack module="module.driver.timer_on_gpt.230584519"/>
    </context>
+    <config id="config.driver.gpt">
+      <property id="config.driver.gpt.param_checking_enable"
value="config.driver.gpt.param_checking_enable.bsp"/>
+      <property id="config.driver.gpt.output_support_enable"
value="config.driver.gpt.output_support_enable.enabled"/>
+      <property id="config.driver.gpt.write_protect_enable"
value="config.driver.gpt.write_protect_enable.disabled"/>
+    </config>
    <config id="config.driver.ioport">
      <property id="config.driver.ioport.checking"
value="config.driver.ioport.checking.system"/>
    </config>
  </raModuleConfiguration>
  <raPinConfiguration>
    <symbolicName propertyId="p000.symbolic_name" value="ARDUINO_A0"/>
    <symbolicName propertyId="p001.symbolic_name" value="ARDUINO_A1"/>
    <symbolicName propertyId="p002.symbolic_name" value="ARDUINO_A2"/>
    <symbolicName propertyId="p003.symbolic_name" value="ARDUINO_A4"/>
    <symbolicName propertyId="p004.symbolic_name" value="ARDUINO_A3"/>
    <symbolicName propertyId="p005.symbolic_name" value="PMOD1_RESET"/>
    <symbolicName propertyId="p006.symbolic_name" value="ARDUINO_D8"/>
    <symbolicName propertyId="p008.symbolic_name" value="ARDUINO_D7"/>
    <symbolicName propertyId="p013.symbolic_name" value="ARDUINO_A5"/>
    <symbolicName propertyId="p014.symbolic_name" value="PMOD2_GPI01"/>
    <symbolicName propertyId="p015.symbolic_name" value="PMOD2_GPI02"/>
    <symbolicName propertyId="p100.symbolic_name" value="PMOD2_SCL0_ARDUINO_SCL"/>
    <symbolicName propertyId="p101.symbolic_name" value="PMOD2_SDA0_ARDUINO_SDA"/>
    <symbolicName propertyId="p104.symbolic_name" value="LED1"/>
    <symbolicName propertyId="p105.symbolic_name" value="ARDUINO_D2"/>
    <symbolicName propertyId="p106.symbolic_name" value="PMOD1_GPI01"/>
    <symbolicName propertyId="p107.symbolic_name" value="PMOD1_GPI02"/>
    <symbolicName propertyId="p108.symbolic_name" value="DEBUG_SWDI0"/>
    <symbolicName propertyId="p109.symbolic_name" value="PMOD1_TX_ARDUINO_D11"/>
    <symbolicName propertyId="p110.symbolic_name" value="PMOD1_RX_ARDUINO_D12"/>
    <symbolicName propertyId="p111.symbolic_name" value="PMOD1_RSPCK_ARDUINO_D13"/>
    <symbolicName propertyId="p112.symbolic_name" value="LED2"/>
    <symbolicName propertyId="p113.symbolic_name" value="ARDUINO_D6"/>
    <symbolicName propertyId="p205.symbolic_name" value="PMOD2_IRQ"/>
    <symbolicName propertyId="p206.symbolic_name" value="PMOD2_SSIDATA"/>
    <symbolicName propertyId="p207.symbolic_name" value="PMOD2_SSICLK"/>
    <symbolicName propertyId="p208.symbolic_name" value="ARDUINO_RESET"/>
    <symbolicName propertyId="p300.symbolic_name" value="DEBUG_SWDCCLK"/>
    <symbolicName propertyId="p301.symbolic_name" value="ARDUINO_D10"/>
    <symbolicName propertyId="p402.symbolic_name" value="PMOD1_IRQ"/>
    <symbolicName propertyId="p403.symbolic_name" value="ARDUINO_D9"/>
    <symbolicName propertyId="p407.symbolic_name" value="PMOD2_SSIBCK"/>
    <symbolicName propertyId="p408.symbolic_name" value="ARDUINO_D3"/>
    <symbolicName propertyId="p409.symbolic_name" value="ARDUINO_D5"/>
    <symbolicName propertyId="p410.symbolic_name" value="PMOD2_MISO_ARDUINO_D0"/>

```

```

    <symbolicName propertyId="p411.symbolic_name"
value="PMOD2_SENSOR_RESET_ARDUINO_D1"/>
    <symbolicName propertyId="p500.symbolic_name" value="ARDUINO_D4"/>
    <pincfg active="true" name="BGK_RA6E2.pincfg" selected="true"
symbol="g_bsp_pin_cfg">
        <configSetting altId="adc0.an000.p000" configurationId="adc0.an000"/>
        <configSetting altId="adc0.an001.p001" configurationId="adc0.an001"/>
        <configSetting altId="adc0.an002.p002" configurationId="adc0.an002"/>
        <configSetting altId="adc0.an004.p004" configurationId="adc0.an004"/>
        <configSetting altId="adc0.an007.p003" configurationId="adc0.an007"/>
        <configSetting altId="adc0.an011.p013" configurationId="adc0.an011"/>
        <configSetting altId="adc0.mode.custom.free" configurationId="adc0.mode"/>
+       <configSetting altId="gpt1.gtioc1b.p104" configurationId="gpt1.gtioc1b"/>
+       <configSetting altId="gpt1.mode.gtiocaorgtiocb.free"
configurationId="gpt1.mode"/>
+       <configSetting altId="gpt3.gtioc3b.p112" configurationId="gpt3.gtioc3b"/>
+       <configSetting altId="gpt3.mode.gtiocaorgtiocb.free"
configurationId="gpt3.mode"/>
        <configSetting altId="jtag_fslash_swd.mode.swd.free"
configurationId="jtag_fslash_swd.mode"/>
        <configSetting altId="jtag_fslash_swd.swclk.p300"
configurationId="jtag_fslash_swd.swclk"/>
        <configSetting altId="jtag_fslash_swd.swdio.p108"
configurationId="jtag_fslash_swd.swdio"/>
        <configSetting altId="p000.adc0.an000" configurationId="p000"/>
        <configSetting altId="p000.gpio_mode.gpio_mode_an"
configurationId="p000.gpio_mode"/>
        <configSetting altId="p001.adc0.an001" configurationId="p001"/>
        <configSetting altId="p001.gpio_mode.gpio_mode_an"
configurationId="p001.gpio_mode"/>
        <configSetting altId="p002.adc0.an002" configurationId="p002"/>
        <configSetting altId="p002.gpio_mode.gpio_mode_an"
configurationId="p002.gpio_mode"/>
        <configSetting altId="p003.adc0.an007" configurationId="p003"/>
        <configSetting altId="p003.gpio_mode.gpio_mode_an"
configurationId="p003.gpio_mode"/>
        <configSetting altId="p004.adc0.an004" configurationId="p004"/>
        <configSetting altId="p004.gpio_mode.gpio_mode_an"
configurationId="p004.gpio_mode"/>
        <configSetting altId="p005.output.high" configurationId="p005"/>
        <configSetting altId="p005.gpio_mode.gpio_mode_out.high"
configurationId="p005.gpio_mode"/>
        <configSetting altId="p006.input" configurationId="p006"/>
        <configSetting altId="p006.gpio_mode.gpio_mode_in"
configurationId="p006.gpio_mode"/>
        <configSetting altId="p008.input" configurationId="p008"/>
        <configSetting altId="p008.gpio_mode.gpio_mode_in"
configurationId="p008.gpio_mode"/>
        <configSetting altId="p013.adc0.an011" configurationId="p013"/>
        <configSetting altId="p013.gpio_mode.gpio_mode_an"
configurationId="p013.gpio_mode"/>
        <configSetting altId="p014.input" configurationId="p014"/>
        <configSetting altId="p014.gpio_mode.gpio_mode_in"
configurationId="p014.gpio_mode"/>
        <configSetting altId="p015.input" configurationId="p015"/>
        <configSetting altId="p015.gpio_mode.gpio_mode_in"
configurationId="p015.gpio_mode"/>
        <configSetting altId="p100.sci0.rxd0" configurationId="p100"/>
        <configSetting altId="p100.gpio_mode.gpio_mode_peripheral"
configurationId="p100.gpio_mode"/>
        <configSetting altId="p100.gpio_otype.gpio_otype_n_ch_od"
configurationId="p100.gpio_otype"/>
        <configSetting altId="p101.sci0.txd0" configurationId="p101"/>
        <configSetting altId="p101.gpio_mode.gpio_mode_peripheral"
configurationId="p101.gpio_mode"/>

```

```

        <configSetting altId="p101.gpio_otype.gpio_otype_n_ch_od"
configurationId="p101.gpio_otype"/>
#        <configSetting altId="p104.gpt1.gtioc1b" configurationId="p104"/>
#        <configSetting altId="p104.gpio_mode.gpio_mode_peripheral"
configurationId="p104.gpio_mode"/>
        <configSetting altId="p105.input" configurationId="p105"/>
        <configSetting altId="p105.gpio_mode.gpio_mode_in"
configurationId="p105.gpio_mode"/>
        <configSetting altId="p106.input" configurationId="p106"/>
        <configSetting altId="p106.gpio_mode.gpio_mode_in"
configurationId="p106.gpio_mode"/>
        <configSetting altId="p107.input" configurationId="p107"/>
        <configSetting altId="p107.gpio_mode.gpio_mode_in"
configurationId="p107.gpio_mode"/>
        <configSetting altId="p108.jtag_fslash_swd.swdio" configurationId="p108"/>
        <configSetting altId="p108.gpio_mode.gpio_mode_peripheral"
configurationId="p108.gpio_mode"/>
        <configSetting altId="p109.sci9.txd9" configurationId="p109"/>
        <configSetting altId="p109.gpio_mode.gpio_mode_peripheral"
configurationId="p109.gpio_mode"/>
        <configSetting altId="p110.sci9.rxd9" configurationId="p110"/>
        <configSetting altId="p110.gpio_mode.gpio_mode_peripheral"
configurationId="p110.gpio_mode"/>
        <configSetting altId="p111.input" configurationId="p111"/>
        <configSetting altId="p111.gpio_mode.gpio_mode_in"
configurationId="p111.gpio_mode"/>
#        <configSetting altId="p112.gpt3.gtioc3b" configurationId="p112"/>
#        <configSetting altId="p112.gpio_mode.gpio_mode_peripheral"
configurationId="p112.gpio_mode"/>
        <configSetting altId="p113.input" configurationId="p113"/>
        <configSetting altId="p113.gpio_mode.gpio_mode_in"
configurationId="p113.gpio_mode"/>
        <configSetting altId="p205.input" configurationId="p205"/>
        <configSetting altId="p205.gpio_mode.gpio_mode_in"
configurationId="p205.gpio_mode"/>
        <configSetting altId="p206.ssie0.ssidata0" configurationId="p206"/>
        <configSetting altId="p206.gpio_mode.gpio_mode_peripheral"
configurationId="p206.gpio_mode"/>
        <configSetting altId="p207.ssie0.ssilrck0" configurationId="p207"/>
        <configSetting altId="p207.gpio_mode.gpio_mode_peripheral"
configurationId="p207.gpio_mode"/>
        <configSetting altId="p208.input" configurationId="p208"/>
        <configSetting altId="p208.gpio_mode.gpio_mode_in"
configurationId="p208.gpio_mode"/>
        <configSetting altId="p300.jtag_fslash_swd.swclk" configurationId="p300"/>
        <configSetting altId="p300.gpio_mode.gpio_mode_peripheral"
configurationId="p300.gpio_mode"/>
        <configSetting altId="p301.input" configurationId="p301"/>
        <configSetting altId="p301.gpio_mode.gpio_mode_in"
configurationId="p301.gpio_mode"/>
        <configSetting altId="p402.input" configurationId="p402"/>
        <configSetting altId="p402.gpio_mode.gpio_mode_in"
configurationId="p402.gpio_mode"/>
        <configSetting altId="p403.input" configurationId="p403"/>
        <configSetting altId="p403.gpio_mode.gpio_mode_in"
configurationId="p403.gpio_mode"/>
        <configSetting altId="p407.ssie0.ssibck0" configurationId="p407"/>
        <configSetting altId="p407.gpio_mode.gpio_mode_peripheral"
configurationId="p407.gpio_mode"/>
        <configSetting altId="p408.input" configurationId="p408"/>
        <configSetting altId="p408.gpio_mode.gpio_mode_in"
configurationId="p408.gpio_mode"/>
        <configSetting altId="p409.input" configurationId="p409"/>
        <configSetting altId="p409.gpio_mode.gpio_mode_in"
configurationId="p409.gpio_mode"/>
        <configSetting altId="p410.input" configurationId="p410"/>

```



```

    <configSetting altId="p410.gpio_mode.gpio_mode_in"
configurationId="p410.gpio_mode"/>
    <configSetting altId="p411.output.high" configurationId="p411"/>
    <configSetting altId="p411.gpio_mode.gpio_mode_out.high"
configurationId="p411.gpio_mode"/>
    <configSetting altId="p500.input" configurationId="p500"/>
    <configSetting altId="p500.gpio_mode.gpio_mode_in"
configurationId="p500.gpio_mode"/>
    <configSetting altId="sci0.mode.simplei2c.free" configurationId="sci0.mode"/>
    <configSetting altId="sci0.rxd0.p100" configurationId="sci0.rxd0"/>
    <configSetting altId="sci0.txd0.p101" configurationId="sci0.txd0"/>
    <configSetting altId="sci9.mode.asynchronousuart.free"
configurationId="sci9.mode"/>
    <configSetting altId="sci9.rxd9.p110" configurationId="sci9.rxd9"/>
    <configSetting altId="sci9.txd9.p109" configurationId="sci9.txd9"/>
    <configSetting altId="ssie0.mode.half_dash_duplex.c"
configurationId="ssie0.mode"/>
    <configSetting altId="ssie0.pairing.c" configurationId="ssie0.pairing"/>
    <configSetting altId="ssie0.ssibck0.p407" configurationId="ssie0.ssibck0"/>
    <configSetting altId="ssie0.ssidata0.p206" configurationId="ssie0.ssidata0"/>
    <configSetting altId="ssie0.ssilrck0.p207" configurationId="ssie0.ssilrck0"/>
+    <lockSetting id="gpt1.gtioc1b" lock="true"/>
  </pincfg>
  <pincfg active="false" name="R7FA6E2BB3CFM.pincfg" selected="false" symbol="">
+    <configSetting altId="gpt1.gtioc1b.p104" configurationId="gpt1.gtioc1b"/>
+    <configSetting altId="gpt1.mode.gtiocaorgtiocb.free"
configurationId="gpt1.mode"/>
    <configSetting altId="jtag_fslash_swd.mode.swd.free"
configurationId="jtag_fslash_swd.mode"/>
    <configSetting altId="jtag_fslash_swd.swclk.p300"
configurationId="jtag_fslash_swd.swclk"/>
    <configSetting altId="jtag_fslash_swd.swdio.p108"
configurationId="jtag_fslash_swd.swdio"/>
+    <configSetting altId="p104.gpt1.gtioc1b" configurationId="p104"/>
+    <configSetting altId="p104.gpio_mode.gpio_mode_peripheral"
configurationId="p104.gpio_mode"/>
    <configSetting altId="p108.jtag_fslash_swd.swdio" configurationId="p108"/>
    <configSetting altId="p108.gpio_mode.gpio_mode_peripheral"
configurationId="p108.gpio_mode"/>
    <configSetting altId="p300.jtag_fslash_swd.swclk" configurationId="p300"/>
    <configSetting altId="p300.gpio_mode.gpio_mode_peripheral"
configurationId="p300.gpio_mode"/>
  </pincfg>
</raPinConfiguration>
</raConfiguration>

```

Code Block 6 configuration.xml

Files to be added:

To initialize the timer PWM stack, middleware API support is required. The following are the files responsible for initializing the external interrupt stack. This function is called in **main_application.c** to initialize the stack.

```

bgk_ra6e2_baremetal/src/gpt_timer.c
bgk_ra6e2_baremetal/src/gpt_timer.h

```

The following is the content of the file that should be added to the project.

```

/*****
*****
* File Name      : gpt_timer.c
* Description    : Contains function definition.
*****
*****
/*****
*****/
/*****
*****
* Copyright (c) 2020 - 2024 Renesas Electronics Corporation and/or its affiliates
*
* SPDX-License-Identifier: BSD-3-Clause
*****
*****/

#include "common_utils.h"
#include "gpt_timer.h"
#include "log_disabled.h"
// #include "log_error.h"
// #include "log_warning.h"
// #include "log_info.h"
// #include "log_debug.h"
/*****
*****//**
* @addtogroup r_gpt_ep
* @{

*****
*****/

/* Boolean flag to determine one-shot mode timer is expired or not.*/

/* Store Timer open state*/

/*****
*****
* @brief      Initialize GPT timer.
* @param[in]  p_timer_ctl    Timer instance control structure
* @param[in]  p_timer_cfg    Timer instance Configuration structure
* @param[in]  timer_mode     Mode of GPT Timer
* @retval     FSP_SUCCESS    Upon successful open of timer.
* @retval     Any Other Error code apart from FSP_SUCCESS on Unsuccessful open .
*****
*****/
fsp_err_t init_gpt_timer(timer_ctrl_t * const p_timer_ctl, timer_cfg_t const * const
p_timer_cfg)
{
    fsp_err_t err = FSP_SUCCESS;

    /* Initialize GPT Timer */
    err = R_GPT_Open(p_timer_ctl, p_timer_cfg);
    if (FSP_SUCCESS != err)
    {
        log_error ("\r\n ** R_GPT_TimerOpen FAILED ** \r\n");
        return err;
    }

    return err;
}

/*****
*****
* @brief      Start GPT timers in periodic, one shot, PWM mode.
* @param[in]  p_timer_ctl    Timer instance control structure
* @retval     FSP_SUCCESS    Upon successful start of timer.
*****
*****

```



```

* @retval      Any Other Error code apart from FSP_SUCCES on Unsuccessful start .
*****
*****/
fsp_err_t start_gpt_timer (timer_ctrl_t * const p_timer_ctl)
{
    fsp_err_t err = FSP_SUCCESS;

    /* Starts GPT timer */
    err = R_GPT_Start(p_timer_ctl);
    if (FSP_SUCCESS != err)
    {
        /* In case of GPT_open is successful and start fails, requires a immediate
        cleanup.
        * Since, cleanup for GPT open is done in start_gpt_timer,Hence cleanup is not
        required */
        log_error ("\r\n ** R_GPT_Start API failed ** \r\n");
    }
    return err;
}

/*****
*****
* @brief      set  duty cycle of PWM timer.
* @param[in]  duty_cycle_percent.
* @retval     FSP_SUCCESS on correct duty cycle set.
* @retval     FSP_INVALID_ARGUMENT on invalid info.
*****
*****/
fsp_err_t set_timer_duty_cycle(uint8_t duty_cycle_percent ,timer_ctrl_t * const
p_timer_ctl)
{
    fsp_err_t err                                = FSP_SUCCESS;
    uint32_t duty_cycle_counts                    = RESET_VALUE;
    uint32_t current_period_counts                = RESET_VALUE;
    timer_info_t info                            = {(timer_direction_t)RESET_VALUE,
RESET_VALUE, RESET_VALUE};

    /* Get the current period setting. */
    err = R_GPT_InfoGet(p_timer_ctl, &info);
    if (FSP_SUCCESS != err)
    {
        /* GPT Timer InfoGet Failure message */
        log_error ("\r\n ** R_GPT_InfoGet API failed ** \r\n");
    }
    else
    {
        /* update period counts locally. */
        current_period_counts = info.period_counts;

        /* Calculate the desired duty cycle based on the current period. Note that if
        the period could be larger than
        * UINT32_MAX / 100, this calculation could overflow. A cast to uint64_t is used
        to prevent this. The cast is
        * not required for 16-bit timers. */
        duty_cycle_counts =(uint32_t) ((uint64_t) (current_period_counts *
duty_cycle_percent) /
GPT_MAX_PERCENT);
#ifdef BOARD_RA4W1_EK || defined (BOARD_RA6T1_RSSK) ||defined (BOARD_RA6T3_MCK) ||
defined (BOARD_RA4T1_MCK)
        duty_cycle_counts = (current_period_counts - duty_cycle_counts);
#endif
    }
}

```

```

    /* Duty Cycle Set API set the desired intensity on the on-board LED */
    err = R_GPT_DutyCycleSet(p_timer_ctl, duty_cycle_counts, TIMER_PIN);
    if(FSP_SUCCESS != err)
    {
        /* GPT Timer DutyCycleSet Failure message */
        /* In case of GPT_open is successful and DutyCycleSet fails, requires a
        immediate cleanup.
        * Since, cleanup for GPT open is done in timer_duty_cycle_set,Hence cleanup
        is not required */
        log_error ("\r\n ** R_GPT_DutyCycleSet API failed ** \r\n");
    }
}
return err;
}

/*****
*****
* @brief      set  duty cycle of PWM timer.
* @param[in]  duty_cycle_percent.
* @retval     FSP_SUCCESS on correct duty cycle set.
* @retval     FSP_INVALID_ARGUMENT on invalid info.
*****
*****/
fsp_err_t set_timer_Period_and_Dutycycle(uint32_t period_counts ,uint8_t
duty_cycle_percent, timer_ctrl_t * const p_timer_ctl)
{
    fsp_err_t err                = FSP_SUCCESS;
    uint32_t duty_cycle_counts   = RESET_VALUE;
    uint32_t current_period_counts = RESET_VALUE;
    timer_info_t info            = {(timer_direction_t)RESET_VALUE,
RESET_VALUE, RESET_VALUE};
    gpt_instance_ctrl_t * p_instance_ctrl = (gpt_instance_ctrl_t *) p_timer_ctl;
    /* PeriodSet Set API set the desired intensity on the on-board LED */
    err = R_GPT_PeriodSet(p_timer_ctl, period_counts);
    if(FSP_SUCCESS != err)
    {
        /* GPT Timer DutyCycleSet Failure message */
        /* In case of GPT_open is successful and DutyCycleSet fails, requires a
        immediate cleanup.
        * Since, cleanup for GPT open is done in timer_duty_cycle_set,Hence cleanup is
        not required */
        log_error ("\r\n ** R_GPT_PeriodSet API failed ** \r\n");
    }

    current_period_counts = period_counts;

    /* Calculate the desired duty cycle based on the current period. Note that if the
    period could be larger than
    * UINT32_MAX / 100, this calculation could overflow. A cast to uint64_t is used to
    prevent this. The cast is
    * not required for 16-bit timers. */
    duty_cycle_counts =(uint32_t) ((uint64_t) (current_period_counts *
duty_cycle_percent) /
GPT_MAX_PERCENT);
#ifdef BOARD_RA4W1_EK || defined (BOARD_RA6T1_RSSK) ||defined (BOARD_RA6T3_MCK) ||
defined (BOARD_RA4T1_MCK)
    duty_cycle_counts = (current_period_counts - duty_cycle_counts);
#endif

    /* Duty Cycle Set API set the desired intensity on the on-board LED */
    err = R_GPT_DutyCycleSet(p_timer_ctl, duty_cycle_counts, TIMER_PIN);
    if(FSP_SUCCESS != err)
    {

```

```

        /* GPT Timer DutyCycleSet Failure message */
        /* In case of GPT_open is successful and DutyCycleSet fails, requires a
        immediate cleanup.
        * Since, cleanup for GPT open is done in timer_duty_cycle_set,Hence cleanup is
        not required */
        log_error ("\r\n ** R_GPT_DutyCycleSet API failed ** \r\n");
    }
    return err;
}

/*****
*****
* @brief      Close the GPT HAL driver.
* @param[in]  p_timer_ctl    Timer instance control structure
* @retval     None
*****
*****/
void deinit_gpt_timer(timer_ctrl_t * const p_timer_ctl)
{
    fsp_err_t err = FSP_SUCCESS;

    /* Timer Close API call*/
    err = R_GPT_Close(p_timer_ctl);
    if (FSP_SUCCESS != err)
    {
        /* GPT Close failure message */
        log_error ("\r\n ** R_GPT_Close FAILED ** \r\n");
    }
}

/*****
*****//**
* @} (end addtogroup r_gpt_ep)
*****
*****/

```

Code Block 7 bgk_ra6e2_baremetal/src/gpt_timer.c

```

/*****
*****
* File Name      : gpt_timer.h
* Description    : Contains Macros and function declarations.

*****
*****/
/*****
*****
* Copyright (c) 2020 - 2024 Renesas Electronics Corporation and/or its affiliates
*
* SPDX-License-Identifier: BSD-3-Clause
*****
*****/
#ifndef GPT_TIMER_H_
#define GPT_TIMER_H_

/* Macros definitions */
#define GPT_MAX_PERCENT      (100U)          /* Max Duty Cycle percentage */
#define BUF_SIZE             (16U)           /* Size of buffer for RTT input data */
#define PERIODIC_MODE_TIMER  (1U)           /* To perform GPT Timer in Periodic
mode */
#define PWM_MODE_TIMER       (2U)           /* To perform GPT Timer in PWM mode */
#define ONE_SHOT_MODE_TIMER  (3U)           /* To perform GPT Timer in ONE-SHOT
mode */
#define INITIAL_VALUE        ('\0')
#define TIMER_UNITS_MILLISECONDS (1000U)    /* timer unit in millisecond */
#define CLOCK_TYPE_SPECIFIER (1ULL)         /* type specifier */

/* GPT Timer Pin for boards */
#define TIMER_PIN             (GPT_IO_PIN_GTIOCB)

#if defined (BOARD_RA2A1_EK) || defined (BOARD_RA4W1_EK) || defined (BOARD_RA4T1_MCK) ||
defined (BOARD_RA4E2_EK)
#define GPT_MAX_PERIOD_COUNT  (0xFFFF)      /* Max Period Count for 16-bit Timer*/
#else
#define GPT_MAX_PERIOD_COUNT  (0xFFFFFFFF)   /* Max Period Count for 32-bit Timer*/
#endif

#define PERIODIC_MODE         (1U)           /* To check status of GPT Timer in
Periodic mode */
#define PWM_MODE              (2U)           /* To check status of GPT Timer in PWM
mode */
#define ONE_SHOT_MODE         (3U)           /* To check status of GPT Timer in ONE-
SHOT mode */

#define EP_INFO               "\r\nThe project initializes GPT module in Periodic, PWM or One-shot
mode based on user input " \
    "from the displayed menu options." \
    "\r\nIn periodic mode, user can enter the time period within the permitted
ranges to change " \
    "the frequency of the user LED." \
    "\r\nIn PWM mode, user can enter the duty cycle within the specified range to
adjust the " \
    "intensity of the user LED." \
    "\r\nIn ONE SHOT mode, Output will be displayed on JlinkRTTViewer when timer
expires.\r\n "

/* Function declaration */
fsp_err_t init_gpt_timer(timer_ctrl_t * const p_timer_ctl, timer_cfg_t const * const
p_timer_cfg);
fsp_err_t start_gpt_timer (timer_ctrl_t * const p_timer_ctl);
fsp_err_t set_timer_duty_cycle(uint8_t duty_cycle_percent ,timer_ctrl_t * const
p_timer_ctl);
uint32_t process_input_data(void);
void deinit_gpt_timer(timer_ctrl_t * const p_timer_ctl);

```

```
void print_timer_menu(void);  
fsp_err_t set_timer_Period_and_Dutycycle(uint32_t period_counts ,uint8_t  
duty_cycle_percent, timer_ctrl_t * const p_timer_ctl);  
  
#endif /* GPT_TIMER_H_ */
```

Code Block 8 bgk_ra6e2_baremetal/src/gpt_timer.h

Next, edit the **main_application.c** file as the following.

```

#include <stdio.h>
#include "common_utils.h"
#include "main_application.h"
+ #include "gpt_timer.h"
// Uncomment the desired debug level
#include "log_disabled.h"
// #include "log_error.h"
// #include "log_warning.h"
// #include "log_info.h"
// #include "log_debug.h"

+ #ifdef ENABLE_PWM_LED1
+ void enable_Led1_PWM(void)
+ {
+     fsp_err_t err = FSP_SUCCESS;
+     uint32_t gpt_desired_duty_cycle_percent = RESET_VALUE;
+     uint32_t gpt_desired_period_ms = RESET_VALUE;
+     uint64_t period_counts = RESET_VALUE;
+     uint32_t pclk_freq_hz = RESET_VALUE;
+     gpt_desired_duty_cycle_percent = LED1_DEFAULT_DUTY_CYCLE ; // edit here to change
duty cycle
+     log_debug( "LED1:Default Period:%d ms   Default Duty Cycle:%d \r\n",
((LED1_DEFAULT_PERIOD* 1000) /SET_PERIOD_1_SECS),LED1_DEFAULT_DUTY_CYCLE);

+     /* Validate Duty cycle percentage */
+     if (GPT_MAX_PERCENT < gpt_desired_duty_cycle_percent)
+     {
+         log_error ("\r\n ** LED1:INVALID INPUT, DESIRED DUTY CYCLE IS OUT OF RANGE. **
\r\n");
+     }
+     else
+     {
+         /* we got valid input, Initialize PWM timer */
+         err = init_gpt_timer(&g_timer_pwm_led1_ctrl, &g_timer_pwm_led1_cfg);
+         if(FSP_SUCCESS != err)
+         {
+             log_error("*** LED1:GPT TIMER INIT FAILED ** \r\n");
+         }
+         log_debug("LED1:Opened Timer in PWM Mode\r\n");

+         /* Start PWM Timer*/
+         err = start_gpt_timer(&g_timer_pwm_led1_ctrl);
+         if(FSP_SUCCESS != err)
+         {
+             log_error("*** LED1:GPT TIMER START FAILED ** \r\n");
+             /*Close PWM Timer instance */
+             deinit_gpt_timer(&g_timer_pwm_led1_ctrl);
+         }
+         log_debug("LED1:Started Timer in PWM Mode\r\n");

+         /* Set DutyCycle and period of PWM timer */
+         err =
set_timer_Period_and_Dutycycle(LED1_DEFAULT_PERIOD,gpt_desired_duty_cycle_percent,&g_tim
er_pwm_led1_ctrl);
+         if(FSP_SUCCESS != err)
+         {
+             /* GPT Timer DutyCycleSet Failure message */
+             log_error ("\r\n ** LED1:Timer Period and DutyCycle SET FAILED **
\r\n");
+             /*Close PWM Timer instance */
+             deinit_gpt_timer(&set_timer_Period_and_Dutycycle);
+         }
+     }
+ }
+}

```



```

+ #endif

+ #ifdef ENABLE_PWM_LED2
+ void enable_Led2_PWM(void)
+ {
+     fsp_err_t err = FSP_SUCCESS;
+     uint32_t gpt_desired_duty_cycle_percent = RESET_VALUE;
+     uint32_t gpt_desired_period_ms = RESET_VALUE;
+     uint64_t period_counts = RESET_VALUE;
+     uint32_t pclk_freq_hz = RESET_VALUE;
+     gpt_desired_duty_cycle_percent = LED2_DEFAULT_DUTY_CYCLE ; // edit here to change
duty cycle
+     log_debug( "LED2:Default Period:%d ms   Default Duty Cycle:%d \r\n",
((LED2_DEFAULT_PERIOD* 1000) /SET_PERIOD_1_SECS),LED2_DEFAULT_DUTY_CYCLE);
+
+     /* Validate Duty cycle percentage */
+     if (GPT_MAX_PERCENT < gpt_desired_duty_cycle_percent)
+     {
+         log_error ("\r\n ** LED2:INVALID INPUT, DESIRED DUTY CYCLE IS OUT OF RANGE. **
\r\n");
+     }
+     else
+     {
+         /* we got valid input, Initialize PWM timer */
+         err = init_gpt_timer(&g_timer_pwm_led2_ctrl, &g_timer_pwm_led2_cfg);
+         if(FSP_SUCCESS != err)
+         {
+             log_error("** LED2:GPT TIMER INIT FAILED ** \r\n");
+         }
+         log_debug("LED2:Opened Timer in PWM Mode\r\n");
+
+         /* Start PWM Timer*/
+         err = start_gpt_timer(&g_timer_pwm_led2_ctrl);
+         if(FSP_SUCCESS != err)
+         {
+             log_error("** LED2:GPT TIMER START FAILED ** \r\n");
+             /*Close PWM Timer instance */
+             deinit_gpt_timer(&g_timer_pwm_led2_ctrl);
+         }
+         log_debug("Started Timer in PWM Mode\r\n");
+
+         err =
set_timer_Period_and_Dutycycle(LED2_DEFAULT_PERIOD,gpt_desired_duty_cycle_percent,&g_tim
er_pwm_led2_ctrl);
+         if(FSP_SUCCESS != err)
+         {
+             /* GPT Timer DutyCycleSet Failure message */
+             log_error ("\r\n ** LED2:Timer Period and Dutycycle SET FAILED ** \r\n");
+             /*Close PWM Timer instance */
+             deinit_gpt_timer(&set_timer_Period_and_Dutycycle);
+         }
+     }
+ }
+ #endif

void main_application(void) {

// Start of autogenerated code

+ #if defined(ENABLE_LED1) && defined(ENABLE_PWM_LED1)
+     enable_Led1_PWM();
+ #endif

+ #if defined(ENABLE_LED2) && defined(ENABLE_PWM_LED2)
+     enable_Led2_PWM();
+ #endif

```

```

    while(true)
    {
        // do nothing
    }
    // End of autogenerated code
}

```

Code Block 9 main_application.c

Updated main_application.h file.

```

#ifndef __MAIN_APPLICATION_H
#define __MAIN_APPLICATION_H

#include "common_utils.h"
+ #define SET_PERIOD_1_SECS      0x10000 // 1 second period
+ #define SET_PERIOD_500_MSECS  0x8000  // 500 ms period
+ #define SET_PERIOD_250_MSECS  0x4000  // 250 ms period
+ #define SET_PERIOD_125_MSECS  0x2000  // 125 ms period
+ #define SET_PERIOD_75_MSECS   0x1000  // 75 ms period
+ #define SET_PERIOD_37_MSECS   0x800   // 37.5 ms period
+ #define SET_PERIOD_16_MSECS   0x400   // 16 ms period
+ #define SET_PERIOD_8_MSECS    0x200   // 8 ms period
+ #define SET_PERIOD_4_MSECS    0x100   // 4 ms period
+ #define SET_PERIOD_2_MSECS    0x80    // 2 ms period
+ #define SET_PERIOD_1_MSECS    0x40    // 1 ms period

+ #define ENABLE_LED1           // Enable or disable LED1
+ #define ENABLE_LED2           // Enable or disable LED2

+ #ifdef ENABLE_LED1
+ #define ENABLE_PWM_LED1
+ #endif

+ #ifdef ENABLE_LED2
+ #define ENABLE_PWM_LED2
+ #endif

+ #ifdef ENABLE_PWM_LED1
+ #define LED1_DEFAULT_DUTY_CYCLE 50 // 50 %
+ #define LED1_DEFAULT_PERIOD    SET_PERIOD_1_SECS
+ #endif
+ #ifdef ENABLE_PWM_LED2 // 50 %
+ #define LED2_DEFAULT_PERIOD    SET_PERIOD_1_SECS
+ #define LED2_DEFAULT_DUTY_CYCLE 50
+ #endif
/* Function declaration */
void main_application(void);

#endif /* __MAIN_APPLICATION_H */

```

Code Block 10 main_application.h


The user can enable or disable the PWM code for individual LEDs using the macros provided below. To use this feature, the user must make the following changes in **main_application.h**:

Enable the Macro:

```
#define ENABLE_LED1 // Enable or disable LED1
#define ENABLE_LED2 // Enable or disable LED2
```

Expected Output RTT Logs:

Check the following logs for the expected behavior and also observe LEDs on Board to co-relate with the feature.



```
J-Link RTT Viewer V8.10h
File Terminals Input Logging Help
All Terminals Terminal 0
00> DEBUG:../src/main_application.c LED1:Default Period:1000 ms Default Duty Cycle:50
00>
00> DEBUG:../src/main_application.c LED1:Opened Timer in PWM Mode
00>
00> DEBUG:../src/main_application.c LED1:Started Timer in PWM Mode
00>
00> DEBUG:../src/main_application.c LED2:Default Period:1000 ms Default Duty Cycle:50
00>
00> DEBUG:../src/main_application.c LED2: Opened Timer in PWM Mode
00>
00> DEBUG:../src/main_application.c LED2:Started Timer in PWM Mode
00>
```

10.3.2.4 Adjust the LED Period using Macro

By default, both LEDs are configured with a 1s period. However, the blink interval can be modified by changing the macro values in **main_application.h**:

- For LED1: #define LED1_DEFAULT_PERIOD
- For LED2: #define LED2_DEFAULT_PERIOD

```
#define SET_PERIOD_1_SECS      0x10000 // 1 second period
#define SET_PERIOD_500_MSECS  0x8000  // 500 ms period
#define SET_PERIOD_250_MSECS  0x4000  // 250 ms period
#define SET_PERIOD_125_MSECS  0x2000  // 125 ms period
#define SET_PERIOD_75_MSECS   0x1000  // 75 ms period
#define SET_PERIOD_37_MSECS   0x800   // 37.5 ms period
#define SET_PERIOD_16_MSECS   0x400   // 16 ms period
#define SET_PERIOD_8_MSECS    0x200   // 8 ms period
#define SET_PERIOD_4_MSECS    0x100   // 4 ms period
#define SET_PERIOD_2_MSECS    0x80    // 2 ms period
#define SET_PERIOD_1_MSECS    0x40    // 1 ms period
```

Any of the previous defined values can be selected and set with LED periods like this:

```
#define LED1_DEFAULT_PERIOD    SET_PERIOD_1_SECS
#define LED2_DEFAULT_PERIOD    SET_PERIOD_1_SECS
```

These macros can be adjusted to achieve the required LED blink intervals.

Expected Output RTT Logs:

Check the following logs for the expected behavior and also observe LEDs on board to co-relate with the feature.

```

J-Link RTT Viewer V8.10h
File Terminals Input Logging Help
All Terminals Terminal 0
00> DEBUG:../src/main_application.c LED1:Default Period:1000 ms   Default Duty Cycle:50
00>
00> DEBUG:../src/main_application.c LED1:Opened Timer in PWM Mode
00>
00> DEBUG:../src/main_application.c LED1:Started Timer in PWM Mode
00>
00> DEBUG:../src/main_application.c LED2:Default Period:1000 ms   Default Duty Cycle:50
00>
00> DEBUG:../src/main_application.c LED2: Opened Timer in PWM Mode
00>
00> DEBUG:../src/main_application.c LED2:Started Timer in PWM Mode
00>

```

10.3.2.5 Adjust the LED ON/OFF duration using macro

Users can adjust the On/OFF duration (that is the duty cycle) using the predefined macro in **main_application.h** file.

These macros as by default set a value of 50% for a duty cycle but they can be set as per required from the range of 1 to 100%.

- `#define LED1_DEFAULT_DUTY_CYCLE 50 // duty cycle macro for LED 1`
- `#define LED2_DEFAULT_DUTY_CYCLE 50 // duty cycle macro for LED 2`

The LEDs are configured with a 1-second period, allowing to be set the duty cycle from 1% to 100%.

- A 1% duty cycle means the LED will be ON for 10ms and OFF for 990ms.
- A 100% duty cycle means the LED stays ON continuously.

This way, users can adjust the ON/OFF duration anywhere between 10ms (minimum ON time) and 990ms (maximum OFF-time), depending on the required brightness or behavior.

Note: To control the LED brightness using PWM, the PWM period should be reduced to a level where the LED's on/off toggling is not visually perceptible. This allows for smooth brightness control through the duty cycle.

In this example, set the PWM period to 37ms by using the macro `SET_PERIOD_37_MSECS` for `LED1_DEFAULT_PERIOD`, and then vary the duty cycle between 1% to 100% to adjust brightness.

Example:

Maximum brightness


```
#define LED1_DEFAULT_DUTY_CYCLE 100 // 100 %
#define LED1_DEFAULT_PERIOD SET_PERIOD_37_MSECS
```

Minimum brightness

```
#define LED1_DEFAULT_DUTY_CYCLE 1 // 1 %
#define LED1_DEFAULT_PERIOD SET_PERIOD_37_MSECS
```

Expected Output RTT Logs:

Check the following logs for the expected behavior and also observe LEDs on the board to correlate with the feature.



The screenshot shows the J-Link RTT Viewer V8.10h interface. The 'Terminal 0' tab is active, displaying the following RTT logs:

```
00> DEBUG:../src/main_application.c LED1:Default Period:1000 ms   Default Duty Cycle:50
00>
00> DEBUG:../src/main_application.c LED1:Opened Timer in PWM Mode
00>
00> DEBUG:../src/main_application.c LED1:Started Timer in PWM Mode
00>
00> DEBUG:../src/main_application.c LED2:Default Period:1000 ms   Default Duty Cycle:50
00>
00> DEBUG:../src/main_application.c LED2: Opened Timer in PWM Mode
00>
00> DEBUG:../src/main_application.c LED2:Started Timer in PWM Mode
00>
```

10.3.3 Customize Sensor Data to AWS Cloud application

As a first step, the user must create a project in the QuickConnect Studio by selecting the appropriate MCU kit (for example, BGK-RA6E2), sensor (for example, HS4001 Temperature / Humidity), connectivity module (for example, DA16600 Wi-Fi) and Sensor Data to AWS Cloud (MQTT onchip) application

10.3.3.1 Exercise 1: Change Sensor Units (C to F or F to C)

This exercise is to update the temperature units between C and F. The default unit for temperature on QCS is Celsius. This exercise publishes temperature data into AWS in Fahrenheit.

Files to be modified:

- `\\src\\main_thread_entry.c`

Modifications:

Modify the following code in the `main_thread_entry()` function to convert the sensor data if the parameter is temperature only.

```

void main_thread_entry(void *pvParameters) {
FSP_PARAMETER_NOT_USED (pvParameters);
uint8_t timeout = 10;
while (1) {
    sm_handle sensor_handle;
    uint8_t sensor_count = 0;
    .
    .
    .
    if (pdTRUE == xQueueReceive(g_sensor_queue,
&sensor_data, PUBLISHING_INTERVAL_MS)) {
        // Store the received data into the right slot
        for (index = 0; index < NUM_SENSORS; index++) {
            if (0 == sensor_slots[index].handle.value ||
sensor_slots[index].handle.value ==
sensor_data.handle.value) {
                // Found a slot
                sensor_slots[index].handle.value =
sensor_data.handle.value;
-                sensor_slots[index].data =
+                sensor_data.data;
+                sensor_slots[index].data = (TEMPERATURE
==
sm_get_sensor_type_by_handle(sensor_slots[index].handle))
? \
+
+ ((sensor_data.data * 9) / 5) + 3200 : \
+
sensor_data.data;
                num_sensors = index + 1;
                break;
            }
        }
    }
    .
    .
}
}

```

Code Block 11 main_thread_entry.c changes

Expected output:



AWS IoT MQTT test client

» <user_device>/feeds/temperature

March 23, 2025, 16:26:51 (UTC+0530)

93.06

» Properties

» <user_device>/feeds/humidity

March 23, 2025, 16:26:51 (UTC+0530)

57.13

» Properties

RTT Viewer

```
00> INFO:../src/sensor/hs4001_sensor.c Sensor channel 0 open success
00> INFO:../src/sensor/hs4001_sensor.c Sensor channel 1 open success
00> DEBUG:../src/sensor/hs4001_sensor.c Sensor read channel 0
00> INFO:../src/main_thread_entry.c Starting Wi-Fi connection...
00> INFO:../src/main_thread_entry.c Wi-Fi connection successful!
00> INFO:../src/main_thread_entry.c MQTT setup successful!
00> INFO:../src/main_thread_entry.c MQTT Subscribe to user_device/feeds/led
00> DEBUG:../src/sensor/hs4001_sensor.c Sensor read channel 0
00> DEBUG:../src/sensor/hs4001_sensor.c Sensor read channel 1
00> DEBUG:../src/main_thread_entry.c Topic: <user_device>/feeds/humidity data: 57.13
00> DEBUG:../src/main_thread_entry.c Topic: <user_device>/feeds/temperature data: 93.06
```

10.3.3.2 Change Frequency of Sensor Update

This exercise is to change the sensor update time from 10 seconds to one minute. The default time for the sensor update on QCS is 30 seconds. This exercise changes the sensor data publish interval the into AWS cloud.

Files to be modified:

- `src/main_thread_entry.c`

Modifications: Define the following mentioned enum in the User Macros section and assign the variable to PUBLISHING_INTERVAL_M:

```

/*****
*****
User Macros
*****
*****/

+// Define sensor update periods (in milliseconds)
+typedef enum {
+    PERIOD_10SEC = 10000,
+    PERIOD_20SEC = 10000,
+    PERIOD_30SEC = 30000,
+    PERIOD_45SEC = 45000,
+    PERIOD_1MIN  = 60000
+} SensorUpdatePeriod_t;
+SensorUpdatePeriod_t sensor_update_period = PERIOD_30SEC;
// Default setting

#define QUEUE_RECEIVE_TIMEOUT (100) //
    this is the interval we also receive MQTT messages
-#define PUBLISHING_INTERVAL_MS (30000)
+#define PUBLISHING_INTERVAL_MS
    sensor_update_period

```

Code Block 12 main_thread_entry.c changes

10.3.3.3 Modify the MQTT Topic Name as <sensor name>/<parameter>

This exercise is to modify the **aws mqtt** publish topic name includes sensor name. The default string in the topic name in QCS is feeds. This is modified by the sensor name (for example, hs4001_sensor).

Files to be modified:

- `\src\main_thread_entry.c`

Modifications: Define the following macro mentioned in User Macros section and change the mentioned code in `main_thread_entry()` function:

```

/*****
*****
User Macros
*****
*****/

+// create automatic headers for each sensor
#define DEFINE_SENSOR_DRIVER(DRIVER) char sensor_name[] =
    #DRIVER;
#include "sm_define_sensors.inc"

/*****
*****
User function implementations
*****
*****/

void main_thread_entry(void *pvParameters) {
    FSP_PARAMETER_NOT_USED (pvParameters);
    uint8_t timeout = 10;
    while (1) {
        sm_handle sensor_handle;
        uint8_t sensor_count = 0;
        .
        .
        .
        char pub_message[WIDTH_64];
        char pub_topic[WIDTH_64];
        snprintf(pub_topic, WIDTH_64,
-       IO_USERNAME"/feeds/%s",\
+       snprintf(pub_topic, WIDTH_64,
+       IO_USERNAME"/%s/%s",\
+       sensor_name,\

        sm_get_sensor_path_by_handle(sensor_slots[index2].handle)
        ,\
        );
        .
        .
    }
}

```

Code Block 13 main_thread_entry.c changes

Expected output:

-  AWS IoT MQTT test client
 - » <user_device>/hs4001_sensor/temperature March 23, 2025, 16:26:51 (UTC+0530)
 - 34.08
 - » Properties
 - » <user_device>/hs4001_sensor/humidity March 23, 2025, 16:26:51 (UTC+0530)
 - 52.86
 - » Properties

RTT Viewer

```
00> INFO:../src/sensor/hs4001_sensor.c Sensor channel 0 open success
00> INFO:../src/sensor/hs4001_sensor.c Sensor channel 1 open success
00> DEBUG:../src/sensor/hs4001_sensor.c Sensor read channel 0
00> INFO:../src/main_thread_entry.c Starting Wi-Fi connection...
00> INFO:../src/main_thread_entry.c Wi-Fi connection successful!
00> INFO:../src/main_thread_entry.c MQTT setup successful!
00> INFO:../src/main_thread_entry.c MQTT Subscribe to <user_device>/feeds/led
00> DEBUG:../src/sensor/hs4001_sensor.c Sensor read channel 0
00> DEBUG:../src/sensor/hs4001_sensor.c Sensor read channel 1
00> DEBUG:../src/main_thread_entry.c Topic: <user_device>/hs4001_sensor/humidity data: 52.86
00> DEBUG:../src/main_thread_entry.c Topic: <user_device>/hs4001_sensor/temperature data: 34.08
```

10.3.3.4 Identify Min, Max, and Averaging of Sensor Values (Send Only when Absolute Change Observed)

This exercise is to calculate the statistics (min, max average, and absolute change) of a sensor parameter and publish the statistics.

Files to be modified:

\\src\\main_thread_entry.c

Modifications: Define the following mentioned enum in the User Macro section, add the variables to the User Global Variables section, and assign the variable to PUBLISHING_INTERVAL_MS as mentioned:

```

/*****
*****

User Macros
*****
*****/
+// Define statistics offsets
+typedef enum {
+    VALUE = 0,
+    MIN,
+    MAX,
+    AVG,
+    ABS,
+    COUNT,
+    STATS_MAX_PARAMS
+}SensorStatsParams_t;

/*****
*****

User global variables
*****
*****/

+static const char* stats_names[] = {"value", "minimum",
    "maximum", "average", "absolute_change"};
+#define STATS_NAMES_COUNT (sizeof(stats_names) /
    sizeof(stats_names[0]))
+static int32_t stats_values[NUM_SENSORS][STATS_MAX_PARAMS];

/*****
*****

User function prototype declarations
*****
*****/

+void update_sensor_stats(int32_t new_value, uint32_t
    senor_index);

/*****
*****

User function implementations
*****
*****/

+// Function to update sensor statistics
+void update_sensor_stats(int32_t new_value, uint32_t
    senor_index) {
+    if(0 == stats_values[senor_index][COUNT])
+    {
+        stats_values[senor_index][MIN]      = new_value;
+        stats_values[senor_index][MAX]      = new_value;
+        stats_values[senor_index][AVG]      = new_value;
+        stats_values[senor_index][VALUE]    = new_value;
+        stats_values[senor_index][ABS]      = 0;
+        stats_values[senor_index][COUNT]++;
+        return;
+    }
+    if (new_value < stats_values[senor_index][MIN]) {
+        stats_values[senor_index][MIN] = new_value;
+    }
+    if (new_value > stats_values[senor_index][MAX]) {
+        stats_values[senor_index][MAX] = new_value;
+    }
+    stats_values[senor_index][AVG] =
    (stats_values[senor_index][AVG] *

```

```

        stats_values[senor_index][COUNT] + new_value) /
        (stats_values[senor_index][COUNT] + 1);
+       stats_values[senor_index][COUNT]++;

+       stats_values[senor_index][ABS] = (new_value >
stats_values[senor_index][VALUE]) ? \
+       (new_value -
stats_values[senor_index][VALUE]) : \
+       (stats_values[senor_index][VALUE] - new_value);
+       stats_values[senor_index][VALUE] = new_value;
+   }
+

void main_thread_entry(void *pvParameters) {
FSP_PARAMETER_NOT_USED (pvParameters);
uint8_t timeout = 10;
while (1) {
    sm_handle sensor_handle;
    uint8_t sensor_count = 0;
    .
    .
    .
    .
        char pub_message[WIDTH_64];
        char pub_topic[WIDTH_64];
        snprintf(pub_topic, WIDTH_64,
-       IO_USERNAME"/feeds/%s", \
-
    sm_get_sensor_path_by_handle(sensor_slots[index2].handle)
    \
-       );
-
-       snprintf((char*)pub_message, WIDTH_64,
-       "%ld.%02ld", \
-           sensor_slots[index2].data/100, \
-           sensor_slots[index2].data%100);
+
    update_sensor_stats(sensor_slots[index2].data, index2);
+       for(SensorStatsParams_t stats_index = 0;
stats_index < STATS_NAMES_COUNT; stats_index++){
+       snprintf(pub_topic, WIDTH_64,
+       IO_USERNAME"/feeds/%s/%s", \
+
    sm_get_sensor_path_by_handle(sensor_slots[index2].handle)
    , \
+       stats_names[stats_index]\
+       );
+       snprintf((char*)pub_message, WIDTH_64,
+       "%ld.%02ld", \
+
+       stats_values[index2][stats_index]/100, \
+
+       stats_values[index2][stats_index]%100);
        mqtt_onchip_da16xxx_pub_info_t pubData;
        pubData.qos = MQTT_ONCHIP_DA16XXX_QOS_0;
        pubData.p_topic_name = pub_topic;
        pubData.topic_name_Length =
        (uint16_t)strlen(pub_topic);
        pubData.p_payload = pub_message;
        pubData.payload_length =
        strlen(pubData.p_payload);
        log_debug("Topic: %s data:
        %s", pub_topic, pub_message);
        /* Publish data to the MQTT Broker */

```

```

        if (FSP_SUCCESS !=
RM_MQTT_DA16XXX_Publish(&g_rm_mqtt_onchip_da16xxx_instanc
e, &pubData)) {
            log_error("MQTT publish failed");
            utils_halt_func();
        }
        // The following delay is very important
as RM_MQTT_DA16XXX_Publish do not send the data right
away
        // and without a delay further publishes
will silently fail
-         vTaskDelay(100);
+         vTaskDelay(200);
+     }
    .
    }
}

```

Code Block 14 main_thread_entry.c changes

Expected output:

AWS IoT MQTT test client	
» <user_device>/feeds/temperature/absolute_change	April 04, 2025, 17:46:12 (UTC+0530)
0.04	
» Properties	
» <user_device>/feeds/temperature/average	April 04, 2025, 17:46:11 (UTC+0530)
34.32	
» Properties	
» <user_device>/feeds/temperature/maximum	April 04, 2025, 17:46:11 (UTC+0530)
34.37	
» Properties	
» <user_device>/feeds/temperature/minimum	April 04, 2025, 17:46:11 (UTC+0530)
34.31	
» Properties	
» <user_device>/feeds/temperature/value	April 04, 2025, 17:46:10 (UTC+0530)
34.33	
» Properties	

RTT Viewer

```


00> INFO:../src/sensor/hs4001_sensor.c Sensor channel 0 open success
00> INFO:../src/sensor/hs4001_sensor.c Sensor channel 1 open success
00> DEBUG:../src/sensor/hs4001_sensor.c Sensor read channel 0
00> INFO:../src/main_thread_entry.c Starting Wi-Fi connection...
00> INFO:../src/main_thread_entry.c Wi-Fi connection successful!
00> INFO:../src/main_thread_entry.c MQTT setup successful!
00> INFO:../src/main_thread_entry.c MQTT Subscribe to user_device/feeds/led
00> DEBUG:../src/sensor/hs4001_sensor.c Sensor read channel 0
00> DEBUG:../src/sensor/hs4001_sensor.c Sensor read channel 1
00> DEBUG:../src/main_thread_entry.c Topic:<user_device>/feeds/humidity/value data: 56.86
00> DEBUG:../src/main_thread_entry.c Topic:<user_device>/feeds/humidity/minimum data: 56.86
00> DEBUG:../src/main_thread_entry.c Topic:<user_device>/feeds/humidity/maximum data: 57.35
00> DEBUG:../src/main_thread_entry.c Topic:<user_device>/feeds/humidity/average data: 57.17
00> DEBUG:../src/main_thread_entry.c Topic:<user_device>/feeds/humidity/absolute_change data: 0.27
00> DEBUG:../src/main_thread_entry.c Topic:<user_device>/feeds/temperature/value data: 34.33
00> DEBUG:../src/main_thread_entry.c Topic:<user_device>/feeds/temperature/minimum data: 34.31
00> DEBUG:../src/main_thread_entry.c Topic:<user_device>/feeds/temperature/maximum data: 34.33
00> DEBUG:../src/main_thread_entry.c Topic:<user_device>/feeds/temperature/average data: 34.32
00> DEBUG:../src/main_thread_entry.c Topic:<user_device>/feeds/temperature/absolute_change data: 0.02

```

10.3.3.5 Add Widget (Gauge / Box)

QCS can only publish the sensor data to the AWS cloud. It does not display like a widget. This can be implemented by installing a third-Party dashboard like AWS cloud watch, Grafana, Node-RED, or AWS Amplify with IoT Dashboard (Custom UI). For ease of exercise, use a direct third-party executable [MQTT explorer](#) to show the sensor value in widget and graph. Follow these steps to configure MQTT explorer.

1. Open MQTT Explorer
 - a. Launch the .exe file and click + to add a new connection.



2. Set the Connection Settings and input the basic information:
 - a. Name: AWS IoT
 - b. Protocol: mqtts:// (use secure MQTT over TLS)

- c. Host: Enter the AWS IoT endpoint, for example:
a3k7example8-ats.iot.us-west-2.amazonaws.com
- d. Port: 8883 (TLS secured MQTT)

- 3. Enable TLS/SSL
 - a. Toggle Enable TLS




- b. Click on **Advanced**.




- c. Click on **Certificates**.




- 4. Upload the certificate files:
 - a. Client Certificate: The device-certificate.pem.crt
 - b. Client Key: The private.pem.key
 - c. CA Certificate: Amazon root CA (for example, AmazonRootCA1.pem)
[Download CA Cert here](#)




5. Client ID
 - a. Optional, but recommended: set a unique client ID, for example, **mqtt-explorer-client**.
6. Click Back and Enter topic
 - a. **Retain** or **Clean Session** can be enabled if required.
 - b. Add Topic name (for example, <user_device>/feeds/temperature)
 - c. Go back and click **Save**.



7. Connect!
 - a. Click Connect.
 - b. If everything is set up right, the MQTT topics appear and start to populate. (Wait for updated interval period that the user has chosen.)
8. MQTT Explorer
 - a. Expand the Username > feeds, to see the real-time value.



- b. Click on **History** to see the history and add charts to observe the real-time values graphically.



Note: <user_device> is replaced by IO_USERNAME from the src/user.h in all output logs.

10.3.4 Customize Sensor Data to BLE application

As a first step, the user must create a project in the QuickConnect Studio by selecting the appropriate MCU kit (BGK-RA6E2), sensor (HS4001 Temperature / Humidity), connectivity module (DA14531 Bluetooth) and Sensor Data over BLE FreeRTOS application.

10.3.4.1 Change Temperature Sensor Units (C to F and F to C)

This exercise is to update the temperature units between Celsius (C) and Fahrenheit (F). The default unit for temperature on QCS is Celsius. This exercise will convert the value to Fahrenheit and display it on the QC sandbox mobile application. Since the QC sandbox application needs to display the correctly converted data as well as the correct unit, Both changes need to be made to achieve the correct result.

Complete the following steps:

1. Generate the Sensor Data over BLE application on QCS using BGK-RA6E2, HS4001 Sensor, and DA14531 BLE module for FreeRTOS.
2. Modify the **ble_app.c** and **gui_cfg.json** files as mentioned above.
3. Rebuild the project by pressing the **Build QCStudio Project** option in QCS.
4. Download the *.srec file from the **Debug/** path and flash the BGK-RA6E2 board.
5. Pair the QC Sandbox mobile application with the board and verify the data.

Files modified:

- / src / qe_gen / ble / ble_app.c
- / gui_cfg.json

Modifications:

ble_app.c: The ble_app_run() function performs the BLE stack execution and obtains the data from FreeRTOS queue whenever it is available. This data is pushed upon receiving the request from mobile application. This function must be modified to convert the temperature value to Fahrenheit. Because this function is generic and is called for both temperature and humidity, the conversion should only take place in the case of temperature. The modification is made to convert only temperature data. (The complete function is not included below, the + symbol indicates you must add those lines inside the original function for the **ble_app.c** file).

```
void ble_app_run(void) {
    /* Process BLE Event */
    R_BLE_Execute();
    .
    .
    .
    if (pdTRUE == xQueueReceive(g_sensor_queue, &sensor_data, 0)) {
        uint32_t index = 2;
        while (index < (uint32_t)sm_get_total_sensor_count()+2) {
            if (qc_sv_req_handlers[index].sensor_handler.value ==
sensor_data.handle.value) {
                sm_scaling scaling;
                sm_get_sensor_scaling(sensor_data.handle, &scaling);
                float floatData = ((float)sensor_data.data *
(float)scaling.multiplier)/((float)scaling.divider + (float)scaling.offset;
+
                if
(sm_get_sensor_type_by_handle(qc_sv_req_handlers[index].sensor_handler) == TEMPERATURE)
+
                {
+
                    floatData = ((floatData * 18) / 10) + 32;
+
                }

                sensor_data_array[index-2] = floatData;
                break;
            }
            index++;
        }
    }
}
```

Code Block 15 ble_app.c

gui_cfg.json: Parameter units for TEMPERATURE indicates the unit that should be shown against the value in mobile application. Default value for this field is C indicating the value is in Celsius, which should be modified to F because the application is pushing temperature data in Fahrenheit.

```

{
  "gui":
  {
    "id": "0000",
    "title": "US000 QC Example",
    "version": "0.0.1",
    "tab":
    [
      {
        "id": "0001",
        "name": "LED",
        "toggle":
        {
          "id": "0100",
          "type": "uint8_t",
          "name": "LED 1",
          "default": 0
        }
      },
      {
        "id": "0002",
        "name": "HS4001",
        "parameters":
        {
          "id": "0200",
          "type": "blob",
          "access": "r",
          "list":
          [
            {
              "id": "0201",
              "name": "TEMPERATURE",
              "units": "F",
              "type": "float",
              "access": "r",
              "auto_read": 1,
              "value": null
            },
            {
              "id": "0202",
              "name": "HUMIDITY",
              "units": "%",
              "type": "float",
              "access": "r",
              "auto_read": 1,
              "value": null
            }
          ]
        }
      }
    ]
  },
  {
    "id": "0003",
    "name": "About",
    "parameters":
    {
      "id": "0300",
      "type": "blob",
      "access": "r",
      "list":
      [
        {
          "id": "0301",
          "name": "Test Version",
          "type": "string",
          "access": "const",
          "value": null
        }
      ]
    }
  }
}

```




```
}  
}  
]  
}  
}  
]  
}  
}
```

Code Block 16 gui_cfg.json

Outcome for this exercise:

After flashing the updated application into BGK-RA6E2 board, open the QC Sandbox mobile application and navigate to HS4001 page. There the user can see the temperature value in Fahrenheit format and the updated unit as well.



10.3.4.2 Change Frequency of Sensor Value Update

This exercise involves updating the time interval at which data is read from the sensor. It adds a custom time interval value for sensor reads, which is reflected on the QC Sandbox mobile application. This update does not modify the interval at which the mobile application requests data from the board.

Complete the following steps:

1. Generate the Sensor Data over BLE application on QCS using BGK-RA6E2, HS4001 Sensor, and DA14531 BLE module for FreeRTOS.
2. Modify the **sensor_thread_entry.c** files as mentioned above.
3. Rebuild the project by pressing the **Build QCSstudio Project** option in QCS.
4. Download the *.srec file from **Debug/** path and flash the BGK-RA6E2 board.
5. Pair the QC Sandbox mobile application with the board and verify the data.

Files modified:

- /src/sensor_thread_entry.c

Modification:

Sensor thread is responsible for the sensor related activities inside this application. That is initializing the sensor manager and reading and parsing the sensor data. To introduce the custom time interval for a sensor data read, create a static function **static void sensor_configure_interval(uint32_t interval)** that accepts the time interval value as parameter and configures the same as a sensor acquisition interval.

```
static void sensor_configure_interval(uint32_t interval)
{
    sm_handle handle;
    uint16_t index;

    sm_get_sensor_handle(SENSOR_ANY_TYPE, &handle, &index);
    sm_set_sensor_attribute(handle, SM_ACQUISITION_INTERVAL, interval);
}
```

Code Block 17 sensor_thread_entry.c

After this is added, modify the existing **void sensor_thread_entry(void *pvParameters)** by calling the above function with the required time interval value. This way, the sensor manager can be configured with the time interval between sensor reads. Here the function is called with 6000, which means the sensor acquisition interval is 6 seconds. The tested maximum supported value is 8 seconds.

```
/* Sensor entry function */
/* pvParameters contains TaskHandle_t */
void sensor_thread_entry(void *pvParameters) {
    FSP_PARAMETER_NOT_USED (pvParameters);

    sensor_configure_interval(6000);

    /* TODO: add your own code here */
    sm_init();

    while (1) {
        sm_run();
    }
}
```

Code Block 18 sensor_thread_entry.c

Outcome for this exercise:

After flashing the .srec file, connect the board with QC Sandbox mobile application over BLE and navigate to the HS4001 page. There, the data update should be according to the configured time interval only. *Note:* The mobile application has separate update interval. The observation is linked with that parameter and, that is, if the sensor update interval is configured for a lesser value than mobile app update, the user does not see any visible change after this exercise.

10.3.4.3 Add Widget for Sensor Value Visualization (Gauges / Box)

This exercise is on adding extra widget on the mobile application for the sensor data visualization. Default configuration for the mobile application is box widget in which the sensor data will be displayed. Additional configuration must be performed on the application to make the gauge widget available on the mobile application.

Complete the following steps:

1. Generate the **Sensor Data over BLE** application on QCS using the BGK-RA6E2, HS4001 Sensor, and DA14531 BLE module for FreeRTOS.
2. Modify the **gui_cfg.json** file as previously mentioned.
3. Rebuild the project by pressing the **Build QCStudio Project** option in QCS.
4. Download the *.srec file from the **Debug/** path and flash the BGK-RA6E2 board.
5. Pair the QC Sandbox mobile application with the board and verify the data.

Files modified:

- / gui_cfg.json

Modifications:

```

{
  "gui": {
    "id": "0000",
    "title": "US000 QC Example",
    "version": "0.0.1",
    "tab": [
      {
        "id": "0001",
        "name": "LED",
        "toggle": {
          "id": "0100",
          "type": "uint8_t",
          "name": "LED 1",
          "default": 0
        }
      },
      {
        "id": "0002",
        "name": "HS4001",
        "parameters": {
          "id": "0200",
          "type": "blob",
          "access": "r",
          "list": [
            {
              "id": "0201",
              "name": "TEMPERATURE",
              "units": "C",
              "type": "float",
              "access": "r",
              "auto_read": 1,
              "value": null
            },
            {
              "id": "0202",
              "name": "HUMIDITY",
              "units": "%",
              "type": "float",
              "access": "r",
              "auto_read": 1,
              "value": null
            }
          ]
        },
        "gauge": [
          {
            "id": "0201",
            "name": "TEMPERATURE",
            "units": "C",
            "type": "float",
            "minimum": 0,
            "maximum": 100,
            "showinmax": true,
            "default": 0,
            "value": null
          },
          {
            "id": "0202",
            "name": "HUMIDITY",
            "units": "%",
            "type": "float",
            "minimum": 0,
            "maximum": 100,
            "showinmax": true,
            "default": 0,
            "value": null
          }
        ]
      }
    ]
  }
}


```

```
    }  
  ],  
  {  
    "id": "0003",  
    "name": "About",  
    "parameters": {  
      "id": "0300",  
      "type": "blob",  
      "access": "r",  
      "list": [  
        {  
          "id": "0301",  
          "name": "Test Version",  
          "type": "string",  
          "access": "const",  
          "value": null  
        }  
      ]  
    }  
  }  
]  
}
```

Code Block 19 gui_cfg.json

Outcome for this exercise:

After this change, the QC Sandbox mobile application should show gauge widget as well for the sensor data.



10.3.4.4 Update Frequency of Sensor Data Update on the BLE Mobile Application

This exercise is to update the time interval at which data is read by the QC Sandbox mobile application. This is independent of the time interval at which the sensor data is read by the firmware (discussed on REQ – 2); that is, this exercise defines the rate at which function **handle_read_data()** is invoked inside the application.

Complete the following steps:

1. Generate Sensor Data over BLE application on QCS using BGK-RA6E2, HS4001 Sensor and DA14531 BLE module for FreeRTOS.
2. Modify the **gui_cfg.json** file as mentioned above.
3. Rebuild the project by pressing the **Build QCStudio Project** option in QCS.
4. Download the ***.srec** file from Debug/ path and flash the BGK-RA6E2 board.
5. Pair QC Sandbox mobile application with the board and verify the data.

Files to be modified:

- **/gui_cfg.json**

Modifications:

The `auto_read` parameter in the **gui_cfg.json** file mentions the time interval (in seconds) at which the request comes from mobile application. Value of 1 (Default) in this field indicates for every one second, the request is made, and the sensor data is collected.


```

{
  "gui": {
    "id": "0000",
    "title": "US000 QC Example",
    "version": "0.0.1",
    "tab": [
      {
        "id": "0001",
        "name": "LED",
        "toggle": {
          "id": "0100",
          "type": "uint8_t",
          "name": "LED 1",
          "default": 0
        }
      },
      {
        "id": "0002",
        "name": "HS4001",
        "parameters": {
          "id": "0200",
          "type": "blob",
          "access": "r",
          "list": [
            {
              "id": "0201",
              "name": "TEMPERATURE",
              "units": "C",
              "type": "float",
              "access": "r",
              "auto_read": 5,
              "value": null
            },
            {
              "id": "0202",
              "name": "HUMIDITY",
              "units": "%",
              "type": "float",
              "access": "r",
              "auto_read": 5,
              "value": null
            }
          ]
        }
      },
      {
        "id": "0003",
        "name": "About",
        "parameters": {
          "id": "0300",
          "type": "blob",
          "access": "r",
          "list": [
            {
              "id": "0301",
              "name": "Test Version",
              "type": "string",
              "access": "const",
              "value": null
            }
          ]
        }
      }
    ]
  }
}


```

Code Block 20 gui_cfg.json

Here it is configured for a 5s interval and the mobile application is expected to send the read request for sensor data every 5s. After everything is done, the user should see the data update for every 5s inside the mobile application.

Outcome for this exercise:

After flashing the **.srec** file, connect the board with QC Sandbox mobile application over BLE and navigate to the HS4001 page. The user should see the data update according to the configured time interval only.



10.3.4.5 Send the Sensor Value Only if the Read Button Pressed on the BLE Mobile Application

This requirement is to disable the auto_read functionality of the QC Sandbox mobile application. The user is expected to initiate the read process from mobile application to get the updated data.

Complete the following steps:

1. Generate Sensor Data over BLE application on QCS using the BGK-RA6E2, HS4001 Sensor, and DA14531 BLE module for FreeRTOS.
2. Modify the **gui_cfg.json** file as mentioned above.
3. Rebuild the project by pressing the Build QCStudio Project option in QCS.
4. Download the ***.srec** file from **Debug/** path and flash the BGK-RA6E2 board.
5. Pair the QC Sandbox mobile application with the board and verify the data.

Files to be modified:

- / gui_cfg.json

Modifications:

The `auto_read` parameter in the **gui_cfg.json** file mentions the time interval (in seconds) at which the request comes from the mobile application. Configuring this value to 0 disables the auto read functionality completely and the user must initiate the data read manually.

```

{
  "gui": {
    "id": "0000",
    "title": "US000 QC Example",
    "version": "0.0.1",
    "tab": [
      {
        "id": "0001",
        "name": "LED",
        "toggle": {
          "id": "0100",
          "type": "uint8_t",
          "name": "LED 1",
          "default": 0
        }
      },
      {
        "id": "0002",
        "name": "HS4001",
        "parameters": {
          "id": "0200",
          "type": "blob",
          "access": "r",
          "list": [
            {
              "id": "0201",
              "name": "TEMPERATURE",
              "units": "C",
              "type": "float",
              "access": "r",
              "auto_read": 0,
              "value": null
            },
            {
              "id": "0202",
              "name": "HUMIDITY",
              "units": "%",
              "type": "float",
              "access": "r",
              "auto_read": 0,
              "value": null
            }
          ]
        }
      },
      {
        "id": "0003",
        "name": "About",
        "parameters": {
          "id": "0300",
          "type": "blob",
          "access": "r",
          "list": [
            {
              "id": "0301",
              "name": "Test Version",
              "type": "string",
              "access": "const",
              "value": null
            }
          ]
        }
      }
    ]
  }
}

```

Code Block 21 gui_cfg.json

Outcome for this exercise:

After flashing the **.srec** file, connect the board with QC Sandbox mobile application over BLE and navigate to the HS4001 page. The user should not see the automatic update for the sensor data. The sensor data should get updated only after pressing the **Read All** button.

10.3.4.6 Using the BLE Mobile Application, Toggle the LED which is Currently ON and OFF

This exercise is to update the onboard LED response for the mobile application action. After this exercise, the LED should toggle for each LED button press on the mobile application. Currently, the button is a simple slider button that can be either at OFF position or ON position. This needs to be modified into a simple button so that with each press, the LED toggle can be visible.

Complete the following steps:

1. Generate the **Sensor Data over BLE** application on QCS using BGK-RA6E2, HS4001 Sensor, and DA14531 BLE module for FreeRTOS.
2. Modify the **gui_cfg.json** and **ble_app.c** files as mentioned above.
3. Rebuild the project by pressing the Build QCStudio Project option in QCS.
4. Download the ***.srec** file from **Debug/** path and flash the BGK-RA6E2 board.
5. Pair the QC Sandbox mobile application with the board and verify the data.

Files to be modified:

- /src/qe_gen/ble/ble_app.c
- /gui_cfg.json

Modifications:

ble_app.c: The handle_write_led() function is responsible for defining the LED state based on requests from the mobile application and data received through BLE. The default code turns OFF the LED if the data received over BLE is 0x00; otherwise, it turns the LED on. This function should be modified to toggle the LED state whenever the handler is invoked.

```
static void handle_write_led(uint16_t id, uint8_t const * const data)
{
    FSP_PARAMETER_NOT_USED(id);
    static bool state = false;

    state = !state;

    if (state == false)
    {
        utils_set_LED(BLUE_LED, BSP_IO_LEVEL_LOW);
    }
    else
    {
        utils_set_LED(BLUE_LED, BSP_IO_LEVEL_HIGH);
    }
}
```

Code Block 22 ble_app.c

gui_cfg.json: This file should be modified to render button for the LED instead of ON and OFF switch.

```

{
  "gui":
  {
    "id": "0000",
    "title": "US000 QC Example",
    "version": "0.0.1",
    "tab":
    [
      {
        "id": "0001",
        "name": "LED",
        "button":
        {
          "id": "0100",
          "name": "LED",
          "ack": false,
          "timeout": 0,
          "read": false
        }
      },
      {
        "id": "0002",
        "name": "HS4001",
        "parameters":
        {
          "id": "0200",
          "type": "blob",
          "access": "r",
          "list":
          [
            {
              "id": "0201",
              "name": "TEMPERATURE",
              "units": "C",
              "type": "float",
              "access": "r",
              "auto_read": 1,
              "value": null
            },
            {
              "id": "0202",
              "name": "HUMIDITY",
              "units": "%",
              "type": "float",
              "access": "r",
              "auto_read": 1,
              "value": null
            }
          ]
        }
      }
    ]
  },
  {
    "id": "0003",
    "name": "About",
    "parameters":
    {
      "id": "0300",
      "type": "blob",
      "access": "r",
      "list":
      [
        {
          "id": "0301",
          "name": "Test Version",
          "type": "string",
          "access": "const",


```

```
    "value": null  
  }  
]  
}  
]  
}  
]  
}
```

Code Block 23 gui_cfg.json

Outcome for this exercise:

The modifications made to **gui_cfg.json** file render buttons on the LED page of QC sandbox application. When ***.srec** is flashed on the BGK-RA6E2 and paired with the QC Sandbox mobile application, on the LED page, button is rendered as follows.



Press this button and the user can see the on-board LED (LED2) toggling for each button press.

11. References

- [RA6E2 - Entry-Line 200MHz Arm® Cortex®-M33 General Purpose Microcontroller | Renesas](#)
- [DA16600MOD - Ultra-Low Power Wi-Fi + Bluetooth® Low Energy Combo Modules for Battery Powered IoT Devices | Renesas](#)
- [HS4001 - Relative Humidity and Temperature Sensor, Digital Output, ±1.5% RH | Renesas](#)
- [US159-DA14531EVZ - Low Power Bluetooth PMOD Board \(Renesas QuickConnect IoT\)](#)

Technical Updates/Technical News

- The latest information can be downloaded from the Renesas Electronics Website.

Website and Support

Renesas Electronics Website - <https://www.renesas.com/>

Inquiries - <https://www.renesas.com/contact/>

12. Ordering Information

Part Number	Description
QC-BEKITPOC2Z	QuickConnect Beginners Kit V2.0

13. Revision History

Revision	Date	Description
1.00	May 8, 2025	Initial release.

IMPORTANT NOTICE AND DISCLAIMER

RENESAS ELECTRONICS CORPORATION AND ITS SUBSIDIARIES ("RENESAS") PROVIDES TECHNICAL SPECIFICATIONS AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD-PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for developers who are designing with Renesas products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. Renesas grants you permission to use these resources only to develop an application that uses Renesas products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Renesas intellectual property or to any third-party intellectual property. Renesas disclaims responsibility for, and you will fully indemnify Renesas and its representatives against, any claims, damages, costs, losses, or liabilities arising from your use of these resources. Renesas' products are provided only subject to Renesas' Terms and Conditions of Sale or other applicable terms agreed to in writing. No use of any Renesas resources expands or otherwise alters any applicable warranties or warranty disclaimers for these products.

(Disclaimer Rev.1.01)

Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,
Koto-ku, Tokyo 135-0061, Japan
www.renesas.com

Contact Information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit www.renesas.com/contact-us/.

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.