

Report No. APR-25-H0111
Date: Jun. 20, 2025

RENESAS SEMICONDUCTOR RELIABILITY REPORT

APPLICATION: High Quality

SERIES: REXFET-1 ANM3

DEVICE: RBA500N10EHWT-2UA01#GFH

Quality Assurance Div.
Renesas Electronics Corporation

Notice

- 1 Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation or any other use of the circuits, software, and information in the design of your product or system. Renesas Electronics disclaims any and all liability for any losses and damages incurred by you or third parties arising from the use of these circuits, software, or information.
- 2 Renesas Electronics hereby expressly disclaims any warranties against and liability for infringement or any other claims involving patents, copyrights, or other intellectual property rights of third parties, by or arising from the use of Renesas Electronics products or technical information described in this document, including but not limited to, the product data, drawings, charts, programs, algorithms, and application examples.
- 3 No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of Renesas Electronics or others.
- 4 You shall be responsible for determining what licenses are required from any third parties, and obtaining such licenses for the lawful import, export, manufacture, sales, utilization, distribution or other disposal of any products incorporating Renesas Electronics products, if required.
- 5 You shall not alter, modify, copy, or reverse engineer any Renesas Electronics product, whether in whole or in part. Renesas Electronics disclaims any and all liability for any losses or damages incurred by you or third parties arising from such alteration, modification, copying or reverse engineering.
- 6 Renesas Electronics products are classified according to the following two quality grades: "Standard" and "High Quality". The intended applications for each Renesas Electronics product depends on the product's quality grade, as indicated below.

"Standard": Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; industrial robots; etc.

"High Quality": Transportation equipment (automobiles, trains, ships, etc.); traffic control (traffic lights); large-scale communication equipment; key financial terminal systems; safety control equipment; etc.

Unless expressly designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not intended or authorized for use in products or systems that may pose a direct threat to human life or bodily injury (artificial life support devices or systems; surgical implantations; etc.), or may cause serious property damage (space system; undersea repeaters; nuclear power control systems; aircraft control systems; key plant systems; military equipment; etc.). Renesas Electronics disclaims any and all liability for any damages or losses incurred by you or any third parties arising from the use of any Renesas Electronics product that is inconsistent with any Renesas Electronics data sheet, user's manual or other Renesas Electronics document.

- 7 No semiconductor product is absolutely secure. Notwithstanding any security measures or features that may be implemented in Renesas Electronics hardware or software products, Renesas Electronics shall have absolutely no liability arising out of any vulnerability or security breach, including but not limited to any unauthorized access to or use of a Renesas Electronics product or a system that uses a Renesas Electronics product. RENESAS ELECTRONICS DOES NOT WARRANT OR GUARANTEE THAT RENESAS ELECTRONICS PRODUCTS, OR ANY SYSTEMS CREATED USING RENESAS ELECTRONICS PRODUCTS WILL BE INVULNERABLE OR FREE FROM CORRUPTION, ATTACK, VIRUSES, INTERFERENCE, HACKING, DATA LOSS OR THEFT, OR OTHER SECURITY INTRUSION ("Vulnerability Issues"). RENESAS ELECTRONICS DISCLAIMS ANY AND ALL RESPONSIBILITY OR LIABILITY ARISING FROM OR RELATED TO ANY VULNERABILITY ISSUES. FURTHERMORE, TO THE EXTENT PERMITTED BY APPLICABLE LAW, RENESAS ELECTRONICS DISCLAIMS ANY AND ALL WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT AND ANY RELATED OR ACCOMPANYING SOFTWARE OR HARDWARE, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE.
- 8 When using Renesas Electronics products, refer to the latest product information (data sheets, user's manuals, application notes, "General Notes for Handling and Using Semiconductor Devices" in the reliability handbook, etc.), and ensure that usage conditions are within the ranges specified by Renesas Electronics with respect to maximum ratings, operating power supply voltage range, heat dissipation characteristics, installation, etc. Renesas Electronics disclaims any and all liability for any malfunctions, failure or accident arising out of the use of Renesas Electronics products outside of such specified ranges.
- 9 Although Renesas Electronics endeavors to improve the quality and reliability of Renesas Electronics products, semiconductor products have specific characteristics, such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Unless designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not subject to radiation resistance design. You are responsible for implementing safety measures to guard against the possibility of bodily injury, injury or damage caused by fire, and/or danger to the public in the event of a failure or malfunction of Renesas Electronics products, such as safety design for hardware and software, including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult and impractical, you are responsible for evaluating the safety of the final products or systems manufactured by you.
- 10 Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. You are responsible for carefully and sufficiently investigating applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive, and using Renesas Electronics products in compliance with all these applicable laws and regulations. Renesas Electronics disclaims any and all liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
- 11 Renesas Electronics products and technologies shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations. You shall comply with any applicable export control laws and regulations promulgated and administered by the governments of any countries asserting jurisdiction over the parties or transactions.
- 12 It is the responsibility of the buyer or distributor of Renesas Electronics products, or any other party who distributes, disposes of, or otherwise sells or transfers the product to a third party, to notify such third party in advance of the contents and conditions set forth in this document.
- 13 This document shall not be reproduced or duplicated in any form or disclosed to any third party, in whole or in part, without prior written consent of Renesas Electronics.
- 14 Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products.

(Note 1) "Renesas Electronics" as used in this document means Renesas Electronics Corporation and also includes its directly or indirectly controlled subsidiaries.

(Note 2) "Renesas Electronics product(s)" means any product developed or manufactured by or for Renesas Electronics.

(Rev.5.0-2 October 2020)

(C)RENESAS Electronics Corporation. All rights reserved.

Q101 Qualification Test Results

[Note : Basically qualification tests were performed using a representative product with the same wafer process and the same package structure .]

Test	#	Reference	Test Conditions	Lots	S.S.	Total	Results (Fail of Total)	Comments: (N/A =Not Applicable)
------	---	-----------	-----------------	------	------	-------	----------------------------	------------------------------------

TEST GROUP A – ACCELERATED ENVIRONMENT STRESS TESTS

PC	A1	JESD22-A113 J-STD-020	SMD only; Moisture Preconditioning for HAST/H3TRB,UHAST/AC,TC,IOL/PTC.	-	-	-	-	N/A Bare Die
HAST	A2	JESD22-A110	Ta=130°C, RH=85%, VDSS=Maximum rating, 96h	-	-	-	-	N/A Bare Die
H3TRB	A2 alt	JESD22-A101	Ta=85°C, 85%RH, VDSS=Maximum rating, 1,000h	-	-	-	-	N/A Bare Die
UHAST	A3	JESD22-A118 or A101	Ta=130°C, RH=85%, 96h	-	-	-	-	N/A Bare Die
AC	A3 alt	JESD22-A102	Ta=121°C, 100%RH, 96h	-	-	-	-	N/A Bare Die
TC	A4	JESD22-A104 Appendix 6	Ta=-55°C to 150°C, 1,000cycles	-	-	-	-	N/A Bare Die
TCHT	A4a	JESD22-A104 Appendix 6	TC Hot Test.	-	-	-	-	N/A Bare Die
TCDT	A4a alt	JESD22-A104 Appendix 6 J-STD-035	TC Delamination Test.	-	-	-	-	N/A Bare Die
IOL	A5	MIL-STD-750 Method 1037	ΔTc=100°C, 15,000cycles	-	-	-	-	N/A Bare Die
PTC	A5 alt	JESD22-A105	Power Temperature Cycling.	-	-	-	-	N/A Bare Die

(C)RENESAS Electronics Corporation. All rights reserved.

Test	#	Reference	Test Conditions	Lots	S.S.	Total	Results (Fail of Total)	Comments: (N/A =Not Applicable)
------	---	-----------	-----------------	------	------	-------	----------------------------	------------------------------------

TEST GROUP B – ACCELERATED LIFETIME SIMULATION TESTS

HTRB	B1	MIL-STD-750-1 M1039	Tch = 175°C, VDSS=Maximum rating, 1,000h	3	77	231	0 of 231	-
ACBV	B1a	MIL-STD-750-1 M1040 Test condition A	AC blocking voltage.	-	-	-	-	N/A Thyristors Only.
SSOP	B1b	MIL-STD-750-1 M1038 condition B (Zeners)	Steady State Operational.	-	-	-	-	N/A Voltage Regulators (Zeners) Only.
HTGB	B2	JESD22-A108	Tch = 175°C, VGSS=+20V, 1,000h	3	77	231	0 of 231	-

TEST GROUP C – PACKAGE ASSEMBLY INTEGRITY TESTS

DPA	C1	AEC Q101-004 Section4	Random sample of parts that have successfully completed H3TRB or HAST and TC.	-	-	-	-	N/A Bare Die
PD	C2	JEDEC JESD22-B100	Physical Dimensions.	-	-	-	-	N/A Bare Die
WBP	C3	MIL-STD-750-2 Method 2037	Wire Bond Pull.	-	-	-	-	N/A Bare Die
WBS	C4	AEC Q101-003 JESD22-B116	Wire Bond Shear Test.	-	-	-	-	N/A Bare Die
DS	C5	MIL-STD-750-2 Method 2017	Die Shear.	-	-	-	-	N/A Bare Die
TS	C6	MIL-STD-750-2 Method 2036	Terminal Strength.	-	-	-	-	N/A Bare Die
RTS	C7	JESD22-B107	Resistance to Solvents.	-	-	-	-	N/A Bare Die
RSH	C8	JESD22-A111 (SMD)	Resistance to Solder Heat.	-	-	-	-	N/A Bare Die

(C)RENESAS Electronics Corporation. All rights reserved.

Test	#	Reference	Test Conditions	Lots	S.S.	Total	Results (Fail of Total)	Comments: (N/A =Not Applicable)
TR	C9	JESD24-3, 24-4, 24-6 as appropriate	Thermal Resistance.	-	-	-	-	N/A Bare Die
SD	C10	JEDEC J-STD-002	Solderability: (>95% coverage)	-	-	-	-	N/A Bare Die
WG	C11	AEC Q005	see AEC-Q005	-	-	-	-	N/A Bare Die
CA	C12	MIL-STD-750-2 Method 2006	Constant Acceleration.	-	-	-	-	N/A Bare Die
VVF	C13	JESD22-B103	Vibration Variable Frequency.	-	-	-	-	N/A Bare Die
MS	C14	JESD22-B104	Mechanical Shock.	-	-	-	-	N/A Bare Die
HER	C15	JEDEC JESD22-A109	Hermeticity.	-	-	-	-	N/A Bare Die

TEST GROUP D – DIE FABRICATION RELIABILITY TESTS

DI	D1	AEC Q101-004 Section3	Dielectric Integrity.	1	5	5	0 of 5	Confirmed by process TEG
----	----	--------------------------	-----------------------	---	---	---	--------	--------------------------

TEST GROUP E – ELECTRICAL VERIFICATION TESTS

EV	E0	JESD22-B101	External Visual.	All	All	All	0 of All	-
TEST	E1	User/Supplier Specification	Pre and Post Stress Electrical Test.	All	All	All	0 of All	-
PV	E2	Individual AEC user specification	Parametric Verification.	3	25	75	0 of 75	-
ESDH	E3	AEC Q101-001	Electrostatic Discharge, Human Body Model.	1	30	30	0 of 30	HBM : C:100pF,R:1.5KΩ,2000V↑

(C)RENESAS Electronics Corporation. All rights reserved.

Test	#	Reference	Test Conditions	Lots	S.S.	Total	Results (Fail of Total)	Comments: (N/A =Not Applicable)
ESDC	E4	AEC Q101-005	Electrostatic Discharge, Charged Device Model.	-	-	-	-	N/A Bare Die
UIS	E5	AEC Q101-004 Section2	UNCLAMPED INDUCTIVE SWITCHING.	1	5	5	0 of 5	-
SC	E6	AEC Q101-006	Short Circuit Characterization.	-	-	-	-	N/A For smart power parts only.

Calculation method of standard failure

• Calculation method of standard failure rate

Operating reliability is decided by inherent reliability of device and environment condition of use (See below).

• Calculation method of standard failure rate (λ)

$$\lambda = \lambda_b \times \pi T \times \pi V \quad (\text{fit})$$

- ③ Power source voltage parameter
(This parameter apply to Si series transistor product and FET only. In case of other product, $\pi V=1$)
- ② Temperature parameter
- ① Basic failure rate

① Basic failure rate (λ_b)

Product Name: RBA500N10EHWT-2UA01 λ_b : 0.59 (Fit)

② Temperature parameter (πT)

$$\pi T = \exp\left(11600 \times Ea \times \left(\frac{1}{273 + 55} - \frac{1}{273 + Ta(j)}\right)\right)$$

Ea : Activation energy

$Tj(Tch)$: junction temperature

πT simplified chart											
$Ea(eV)$	$Tj(Tch)$	40	55	60	65	70	75	80	90	100	110
0.8	πT	0.26	1.00	1.53	2.31	3.45	5.08	7.42	15.30	30.37	58.14

③ Power source voltage parameter (πV) (Si series transistor products, FET only)

$$S = \frac{\text{supply voltage (VCE or VDS)}}{\text{absolute maximum voltage (VCES or VDSS)}}$$

$$S > 0.2 \quad \pi V = \exp(2.86 \times S - 2.29)$$

$$S \leq 0.2 \quad \pi V = 0.18$$

④ MTTF (Mean Time To Failure)

MTTF and failure rate have the following relationship in the contingent failure domain

$$MTTF = \frac{1}{\lambda} \times 10^9 \quad (\text{h})$$

$$MTTF^* = 1,694,915,254 \quad (\text{h})$$

(* $\pi T=1$, $\pi V=1$)

Calculation standard

- Confidence level 60%
- Standard temperature $Tj = 55^\circ\text{C}$
- Use within recommended conditions