

HS-1825AEH

Total Dose Testing

AN1823
Rev 0.00
May 22, 2013

Introduction

This report summarizes the results of a low dose rate (LDR), total dose test of the HS-1825AEH current mode PWM controller. The test was specifically conducted in order to determine the total dose sensitivity under low dose rate conditions.

Both the HS-1825ARH and HS-1825AEH are acceptance tested on a wafer-by-wafer basis to 300krad(Si) at high dose rate (50 to 300 rad(Si)/s). Only the HS-1825AEH is acceptance tested on a wafer-by-wafer basis to 50krad(Si) at low dose rate (0.01 rad(Si)/s). The LDR performance characterization beyond the 50krad(Si) assurance level is included in this report as indicative, but no assurance testing beyond 50krad(Si) is performed at LDR in production.

Reference Documents

- MIL-STD-883G test method 1019.7
- MIL-PRF-38535 (QML)
- [HS-1825AEH](#) data sheet
- DLA Standard Microcircuit Drawing (SMD) [5962-99558](#)

Part Description

The HS-1825ARH, HS-1825AEH pulse width modulator is designed to be used in high frequency switched-mode power supplies and can be used in either current-mode or voltage-mode. It is well suited for single-ended boost converter applications.

Device features include a precision voltage reference, low power start-up circuit, high frequency oscillator, wide-band error amplifier, and fast current-limit comparator. The use of proprietary process capabilities and unique design techniques results in fast propagation delay times and high output current over a wide range of output voltages.

Constructed with the Intersil Rad Hard Silicon Gate (RSG), Dielectric Isolation BiCMOS process, the HS-1825ARH, HS-1825AEH have been specifically designed to provide highly

reliable performance when exposed to harsh radiation environments.

- Electrically screened to DLA SMD [5962-99558](#)
- QML qualified per MIL-PRF-38535 requirements
- Maximum high dose rate total dose 300krad(Si)
- Vertical architecture provides low dose rate immunity
- Dielectric isolation process (RSG) provides latch-up immunity
- Low start-up current. 100µA (Typ)
- Fast propagation delay 80ns (Typ)
- 12V to 30V operation
- 1A (peak-to-peak) dual output drive capability
- 5.1V reference
- Undervoltage lock-out (UVLO)
- Programmable soft-start
- Switching frequencies 500kHz
- Latched overcurrent comparator with full cycle restart




FIGURE 1. HS-1825AEH CONCEPTUAL BLOCK DIAGRAM

The HS-1825AEH is implemented in Intersil's dielectrically isolated radiation hardened silicon gate BiCMOS technology (RSG). Active devices include 30V CMOS and complementary bipolar transistors. The process in production is under MIL PRF 38535 certification and is used for a range of space qualified products.


Test Description

Irradiation Facilities

Low dose rate testing was done at Intersil's low dose rate irradiation facility located in Palm Bay, FL. This facility was built expressly for supporting production (LDR assurance testing) of Intersil products. A description of the Intersil LDR facility can be found on the Intersil web site. The facility uses a ^{60}Co source and maintains a 10mrad(Si)/s flux by device positioning relative to the source. Devices are packaged in PbAl boxes to shield them against low energy secondary gamma radiation, as required by MIL STD 883.

Test Fixturing

Figure 2 on page 3 shows the configuration used for biased irradiation in conformance with Standard Microcircuit Drawing (SMD) 5962-99558. This configuration was used for the biased low dose rate irradiation. The unbiased low dose rate irradiation was carried out with all pins grounded.



NOTE: V1 and V2 are separate supplies.
V1, V2 = 15V, ±0.5V
R1 = 6kΩ, ±5%, R2 = 10kΩ, ±5%, R3 = 10kΩ, ±1%
C1 = 250pF, ±5%, C2 = 1000pF, ±5%, C3 = 1μF, ±10%
C4 = 0.1μF, ±10%

FIGURE 2. IRRADIATION BIAS CONFIGURATION FOR THE HS-1825AEH PER STANDARD MICROCIRCUIT DRAWING (SMD) 5962-99558, AS USED FOR BOTH LOW DOSE RATE IRRADIATION REPORTED IN THIS DOCUMENT

Characterization Equipment and Procedures

All electrical testing was performed outside the irradiator using the production automated test equipment (ATE) with data-logging of all parameters at each downpoint. Electrical testing was performed at room temperature.

Experimental Matrix

The experimental matrix consists of two irradiation groups; biased and unbiased, and a sequence of dose downpoints. Units were cumulatively dosed up to the maximum dose listed; Table 1 summarizes the test points and identifies the number of units tested for each condition. The number of samples in the unbiased condition changes from 18 to 10. This was due to electrical overstress damage incurred during testing the devices.

TABLE 1. NUMBER OF UNITS TESTED AT EACH CONDITION

	0 krad	50 krad	100 krad	150 krad	200 krad
Biased	18	18	18	18	–
Unbiased	18	18	10	10	10

NOTE: The dose downpoints are sequential on the units left to right.

Samples of the HS-1825AEH were drawn from pre-production inventory for the HS-1825ARH and were packaged in the standard hermetic 16-pin ceramic flatpack (CFP) production package. Samples were processed through the standard burn-in cycle before irradiation, as required by MIL-STD-883 and were screened to the SMD 5962-99558 limits at room, low and high temperature before the radiation testing.

SMD Electrical Parameter Results

Results for the key parameters are presented in Figures 3 through 37 for all downpoints. The plots show the median parameter values as connected points against total dose. The median values are augmented with markers at each of the extremes recorded. Table 2 lists the SMD parameters, limits, plus

chart number and page. Some redundant test data and SMD parameters were omitted from the charts. These omitted charts added no information beyond those included.

TABLE 2. SMD PARAMETERS, LIMITS PLUS CHART NUMBER AND PAGE

SMD ELECTRICAL PARAMETER	SYMBOL	PRE/POST RADIATION LIMITS +25°C			CHART NO. & PG.
		MIN	MAX	UNIT	
Reference Output Voltage	V _{REF}	5.05/5.00	5.15/5.20	V	3, 5
Reference Line Regulation	V _{LINE}	-15/-20	15/20	mV	4, 5
Reference Load Regulation	V _{LOAD}	-25/-50	25/50	mV	5, 6
Reference Total Output Variation	V _{OM}	5.00/4.95	5.20/5.25	mV	
Reference Short Circuit Current	I _{SC}	30/20		mA	6, 6
Oscillatory Initial Accuracy	F _O	350/300	425	kHz	7, 6
Oscillatory Voltage Stability	dF _O /dV	-2/-3	2/3	%	8, 6
Oscillatory Total Variation	F _{OM}	350/300	425	kHz	
Clock Out High Voltage	V _{CLKH}	4.00/3.75		V	9, 7
Clock Out Low Voltage	V _{CLKL}		0.2	V	10, 7
E/A Input Offset Voltage	V _{OS}	-10	10	mV	11, 7
E/A Input Bias Current	I _{IB}	-1	1	μA	12, 7
E/A Amplifier Input Offset Current	I _{OS}	-4	4	μA	13, 8
E/A Open Loop Gain	A _{VOL}	60		dB	14, 8
E/A Common Mode Rejection Ratio	CMRR	65		dB	15, 8
E/A Power Supply Rejection Ratio	PSRR	80		dB	16, 8
E/A Output Sink Current	I _{OSK}	1		mA	17, 9
E/A Output Source Current	I _{OSC}	-0.5		mA	18, 9
E/A Output High Voltage	V _{OH1}	4.0		V	19, 9
E/A Output Low Voltage	V _{OL1}		1.0	V	20, 9
PWM Ramp Bias Current	I _{RAMP}		-8	μA	21, 10
PWM Duty Cycle Range	D _{CRNG}	40		%	22, 10
PWM E/A Out Zero DC Threshold	V _{TH}	0.89		V	23, 10
Soft-Start Charge Current	I _{CHG}	8	20/25	μA	24, 10
Soft-Start Discharge Current	I _{DCHG}	0.1	0.5	mA	25, 11
Overcurrent Restart Threshold	V _{RS}		0.5	V	26, 11
I _{LIM} Bias Current	I _{BLIM}		15	μA	27, 11
Current Limit Threshold	V _{LIMIT}	0.95/0.88	1.10	V	28, 11
Overcurrent Threshold	V _{OVER}	1.14/1.08	1.26	V	29, 12
Output Low Saturation 1	V _{SATL1}		0.8	V	
Output Low Saturation 2	V _{SATL2}		2.2	V	30, 12
Output High Saturation 1	V _{SATH1}	10		V	
Output High Saturation 2	V _{SATH2}	9		V	31, 12
UVLO Output Low Saturation	V _{OLS}		1.2	V	32, 12

TABLE 2. SMD PARAMETERS, LIMITS PLUS CHART NUMBER AND PAGE (Continued)

SMD ELECTRICAL PARAMETER	SYMBOL	PRE/POST RADIATION LIMITS +25°C			CHART NO. & PG.
		MIN	MAX	UNIT	
UVLO Start Threshold	V_{START}	8.4	9.6	V	33, 13
UVLO Stop Threshold	V_{STOP}		9.6	V	34, 13
UVLO Hysteresis	V_{HYS}	0.3	1.2	V	35, 13
Start-Up Current	I_{SU}		300	μA	36, 13
Supply Current	I_{CC}		36	mA	37, 14

NOTE: Not all parameters have charts.

Parameter Results




FIGURE 3. REFERENCE OUTPUT VOLTAGE, V_{REF} . THE REFERENCE TOTAL OUTPUT VARIATION, V_{OM} , CLOSELY MATCHES V_{REF} , SO IT IS NOT INCLUDED AS A SEPARATE CHART












FIGURE 4. REFERENCE VOLTAGE LINE REGULATION, V_{LINE}

Parameter Results (Continued)

FIGURE 5. REFERENCE VOLTAGE LOAD REGULATION, V_{LOAD} FIGURE 6. REFERENCE SHORT CIRCUIT CURRENT, I_{SC} FIGURE 7. OSCILLATOR INITIAL FREQUENCY, F_0 FIGURE 8. OSCILLATOR FREQUENCY VOLTAGE STABILITY, dF_0/dV

Parameter Results (Continued)

FIGURE 9. CLOCK OUTPUT HIGH VOLTAGE, V_{CLKH} FIGURE 10. CLOCK LOW OUTPUT VOLTAGE, V_{CLKL} FIGURE 11. ERROR AMPLIFIER OFFSET VOLTAGE, V_{OS} FIGURE 12. ERROR AMPLIFIER INPUT BIAS CURRENT, I_{IB}

Parameter Results (Continued)




FIGURE 13. ERROR AMPLIFIER INPUT OFFSET CURRENT, I_{OS}




FIGURE 14. ERROR AMPLIFIER OPEN LOOP GAIN, A_{VOL}




FIGURE 15. ERROR AMPLIFIER COMMON MODE REJECTION RATIO (CMRR)












FIGURE 16. ERROR AMPLIFIER POWER SUPPLY REJECTION RATIO (PSRR)





Parameter Results (Continued)

FIGURE 17. ERROR AMPLIFIER OUTPUT SINK CURRENT (I_{OSK})FIGURE 18. ERROR AMPLIFIER OUTPUT SOURCE CURRENT (I_{OSC})FIGURE 19. ERROR AMPLIFIER OUTPUT HIGH VOLTAGE (V_{OH1})FIGURE 20. ERROR AMPLIFIER OUTPUT LOW VOLTAGE (V_{OL1})





Parameter Results (Continued)

FIGURE 21. PWM RAMP BIAS CURRENT (I_{RAMP})FIGURE 22. PWM DUTY CYCLE RANGE (D_{CRNG}) FOR OUTPUT AFIGURE 23. PWM ERROR AMPLIFIER OUTPUT ZERO THRESHOLD VOLTAGE (V_{TH})FIGURE 24. SOFT START CHARGING CURRENT (I_{CHG})





Parameter Results (Continued)

FIGURE 25. SOFT-START DISCHARGING CURRENT (I_{DCHG})FIGURE 26. OVERCURRENT RESTART THRESHOLD VOLTAGE (V_{RS})FIGURE 27. CURRENT LIMIT BIAS CURRENT AT 2V (I_{BLIM})FIGURE 28. CURRENT LIMIT THRESHOLD VOLTAGE (V_{LIMIT})

Parameter Results (Continued)

FIGURE 29. OVERCURRENT THRESHOLD VOLTAGE (V_{OVER})FIGURE 30. OUTPUT A LOW SATURATION VOLTAGE AT $I_{OUT} = 200\text{mA}$ (V_{SATL2})FIGURE 31. OUTPUT A HIGH SATURATION VOLTAGE AT $I_{OUT} = 200\text{mA}$ (V_{SATH2})FIGURE 32. UNDERVOLTAGE LOCK-OUT (UVLO) OUTPUT SATURATION VOLTAGE (V_{OLs})

Parameter Results (Continued)

FIGURE 33. UNDERVOLTAGE LOCK-OUT START THRESHOLD (V_{START})FIGURE 34. UNDERVOLTAGE LOCK-OUT STOP THRESHOLD (V_{STOP})FIGURE 35. UNDERVOLTAGE LOCK-OUT HYSTERESIS VOLTAGE (V_{HYS})FIGURE 36. START-UP SUPPLY CURRENT (I_{SU})

Parameter Results (Continued)




FIGURE 37. OPERATING SUPPLY CURRENT (I_{CC})

Discussion and Conclusion

The low dose rate downpoints of the HS-1825AEH were tested to the SMD post-irradiation limits. All parameters passed the post radiation limits at the 50krad(Si) low dose rate assurance level. The current limit (V_{LIMIT}) and overcurrent (V_{OVER}) threshold voltages (Figures 28 and 29), dropped just below the post radiation specifications at 150krad(Si) for the biased condition. The unbiased case for these parameters showed little movement through the 200krad(Si) dose point.

The data clearly indicates that the part is capable of maintaining specified operation up to the 50krad(Si) level of radiation assurance testing for the "EH" version of the part. Further, the data indicates considerable margin with performance being maintained up to 100krad(Si). At 150krad(Si), two parameters for the biased configuration, the current limit threshold (V_{LIMIT}) and the overcurrent threshold (V_{OVER}) begin to drop just below specification. These two parameters in the biased condition are shown to be the most sensitive to the LDR environment.

Notice

1. Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation or any other use of the circuits, software, and information in the design of your product or system. Renesas Electronics disclaims any and all liability for any losses and damages incurred by you or third parties arising from the use of these circuits, software, or information.
 2. Renesas Electronics hereby expressly disclaims any warranties against and liability for infringement or any other claims involving patents, copyrights, or other intellectual property rights of third parties, by or arising from the use of Renesas Electronics products or technical information described in this document, including but not limited to, the product data, drawings, charts, programs, algorithms, and application examples.
 3. No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of Renesas Electronics or others.
 4. You shall not alter, modify, copy, or reverse engineer any Renesas Electronics product, whether in whole or in part. Renesas Electronics disclaims any and all liability for any losses or damages incurred by you or third parties arising from such alteration, modification, copying or reverse engineering.
 5. Renesas Electronics products are classified according to the following two quality grades: "Standard" and "High Quality". The intended applications for each Renesas Electronics product depends on the product's quality grade, as indicated below.

"Standard": Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; industrial robots; etc.

"High Quality": Transportation equipment (automobiles, trains, ships, etc.); traffic control (traffic lights); large-scale communication equipment; key financial terminal systems; safety control equipment; etc.

Unless expressly designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not intended or authorized for use in products or systems that may pose a direct threat to human life or bodily injury (artificial life support devices or systems; surgical implantations; etc.), or may cause serious property damage (space system; undersea repeaters; nuclear power control systems; aircraft control systems; key plant systems; military equipment; etc.). Renesas Electronics disclaims any and all liability for any damages or losses incurred by you or any third parties arising from the use of any Renesas Electronics product that is inconsistent with any Renesas Electronics data sheet, user's manual or other Renesas Electronics document.
 6. When using Renesas Electronics products, refer to the latest product information (data sheets, user's manuals, application notes, "General Notes for Handling and Using Semiconductor Devices" in the reliability handbook, etc.), and ensure that usage conditions are within the ranges specified by Renesas Electronics with respect to maximum ratings, operating power supply voltage range, heat dissipation characteristics, installation, etc. Renesas Electronics disclaims any and all liability for any malfunctions, failure or accident arising out of the use of Renesas Electronics products outside of such specified ranges.
 7. Although Renesas Electronics endeavors to improve the quality and reliability of Renesas Electronics products, semiconductor products have specific characteristics, such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Unless designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not subject to radiation resistance design. You are responsible for implementing safety measures to guard against the possibility of bodily injury, injury or damage caused by fire, and/or danger to the public in the event of a failure or malfunction of Renesas Electronics products, such as safety design for hardware and software, including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult and impractical, you are responsible for evaluating the safety of the final products or systems manufactured by you.
 8. Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. You are responsible for carefully and sufficiently investigating applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive, and using Renesas Electronics products in compliance with all these applicable laws and regulations. Renesas Electronics disclaims any and all liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
 9. Renesas Electronics products and technologies shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations. You shall comply with any applicable export control laws and regulations promulgated and administered by the governments of any countries asserting jurisdiction over the parties or transactions.
 10. It is the responsibility of the buyer or distributor of Renesas Electronics products, or any other party who distributes, disposes of, or otherwise sells or transfers the product to a third party, to notify such third party in advance of the contents and conditions set forth in this document.
 11. This document shall not be reprinted, reproduced or duplicated in any form, in whole or in part, without prior written consent of Renesas Electronics.
 12. Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products.
- (Note 1) "Renesas Electronics" as used in this document means Renesas Electronics Corporation and also includes its directly or indirectly controlled subsidiaries.
- (Note 2) "Renesas Electronics product(s)" means any product developed or manufactured by or for Renesas Electronics.

(Rev.4.0-1 November 2017)



SALES OFFICES

Renesas Electronics Corporation

<http://www.renesas.com>

Refer to "<http://www.renesas.com/>" for the latest and detailed information.

Renesas Electronics America Inc.
1001 Murphy Ranch Road, Milpitas, CA 95035, U.S.A.
Tel: +1-408-432-8888, Fax: +1-408-434-5351

Renesas Electronics Canada Limited
9251 Yonge Street, Suite 8309 Richmond Hill, Ontario Canada L4C 9T3
Tel: +1-905-237-2004

Renesas Electronics Europe Limited
Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5FH, U.K
Tel: +44-1628-651-700, Fax: +44-1628-651-804

Renesas Electronics Europe GmbH
Arcadiastrasse 10, 40472 Düsseldorf, Germany
Tel: +49-211-6503-0, Fax: +49-211-6503-1327

Renesas Electronics (China) Co., Ltd.
Room 1709 Quantum Plaza, No.27 ZhichunLu, Haidian District, Beijing, 100191 P. R. China
Tel: +86-10-8235-1155, Fax: +86-10-8235-7679

Renesas Electronics (Shanghai) Co., Ltd.
Unit 301, Tower A, Central Towers, 555 Langao Road, Putuo District, Shanghai, 200333 P. R. China
Tel: +86-21-2226-0888, Fax: +86-21-2226-0999

Renesas Electronics Hong Kong Limited
Unit 1601-1611, 16/F., Tower 2, Grand Century Place, 193 Prince Edward Road West, Mongkok, Kowloon, Hong Kong
Tel: +852-2265-6688, Fax: +852-2886-9022

Renesas Electronics Taiwan Co., Ltd.
13F, No. 363, Fu Shing North Road, Taipei 10543, Taiwan
Tel: +886-2-8175-9600, Fax: +886-2-8175-9670

Renesas Electronics Singapore Pte. Ltd.
80 Bendemeer Road, Unit #06-02 Hyflux Innovation Centre, Singapore 339949
Tel: +65-6213-0200, Fax: +65-6213-0300

Renesas Electronics Malaysia Sdn.Bhd.
Unit 1207, Block B, Menara Amcorp, Amcorp Trade Centre, No. 18, Jln Persiaran Barat, 46050 Petaling Jaya, Selangor Darul Ehsan, Malaysia
Tel: +60-3-7955-9390, Fax: +60-3-7955-9510

Renesas Electronics India Pvt. Ltd.
No.777C, 100 Feet Road, HAL 2nd Stage, Indiranagar, Bangalore 560 038, India
Tel: +91-80-67208700, Fax: +91-80-67208777

Renesas Electronics Korea Co., Ltd.
17F, KAMCO Yangjae Tower, 262, Gangnam-daero, Gangnam-gu, Seoul, 06265 Korea
Tel: +82-2-558-3737, Fax: +82-2-558-5338