

[Notes] RX Family

R20TS1087EJ0100

Rev.1.00

Feb. 05, 2025

Clock Synchronous Control Module for EEPROM

Access Firmware Integration Technology

RX Driver Package

Outline

When using the products in the title, note the following point.

1. The contents of the EEPROM Access Clock Synchronous Control Module^(*) Rev.3.10 included in the individual package⁽²⁾ and the RX Driver Package are different.

Note 1: Hereafter, it says an EEPROM SPI FIT module.

Note 2: A module package that can be obtained from a web page separately from the RX Driver Package (r01an2325xx0310-rx-serial.zip)

1. The contents of the EEPROM Access Clock Synchronous Control Module Rev.3.10 included in the individual package and the RX Driver Package are different.

1.1 Applicable Products

(1) EEPROM SPI FIT module

The applicable revision numbers and document numbers are as follows:

Table 1.1 EEPROM SPI FIT module applicable products

Revision number of the EEPROM SPI FIT module	Document number
Rev.3.10	R01AN2325EJ0310

(2) RX Driver Package

The EEPROM SPI FIT module in (1) is also included in the RX Driver Package.

The product names and revision numbers of the applicable RX Driver Package and the revision numbers of the EEPROM SPI FIT module are as follows:

Table 1.2 EEPROM SPI FIT module applicable products

RX Driver Package product name	RX Driver Package revision number	Document number	Revision number of the included EEPROM SPI FIT module
RX Family RX Driver Package Ver.1.45	Rev.1.45	R01AN7470xx0145	Rev.3.10
RX Family RX Driver Package Ver.1.44	Rev.1.44	R01AN7446xx0144	Rev.3.10
RX Family RX Driver Package Ver.1.42	Rev.1.42	R01AN7163xx0142	Rev.3.10
RX Family RX Driver Package Ver.1.41	Rev.1.41	R01AN6907xx0141	Rev.3.10
RX Family RX Driver Package Ver.1.40	Rev.1.40	R01AN6906xx0140	Rev.3.10
RX Family RX Driver Package Ver.1.39	Rev.1.39	R01AN6905xx0139	Rev.3.10
RX Family RX Driver Package Ver.1.37	Rev.1.37	R01AN6721xx0137	Rev.3.10

1.2 Applicable Devices

RX110, RX111, RX113, RX130, RX13T, and RX140 groups

RX230, RX231, RX23E-A, RX23E-B, RX23T, RX23W, RX24T, RX24U, RX26T, RX260, and RX261 groups

RX64M, RX651, RX65N, RX660, RX66N, RX66T, and RX671 groups

RX71M, RX72M, RX72N, and RX72T groups

1.3 Details and Conditions

The EEPROM SPI FIT module are different for the RX Driver Package and the individual package as follows.

r_eeeprom_spi_config.h in RX Driver Package (Line 118 to 122):

```
/* The #defines specify the ports used for SS#. */
#define EEPROM_SPI_CS_DEV0_CFG_PORTNO ('C') /* Device 0 Port Number :
EEPROM SS# */
#define EEPROM_SPI_CS_DEV0_CFG_BITNO ('0') /* Device 0 Bit Number :
EEPROM SS# */
#define EEPROM_SPI_CS_DEV1_CFG_PORTNO ('C') /* Device 1 Port Number :
EEPROM SS# */
#define EEPROM_SPI_CS_DEV1_CFG_BITNO ('0') /* Device 1 Bit Number :
EEPROM SS# */
```

r_eeeprom_spi_config.h in individual package (Line 118 to 125):

```
/* The macros to specify the ports used for SS#.
Default value 'X' is for reference only, If this default value is kept,
then the code
support for device port will be temporarily disabled until user assigns a
value of port
used for SS# according to a device. */
#define EEPROM_SPI_CS_DEV0_CFG_PORTNO ('X') /* Device 0 Port Number :
EEPROM SS# */
#define EEPROM_SPI_CS_DEV0_CFG_BITNO ('0') /* Device 0 Bit Number :
EEPROM SS# */
#define EEPROM_SPI_CS_DEV1_CFG_PORTNO ('X') /* Device 1 Port Number :
EEPROM SS# */
#define EEPROM_SPI_CS_DEV1_CFG_BITNO ('0') /* Device 1 Bit Number :
EEPROM SS# */
```

r_eeeprom_spi_dev_port.h in RX Driver Package (Line 158 to 164):

```
#elif (('X' == EEPROM_SPI_CS_DEV0_CFG_PORTNO) || ('x' ==
EEPROM_SPI_CS_DEV0_CFG_PORTNO))
#define EEPROM_SPI_CS_DEV0_CFG_PORTNO_SFR X
#elif (('Y' == EEPROM_SPI_CS_DEV0_CFG_PORTNO) || ('y' ==
EEPROM_SPI_CS_DEV0_CFG_PORTNO))
#define EEPROM_SPI_CS_DEV0_CFG_PORTNO_SFR Y
#elif (('Z' == EEPROM_SPI_CS_DEV0_CFG_PORTNO) || ('z' ==
EEPROM_SPI_CS_DEV0_CFG_PORTNO))
#define EEPROM_SPI_CS_DEV0_CFG_PORTNO_SFR Z
#endif
```

r_eeeprom_spi_dev_port.h in individual package (Line 159 to 161):

```
#elif (('X' == EEPROM_SPI_CS_DEV0_CFG_PORTNO) || ('x' ==
EEPROM_SPI_CS_DEV0_CFG_PORTNO))
    #define EEPROM_SPI_CS_DEV0_CFG_PORTNO_SFR    X
#endif
```

r_eeeprom_spi_dev_port.h in RX Driver Package (Line 278 to 284):

```
#elif (('X' == EEPROM_SPI_CS_DEV1_CFG_PORTNO) || ('x' ==
EEPROM_SPI_CS_DEV1_CFG_PORTNO))
    #define EEPROM_SPI_CS_DEV1_CFG_PORTNO_SFR    X
    #elif (('Y' == EEPROM_SPI_CS_DEV1_CFG_PORTNO) || ('y' ==
EEPROM_SPI_CS_DEV1_CFG_PORTNO))
        #define EEPROM_SPI_CS_DEV1_CFG_PORTNO_SFR    Y
    #elif (('Z' == EEPROM_SPI_CS_DEV1_CFG_PORTNO) || ('z' ==
EEPROM_SPI_CS_DEV1_CFG_PORTNO))
        #define EEPROM_SPI_CS_DEV1_CFG_PORTNO_SFR    Z
#endif
```

r_eeeprom_spi_dev_port.h in individual package (Line 275 to 277):

```
#elif (('X' == EEPROM_SPI_CS_DEV1_CFG_PORTNO) || ('x' ==
EEPROM_SPI_CS_DEV1_CFG_PORTNO))
    #define EEPROM_SPI_CS_DEV1_CFG_PORTNO_SFR    X
#endif
```

In addition, the following contents have been added in the individual package.

r_eeeprom_spi_dev_port.h (Line 357 to 362):

```
/* ---- Temporary disable support for code without target device port ----
*/

#if (defined(EEPROM_SPI_CFG_DEV0_INCLUDED) && ('X' ==
EEPROM_SPI_CS_DEV0_CFG_PORTNO)) ¥

    || (defined(EEPROM_SPI_CFG_DEV1_INCLUDED) && ('X' ==
EEPROM_SPI_CS_DEV1_CFG_PORTNO))

#define EEPROM_SPI_TEMPORARY_DISABLE_DEV_PORT

#endif /* #if (defined(EEPROM_SPI_CFG_DEV0_INCLUDED) && ('X' ==
EEPROM_SPI_CS_DEV0_CFG_PORTNO)) ¥

    || (defined(EEPROM_SPI_CFG_DEV1_INCLUDED) && ('X' ==
EEPROM_SPI_CS_DEV1_CFG_PORTNO)) */
```

r_eeeprom_spi_dev_port_gpio.c (Line 60, 61):

```
/* Check the value of the port is usable or not */
#if !defined(EEPROM_SPI_TEMPORARY_DISABLE_DEV_PORT)
```

r_eeeprom_spi_dev_port_gpio.c (Line 290 to 315):

```
#else
    #warning "Please select a port number assigned to SS# to enable code
    support for device port. Check in file r_eeeprom_spi_config.h"
void r_eeeprom_spi_cs_init(uint8_t devno)
{
    /* This is dummy function. */
    R_BSP_NOP();
} /* End of function r_eeeprom_spi_cs_init() */

void r_eeeprom_spi_set_cs(uint8_t devno, uint8_t lv)
{
    /* This is dummy function. */
    R_BSP_NOP();
} /* End of function r_eeeprom_spi_set_cs() */

void r_eeeprom_spi_cs_reset(uint8_t devno)
{
    /* This is dummy function. */
    R_BSP_NOP();
} /* End of function r_eeeprom_spi_cs_reset() */

eeeprom_status_t r_eeeprom_spi_wait_lp(uint8_t unit)
{
    /* This is dummy function. */
    return EEPROM_SPI_SUCCESS;
} /* End of function r_eeeprom_spi_wait_lp() */
#endif /* #if !defined(EEPROM_SPI_TEMPORARY_DISABLE_DEV_PORT) */
```

r_eeeprom_spi_dev_port_iodefne.c (Line 61, 62):

```
/* Check the value of the port is usable or not */
#if !defined(EEPROM_SPI_TEMPORARY_DISABLE_DEV_PORT)
```

r_eeeprom_spi_dev_port_iodefine.c (Line 332 to 357):

```
#else
    #warning "Please select a port number assigned to SS# to enable code
    support for device port. Check in file r_eeeprom_spi_config.h"
void r_eeeprom_spi_cs_init(uint8_t devno)
{
    /* This is dummy function. */
    R_BSP_NOP();
} /* End of function r_eeeprom_spi_cs_init() */

void r_eeeprom_spi_set_cs(uint8_t devno, uint8_t lv)
{
    /* This is dummy function. */
    R_BSP_NOP();
} /* End of function r_eeeprom_spi_set_cs() */

void r_eeeprom_spi_cs_reset(uint8_t devno)
{
    /* This is dummy function. */
    R_BSP_NOP();
} /* End of function r_eeeprom_spi_cs_reset() */

eeeprom_status_t r_eeeprom_spi_wait_lp(uint8_t unit)
{
    /* This is dummy function. */
    return EEPROM_SPI_SUCCESS;
} /* End of function r_eeeprom_spi_wait_lp() */
#endif /* #if !defined(EEPROM_SPI_TEMPORARY_DISABLE_DEV_PORT) */
```

1.4 Permanent Measures

Please use individual package.

<https://www.renesas.com/en/document/scd/rx-family-clock-synchronous-control-module-eeeprom-access-firmware-integration-technology>

Or please use RX Driver Package Ver.1.46 or more.

Revision History

Rev.	Date	Description	
		Page	Summary
1.00	Feb.05.25	-	First edition issued

Renesas Electronics has used reasonable care in preparing the information included in this document, but Renesas Electronics does not warrant that such information is error free. Renesas Electronics assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.

The past news contents have been based on information at the time of publication. Now changed or invalid information may be included.

The URLs in the Tool News also may be subject to change or become invalid without prior notice.

Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,
Koto-ku, Tokyo 135-0061, Japan
www.renesas.com

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.

Contact information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit:
www.renesas.com/contact/